

California Environmental Quality Act Guidelines Update

Proposed Thresholds of Significance

November 2, 2009

Table of Contents

Secti	on	Page
1	Introduction	1
1.1 1.2	BAAQMD/CEQA Regulatory Authority Justification for Updating CEQA Thresholds	1
2	Greenhouse Gas Thresholds	6
2.2	Proposed Thresholds of Significance	6
2.3	Justification and Substantial Evidence Supporting Thresholds	6
2.3	3.1 Scientific and Regulatory Justification	7
2.3	B.2 Project-Level GHG Thresholds	9
2.3	B.3 Plan-Level GHG Thresholds	
2.3	Climate Action Plans	
2.3	3.5 Stationary Source GHG Threshold	
2.3	S.6 Summary of Justification for GHG Thresholds	
3	Community Risk and Hazard Thresholds	29
3 7	Proposed Thresholds of Significance	30
3 3	Integration and Substantial Evidence Supporting Thresholds	31
3.3	Construction, Land Use and Stationary Source Risk and Hazard	
	Thresholds	
3.3	3.2 Cumulative Risk and Hazard Thresholds	
3.3	B.3 Plan-Level Risk and Hazard Thresholds	
3.3	Community Risk Reduction Plans	
4	Criteria Pollutant Thresholds	38
1 ~	Proposed Thresholds of Significance	20
4.2	Internet Substantial Evidence Supporting Thresholds	38
4 3	Project Construction Criteria Pollutant Thresholds	38
4 3	2 Project Operation Criteria Pollutant Thresholds	39
4.3	Local Carbon Monoxide Thresholds	40
4.3	Plan-Level Criteria Pollutant Thresholds	40
5	Odor Thresholds	41
5 7	Proposed Thresholds of Significance	<u>4</u> 1
5.3	Justification and Substantial Evidence Supporting Thresholds	41
Refe	erences	43

List of Tables

Table 1 – Proposed Air Quality CEQA Thresholds of Significance	4
Table 2 – California 1990, 2002-2004, and 2020 Land Use Sector GHG ¹ 1	4
Table 3 – 2020 Land Use Sector GHG Emission Reductions from State Regulations and AB 32 Measures 1	5
Table 4 – SFBAAB 1990, 2007, and 2020 Land Use Sector GHG Emissions Inventories and Projections (MMT CO2e/yr) 1	6
Table 5 – Operational GHG Threshold Sensitivity Analysis 1	9
Table 6 – California 2020 GHG Emissions, Population Projections and GHG Efficiency Thresholds - Land Use Inventory Sectors 2	.0
Table 7 – California 2020 GHG Emissions, Population Projections and GHG Efficiency Thresholds - All Inventory Sectors 2	2
Table 8 – Statistical Summary of Population-Weighted Ambient Cancer Risk	0
Table 9 – Screening Distances for Potential Odor Sources	2

List of Figures

Proposed Air Quality CEQA Thresholds of Significance

1 INTRODUCTION

Bay Area Air Quality Management District (BAAQMD or Air District) staff analyzed various options for California Environmental Quality Act (CEQA) air quality thresholds of significance for use within BAAQMD's jurisdiction. The analysis and evaluation undertaken by Air District staff is documented in the *Revised Draft Options and Justification Report – California Environmental Quality Act Thresholds of Significance* (Draft Options Report) (BAAQMD October 2009).

Air District staff hosted public workshops in February, April, September and October 2009 at several locations around the Bay Area. In addition, Air District staff met with regional stakeholder groups to discuss and receive input on the threshold options being evaluated. Throughout the course of the public workshops and stakeholder meetings Air District staff received many comments on the various options under consideration. Based on comments received and additional staff analysis, the threshold options and staff-recommended thresholds were further refined. The culmination of this year-long effort is presented in this Report as the Air District staff's proposed air quality thresholds of significance. The proposed thresholds presented herein are intended to replace all of the Air District's currently recommended thresholds. The proposed air quality thresholds of significance are provided in Table 1 at the end of this introduction.

1.1 BAAQMD/CEQA REGULATORY AUTHORITY

The BAAQMD has direct and indirect regulatory authority over sources of air pollution in the San Francisco Bay Area Air Basin (SFBAAB). CEQA requires that public agencies consider the potential adverse environmental impacts of any project that a public agency proposes to carry out, fund or approve. CEQA requires that a lead agency prepare an Environmental Impact Report (EIR) whenever it can be fairly argued (the "fair argument" standard), based on substantial evidence,¹ that a project may have a significant effect² on the environment, even if there is substantial evidence to the contrary (CEQA Guidelines §15064). CEQA requires that the lead agency review not only a project's direct effects on the environment, but also the cumulative impacts of a project and other projects causing related impacts. When the incremental effect of a project is cumulatively considerable,

¹ "Substantial evidence" includes facts, reasonable assumptions predicated upon facts, or expert opinions supported by facts, but does not include argument, speculation, unsubstantiated opinion or narrative, evidence that is clearly inaccurate or erroneous, or evidence of social or economic impacts that do not contribute to, or are not caused by, physical impacts on the environment. Cal. Pub. Res. C. §21080(c); *see also* CEQA Guidelines §15384.

² A "significant effect" on the environment is defined as a "substantial, or potentially substantial, adverse change in the environment." Cal. Pub. Res. C. §21068; *see also* CEQA Guidelines §15382.

the lead agency must discuss the cumulative impacts in an EIR. (CEQA Guidelines §15064).

The "fair argument" standard refers to whether a fair argument can be made that a project may have a significant effect on the environment (*No Oil, Inc. v. City of Los Angeles* (1974) 13 Cal.3d 68, 84). The fair argument standard is generally considered a low threshold requirement for preparation of an EIR. The legal standards reflect a preference for requiring preparation of an EIR and for "resolving doubts in favor of environmental review." *Meija v. City of Los Angeles* (2005) 130 Cal. App. 4th 322, 332. "The determination of whether a project may have a significant effect on the environment calls for careful judgment on the part of the public agency involved, based to the extent possible on scientific and factual data." (CEQA Guidelines §15064(b).

In determining whether a project may have a significant effect on the environment, CEQA Guidelines Section 15064.7 provides that lead agencies may adopt and/or apply "thresholds of significance." A threshold of significance is "an identifiable quantitative, qualitative or performance level of a particular environmental effect, non-compliance with which means the effect will normally be determined to be significant by the agency and compliance with which means the effect normally will be determined to be less than significant" (CEQA Guidelines §15064.7).

While thresholds of significance give rise to a presumption of insignificance, thresholds are not conclusive, and do not excuse a public agency of the duty to consider evidence that a significant effect may occur under the fair argument standard. *Meija*, 130 Cal. App. 4th at 342. "A public agency cannot apply a threshold of significance or regulatory standard 'in a way that forecloses the consideration of any other substantial evidence showing there may be a significant effect." *Id.* This means that if a public agency is presented with factual information or other substantial evidence establishing a fair argument that a project may have a significant effect on the environment, the agency must prepare an EIR to study those impacts even if the project's impacts fall below the applicable threshold of significance.

Thresholds of significance must be supported by substantial evidence. This Report provides the substantial evidence in support of the thresholds of significance developed by the BAAQMD. If adopted by the BAAQMD Board of Directors, the Air District will recommend that lead agencies within the nine counties of the BAAQMD's jurisdiction use the thresholds of significance in this Report when considering the air quality impacts of projects under their consideration.

1.2 JUSTIFICATION FOR UPDATING CEQA THRESHOLDS

Any analysis of environmental impacts under CEQA includes an assessment of the nature and extent of each impact expected to result from the project to determine whether the impact will be treated as significant or less than significant. CEQA gives lead agencies discretion whether to classify a particular environmental impact as significant. Ultimately, formulation of a standard of significance requires the lead agency to make a policy judgment about where the line should be drawn distinguishing adverse impacts it considers significant from those that are not deemed significant. This judgment must, however, be based on scientific information and other factual data to the extent possible (CEQA Guidelines §15064(b)).

In the sense that advances in science provide new or refined factual data, combined with advances in technology and the gradual improvement or degradation of an environmental resource, the point where an environmental effect is considered significant is fluid over time. Other factors influencing this fluidity include new or revised regulations and standards, and emerging, new areas of concern.

In the ten years since BAAQMD last reviewed its recommended CEQA thresholds of significance for air quality, there have been tremendous changes that affect the quality and management of the air resources in the Bay Area. Traditional criteria air pollutant ambient air quality standards, at both the state and federal levels, have become increasingly more stringent. A new criteria air pollutant standard for $PM_{2.5}$ has been added to federal and state ambient air quality standards. We have found, through technical advances in impact assessment, that toxic air contaminants are not only worse than previously thought from a health perspective, but that certain communities experience high levels of toxic air contaminants, giving rise to new regulations and programs to reduce the significantly elevated levels of ambient toxic air contaminant concentrations in the Bay Area.

In response to the elevated levels of toxic air contaminants in some Bay Area communities, the Air District created the Community Air Risk Evaluation (CARE) Program. Phase 1 of the BAAQMD's CARE program compiled and analyzed a regional emissions inventory of toxic air contaminants (TACs), including emissions from stationary sources, area sources, and on-road and off-road mobile sources. Phase 2 of the CARE Program conducted regional computer modeling of selected TAC species, species which collectively posed the greatest risk to Bay Area residents. In both Phases 1 and 2 demographic data were combined with estimates of TAC emissions and concentrations to identify communities that are disproportionally impacted from high concentrations of TACs.

Another significant issue that affects the quality of life for Bay Area residents is the growing concern with global climate change. In just the past few years, estimates of the global atmospheric temperature and greenhouse gas concentration limits needed to stabilize climate change have been adjusted downward and the impacts of greenhouse gas emissions considered more dire. Previous scientific assessments assumed that limiting global temperature rise to 2-3°C above pre-industrial levels would stabilize greenhouse gas concentrations in the range of 450-550 parts per million (ppm) of carbon dioxide-equivalent (CO₂e). Now the science indicates that a temperature rise of 2°C would not prevent dangerous interference with the climate system. Recent scientific assessments suggest that global temperature rise should be kept below 2°C by stabilizing greenhouse gas concentrations below 350 ppm CO₂e, a significant reduction from the current level of 385 ppm CO₂e.

For the reasons stated above, and to further the goals of other District programs such as encouraging transit-oriented and infill development, BAAQMD has undertaken an effort to review all of its currently-recommended CEQA thresholds, revise them as appropriate, and develop new thresholds where appropriate. The overall goal of this effort is to develop CEQA significance criteria that ensure new development implements appropriate and feasible emission reduction measures to mitigate significant air quality impacts. The Air District's recommended CEQA significance thresholds have been vetted through a public review process and will be presented to the BAAQMD Board of Directors for adoption.

Table 1 – Proposed Air Quality CEQA Thresholds of Significance					
Pollutant	Construction-Related	Operation	al-Related		
Project-Level					
Criteria Air Pollutants and Precursors (Regional)	Average Daily Emissions (lb/day)	Average Daily Emissions (lb/day)	Maximum Annual Emissions (tpy)		
ROG	54	54	10		
NO _X	54	54	10		
PM ₁₀ (exhaust)	82	82	15		
PM _{2.5} (exhaust)	54	54	10		
PM ₁₀ /PM _{2.5} (fugitive dust)	Best Management Practices	Nc	one		
Local CO	None	9.0 ppm (8-hour avera aver	ige), 20.0 ppm (1-hour rage)		
GHGs – Projects other than Stationary Sources	None	Compliance with Qualified Climate Action Pla OR 1,100 MT of CO ₂ e/yr OR 4.6 MT CO ₂ e/SP/yr (residents + employees)			
GHGs –Stationary Sources	None	10,000 MT/yr			
Risks and Hazards (Siting a New Source or Receptor)	Same as Operational Thresholds	Compliance with Qualif O Increased cancer risk Increased non-cancer ris (Chronic Ambient PM _{2.5} increase: > <u>Zone of Influence</u> : 1,000- line of	ied Risk Reduction Plan R of >10.0 in a million sk of > 1.0 Hazard Index or Acute) \cdot 0.3 µg/m ³ annual average foot radius from fence f source or receptor		

PollutantConstruction-RelatedOperational-RelatedRisks and Hazards (Cumulative – Source or Receptor)Same as Operational ThresholdsCompliance with Qualified Risk Reduction Plan OR Cancer: > 1.0 Hazard Index (from all local sources) Non-cancer: > 1.0 Hazard Index (from all local sources) (Chronic or Acute) $\underline{PM_{2:S}}$ > 0.8 µg/m³ annual average (from all local sources) Zone of Influence: 1,000-foot radius from fence line of source or receptorAccidental Release of Acutely Hazardous Air PollutantsNoneStorage or use of acutely hazardous materials locating near receptors or receptors locating near stored or used acutely hazardous materials considered significantOdorsNoneScreening Level Distances and Complaint HistoryPlan-Level1. Consistency with Current Air Quality Plan control measuresGHGsNone1. Consistency with Current Air Quality Plan control measuresGHGsNoneCompliance with Qualified Climate Action Plan (or similar criteria included in a General Plan) OR 6.6 MT CO2e/SP/yr (residents + employees)Risks and Hazards/OdorsNone1. Overlay zones around existing and planned sources of TACs (including adopted Risk Reduction Plan areas) and doors 2. Overlay zones of TAcs (including adopted Risk Reduction Plan areas) and doorsAccidental Release of Acutely Hazardous Air PollutantsNone1. Overlay zones around existing and planned sources of TACs (including adopted Risk Reduction Plan areas) and doors 2. Overlay zones of a Heast 500 feet (or Air District-approved modeled distance) from all freeways and high volume roadways	Table 1 – Proposed Air Quality CEQA Thresholds of Significance					
Risks and Hazards (Cumulative – Source or Receptor)Same as Operational ThresholdsCompliance with Qualified Risk Reduction Plan OR Cancer: > 100 in a million (from all local sources) Non-cancer: > 10 Hazard Index (from all local sources) (Chronic or Acute) $PM_{2.5}$ > 0.8 µg/m ³ annual average (from all local sources) Zone of Influence: 1,000-foot radius from fence line of source or receptorAccidental Release of Acutely Hazardous Air PollutantsNoneStorage or use of acutely hazardous materials locating near receptors or receptors locating near stored or used acutely hazardous materials considered significantOdorsNoneScreening Level Distances and Complaint HistoryPlan-LevelIConsistency with Current Air Quality Plan control measuresGHGsNoneCompliance with Qualified Climate Action Plan (or similar criteria nichued in a General Plan) OR 6.6 MT CO2e/SPlyr (residents + employees)Risks and Hazards/OdorsNoneIOverlay zones around existing adopted Risk Reduction Plan reces) and doors 2. Overlay zones of a Ideatof Or Air District-approved modeled distance) from all freeways and high volume roadways	Pollutant	Construction-Related	Operational-Related			
Accidental Release of Acutely Hazardous Air PollutantsNoneStorage or use of acutely hazardous materials locating near receptors or receptors locating near stored or used acutely hazardous materials considered significantOdorsNoneScreening Level Distances and Complaint HistoryPlan-LevelI.Consistency with Current Air Quality Plan control measuresCriteria Air Pollutants and Precursors (Regional and Local)NoneI.Consistency with Current Air Quality Plan control measuresGHGsNoneI.Compliance with Qualified Climate Action Plan (or similar criteria included in a General Plan) OR 6.6 MT CO2e/ SP/yr (residents + employees)Risks and Hazards/OdorsNoneI.Overlay zones around existing and planned sources of TACs (including adopted Risk Reduction Plan areas) and odorsAccidental Release of Acutely Hazardous Air PollutantsNoneNoneNone	Risks and Hazards (Cumulative – Source or Receptor) Same as Operational Thresholds		Compliance with Qualified Risk Reduction Plan ORORCancer: > 100 in a million (from all local sources)Non-cancer: > 1.0 Hazard Index (from all local sources) (Chronic or Acute) $\underline{PM_{2.5:}}$ > 0.8 µg/m³ annual average (from all local sources)Zone of Influence: 1,000-foot radius from fence line of source or receptor			
OdorsNoneScreening Level Distances and Complaint HistoryPlan-LevelI.Consistency with Current Air Quality Plan control measuresCriteria Air Pollutants and Precursors (Regional and Local)NoneI.Consistency with Current Air Quality Plan control measuresGHGsNoneI.Complaint event of the projected VMT or vehicle trip increase is less than or equal to projected population increaseGHGsNoneCompliance with Qualified Climate Action Plan (or similar criteria included in a General Plan) OR 6.6 MT CO2e/ SP/yr (residents + employees)Risks and Hazards/OdorsNoneI.Overlay zones around existing and planned sources of TACs (including adopted Risk Reduction Plan areas) and odorsAccidental Release of Acutely Hazardous Air PollutantsNoneNone	Accidental Release of Acutely Hazardous Air Pollutants	None	Storage or use of acutely hazardous materials locating near receptors or receptors locating near stored or used acutely hazardous materials considered significant			
Plan-Level Criteria Air Pollutants and Precursors (Regional and Local) None 1. Consistency with Current Air Quality Plan control measures GHGs None 2. Projected VMT or vehicle trip increase is less than or equal to projected population increase GHGs None Compliance with Qualified Climate Action Plan (or similar criteria included in a General Plan) OR 6.6 MT CO2e/ SP/yr (residents + employees) Risks and Hazards/Odors None 1. Overlay zones around existing and planned sources of TACs (including adopted Risk Reduction Plan areas) and odors Accidental Release of Acutely Hazardous Air Pollutants None None	Odors	None	Screening Level Distances and Complaint History			
Criteria Air Pollutants and Precursors (Regional and Local)None1. Consistency with Current Air Quality Plan control measuresBeta GHGsNone2. Projected VMT or vehicle trip increase is less than or equal to projected population increaseGHGsNoneCompliance with Qualified Climate Action Plan (or similar criteria included in a General Plan) OR 6.6 MT CO2e/ SP/yr (residents + employees)Risks and Hazards/OdorsNone1. Overlay zones around existing and planned sources of TACs (including adopted Risk Reduction Plan areas) and odors 2. Overlay zones of at least 500 feet (or Air District-approved modeled distance) from all freeways and high volume roadwaysAccidental Release of Acutely Hazardous Air PollutantsNoneNone	Plan-Level					
GHGsNoneCompliance with Qualified Climate Action Plan (or similar criteria included in a General Plan) OR 6.6 MT CO2e/ SP/yr (residents + employees)Risks and Hazards/OdorsNone1. Overlay zones around existing and planned sources of TACs (including adopted Risk Reduction Plan areas) and odors 2. Overlay zones of at least 500 feet (or Air District-approved modeled distance) from all freeways and high volume roadwaysAccidental Release of 	Criteria Air Pollutants and Precursors (Regional and Local)	None	 Consistency with Current Air Quality Plan control measures Projected VMT or vehicle trip increase is less than or equal to projected population increase 			
Risks and Hazards/OdorsNone1. Overlay zones around existing and planned sources of TACs (including adopted Risk Reduction Plan areas) and odors 2. Overlay zones of at least 500 feet (or Air District-approved modeled distance) from all freeways and high volume roadwaysAccidental Release of Acutely Hazardous Air PollutantsNoneNone	GHGs	None	Compliance with Qualified Climate Action Plan (or similar criteria included in a General Plan) OR 6.6 MT CO2e/ SP/yr (residents + employees)			
Accidental Release of Acutely Hazardous Air PollutantsNoneNone	Risks and Hazards/Odors	None	 Overlay zones around existing and planned sources of TACs (including adopted Risk Reduction Plan areas) and odors Overlay zones of at least 500 feet (or Air District-approved modeled distance) from all freeways and high volume roadways 			
	Accidental Release of Acutely Hazardous Air Pollutants	None	None			

Notes: CEQA = California Environmental Quality Act; CO = carbon monoxide; CO₂e = carbon dioxide equivalent; GHGs = greenhouse gases; lb/day = pounds per day; MT = metric tons; NO_x = oxides of nitrogen; PM_{2.5}= fine particulate matter with an aerodynamic resistance diameter of 2.5 micrometers or less; PM₁₀ = respirable particulate matter with an aerodynamic resistance diameter of 10 micrometers or less; ppm = parts per million; ROG = reactive organic gases; SO₂ = sulfur dioxide; SP = service population; TACs = toxic air contaminants; TBP = toxic best practices; tons/day = tons per day; tpy = tons per year; yr= year; TBD: to be determined.

2 GREENHOUSE GAS THRESHOLDS

BAAQMD does not currently have an adopted threshold of significance for GHG emissions. BAAOMD currently recommends that lead agencies quantify GHG emissions resulting from new development and apply all feasible mitigation measures to lessen the potentially adverse impacts. One of the primary objectives in updating the current CEQA Guidelines is to identify a GHG significance threshold, analytical methodologies, and mitigation measures to ensure new land use development meets its fair share of the emission reductions needed to address the cumulative environmental impact from GHG emissions. GHG emissions contribute, on a cumulative basis, to the significant adverse environmental impacts of global climate change. As reviewed herein, climate change impacts include an increase in extreme heat days, higher ambient concentrations of air pollutants, sea level rise, impacts to water supply and water quality, public health impacts, impacts to ecosystems, impacts to agriculture, and other environmental impacts. No single land use project could generate enough GHG emissions to noticeably change the global average temperature. The combination of GHG emissions from past, present, and future projects contribute substantially to the phenomenon of global climate change and its associated environmental impacts.

Project Type Proposed Thresholds		
	Compliance with Qualified Climate Action Plan	
	OR	
Land Use Projects	1,100 MT of CO ₂ e/yr	
U U	OR	
	4.6 MT $CO_2 e/SP/yr^*$ (residents + employees)	
Stationary Sources	10,000 MT of CO ₂ e/yr	
	Compliance with Qualified Climate Action Plan	
	(or similar criteria included in a General Plan)	
General Plans	OR	
	$6.6 \text{ MT CO}_{2} \text{e/SP/yr} \text{ (residents + employees)}$	

2.2 **PROPOSED THRESHOLDS OF SIGNIFICANCE**

* Staff notes that the efficiency-based thresholds should be applied to individual projects with caution. As explained herein, lead agencies may determine that the efficiency-based GHG thresholds for individual land use projects may not be appropriate for very large projects. If there is a fair argument that the project's emissions on a mass level will have a cumulatively considerable impact on the region's GHG emissions, the insignificance presumption afforded to a project that meets an efficiency-based GHG threshold would be overcome.

2.3 JUSTIFICATION AND SUBSTANTIAL EVIDENCE SUPPORTING THRESHOLDS

BAAQMD's approach to developing a threshold of significance for GHG emissions is to identify the emissions level for which a project would not be expected to substantially conflict with existing California legislation adopted to reduce statewide GHG emissions. If a project would generate GHG emissions above the threshold level, it would be

considered to contribute substantially to a cumulative impact, and would be considered significant. If mitigation can be applied to lessen the emissions such that the project meets its share of emission reductions needed to address the cumulative impact, the project would normally be considered less than significant.

As explained in the District's *Revised Draft Options and Justifications Report* (BAAQMD 2009), there are several types of thresholds that may be supported by substantial evidence and be consistent with existing California legislation and policy to reduce statewide GHG emissions. In determining which thresholds to recommend, Staff studied numerous options, relying on reasonable, environmentally conservative assumptions on growth in the land use sector, predicted emissions reductions from statewide regulatory measures and resulting emissions inventories, and the efficacies of GHG mitigation measures. The thresholds represent quantitative and/or qualitative levels of GHG emissions, compliance with which means that the environmental impact of the GHG emissions will normally not be cumulatively considerable under CEQA. Compliance with such thresholds will be part of the solution to the cumulative GHG emissions problem, rather than hinder the state's ability to meet its goals of reduced statewide GHG emissions that can be supported by substantial evidence.

GHG CEQA significance thresholds recommended herein are intended to serve as interim levels during the implementation of the AB 32 Scoping Plan and SB 375, which will occur over time. Until AB 32 has been fully implemented in terms of adopted regulations, incentives, and programs and until SB 375 required plans have been fully adopted, or ARB adopts a recommended threshold, the BAAQMD recommends that local agencies in the Bay Area apply the GHG thresholds recommended herein.

If left unchecked, GHG emissions from new land use development in California will result in a cumulatively considerable amount of GHG emissions and a substantial conflict with the State's ability to meet the goals within AB 32. Thus, BAAQMD proses to adopt interim GHG thresholds for CEQA analysis, which can be used by lead agencies within the Bay Area. This would help lead agencies navigate this dynamic regulatory and technological environment where the field of analysis has remained wide open and inconsistent. BAAQMD's framework for developing a GHG threshold for land development projects that is based on policy and substantial evidence follows.

2.3.1 SCIENTIFIC AND REGULATORY JUSTIFICATION

Climate Science Overview

Prominent GHGs contributing to the greenhouse effect are carbon dioxide (CO₂), methane (CH₄), nitrous oxide (N₂O), hydrofluorocarbons, chlorofluorocarbons, and sulfur hexafluoride. Human-caused emissions of these GHGs in excess of natural ambient concentrations are responsible for intensifying the greenhouse effect and have led to a trend of unnatural warming of the earth's climate, known as global climate change or

global warming. It is *extremely unlikely* that global climate change of the past 50 years can be explained without the contribution from human activities (IPCC 2007a).

According to Article 2 of the United Nations Framework Convention on Climate Change (UNFCCC), "Avoiding Dangerous Climate Change" means: *"stabilization of greenhouse gas concentrations in the atmosphere at a level that would prevent dangerous anthropogenic interference with the climate system.*" Dangerous climate change defined in the UNFCCC is based on several key indicators including the potential for severe degradation of coral reef systems, disintegration of the West Antarctic Ice Sheet, and shut down of the large-scale, salinity- and thermally-driven circulation of the oceans. (UNFCCC 2009). The global atmospheric concentration of carbon dioxide has increased from a pre-industrial value of about 280 ppm to 379 ppm in 2005 (IPCC 2007a). "Avoiding dangerous climate change" is generally understood to be achieved by stabilizing global average temperatures between 2 and 2.4°C above pre-industrial levels. In order to limit temperature increases to this level, ambient global CO₂ concentrations must stabilize between 350 and 400 ppm (IPCC 2007b).

Executive Order S-3-05

Executive Order S-3-05, which was signed by Governor Schwarzenegger in 2005, proclaims that California is vulnerable to the impacts of climate change. It declares that increased temperatures could reduce the Sierra's snowpack, further exacerbate California's air quality problems, and potentially cause a rise in sea levels. To combat those concerns, the Executive Order established total GHG emission targets. Specifically, emissions are to be reduced to the 2000 level by 2010, the 1990 level by 2020, and to 80 percent below the 1990 level by 2050.

Assembly Bill 32, the California Global Warming Solutions Act of 2006

In September 2006, Governor Arnold Schwarzenegger signed Assembly Bill 32, the California Global Warming Solutions Act of 2006, which set the 2020 greenhouse gas emissions reduction goal into law. AB 32 finds and declares that "Global warming poses a serious threat to the economic well-being, public health, natural resources, and the environment of California." AB 32 requires that statewide GHG emissions be reduced to 1990 levels by 2020, and establishes regulatory, reporting, voluntary, and market mechanisms to achieve quantifiable reductions in GHG emissions to meet the statewide goal.

In December of 2008, ARB adopted its *Climate Change Scoping Plan (Scoping Plan)*, which is the State's plan to achieve GHG reductions in California, as required by AB 32 (ARB 2008). The Scoping Plan contains strategies California will implement to achieve a reduction of 169 MMT CO₂e emissions, or approximately 28 percent from the state's projected 2020 emission level of 596 MMT of CO₂e under a business-as-usual scenario (this is a reduction of 42 MMT of CO₂e, or almost 10 percent, from 2002-2004 average emissions), so that the state can return to 1990 emission levels, as required by AB 32.

While the Scoping Plan establishes the policy intent to control numerous GHG sources through regulatory, incentive, and market means, given the early phase of implementation

and the level of control that local CEQA lead agencies have over numerous GHG sources, CEQA is an important and supporting tool in achieving GHG reductions overall in compliance with AB 32. In this spirit, BAAQMD is considering the adoption of thresholds of significance for GHG emissions for stationary source and land use development projects.

Senate Bill 375

Senate Bill (SB) 375, signed in September 2008, aligns regional transportation planning efforts, regional GHG reduction targets, and land use and housing allocation. SB 375 requires Metropolitan Planning Organizations (MPOs) to adopt a Sustainable Communities Strategy (SCS) or Alternative Planning Strategy (APS), which will prescribe land use allocation in that MPO's Regional Transportation Plan (RTP). ARB, in consultation with MPOs, will provide each affected region with reduction targets for GHGs emitted by passenger cars and light trucks in the region for the years 2020 and 2035. These reduction targets will be updated every eight years, but can be updated every four years if advancements in emission technologies affect the reduction strategies to achieve the targets. ARB is also charged with reviewing each MPO's SCS or APS for consistency with its assigned targets. If MPOs do not meet the GHG reduction targets, transportation projects would not be eligible for State funding programmed after January 1, 2012. New provisions of CEQA would incentivize qualified projects that are consistent with an approved SCS or APS, categorized as "transit priority projects."

While SB 375 is considered in the development of these thresholds, given that the Association of Bay Area Governments (ABAG) and the Metropolitan Transportation Commission (MTC) development of the SCS for the Bay Area is in its early stages and the ARB GHG reduction target for light duty and passenger vehicles in the Bay Area has not yet been proposed, it is not appropriate from a CEQA perspective to expect SB 375 to completely address the emission reductions needed from this transportation sector in meeting AB 32 goals. In the future, as SB 375 implementation progresses, BAAQMD may need to revisit GHG thresholds.

2.3.2 **PROJECT-LEVEL GHG THRESHOLDS**

Staff recommends setting GHG significance thresholds based on AB 32 GHG emission reduction goals while taking into consideration emission reduction strategies outlined in ARB's Scoping Plan. Staff proposes two quantitative thresholds for land use projects: a bright line threshold based on a "gap" analysis and an efficiency threshold based on emission levels required to be met in order to achieve AB 32 goals.

Staff also proposes one qualitative threshold for land use projects: if a project complies with a Qualified Climate Action Plan (as defined in Section 2.3.4 below) that addresses the project or a Sustainable Communities Strategy (SCS) or Alternative Planning Strategy (APS) developed pursuant to SB 375 that addresses the project, it would be considered less than significant. As explained in detail in Section 2.3.4 below, compliance with a Qualified Climate Action Plan (or similar adopted policies, ordinances and programs), SCS or APS would provide the evidentiary basis for making CEQA

findings that development consistent with the plan would result in feasible, measureable, and verifiable GHG reductions consistent with broad state goals such that projects approved under qualified Climate Action Plans or equivalent demonstrations would achieve their fair share of GHG emission reductions.

2.3.2.1 LAND USE PROJECTS "GAP-BASED" THRESHOLD

Staff took eight steps in developing this threshold approach, which are summarized here and detailed in the sections that follow. It should be noted that the "gap-based approach" used for threshold development is a conservative approach that focuses on a limited set of state mandates that appear to have the greatest potential to reduce land use developmentrelated GHG emissions at the time of this writing. It is also important to note that over time as the effectiveness of the State's implementation of AB 32 (and SB 375) progresses, BAAQMD will need to reconsider the extent of GHG reductions needed over and above those from the implementation thereof for the discretionary approval of land use development projects. Although there is an inherent amount of uncertainty in the estimated capture rates (i.e., frequency at which project-generated emissions would exceed a threshold and would be subject to mitigation under CEQA) and the aggregate emission reductions used in the gap analysis, they are based on BAAQMD's expertise, the best available data, and use conservative assumptions for the amount of emission reductions from legislation in derivation of the gap (e.g., only adopted legislation was relied upon). This approach is intended to attribute an appropriate share of GHG emission reductions necessary to reach AB 32 goals to new land use development projects in BAAQMD's jurisdiction that are evaluated pursuant to CEQA.

- Step 1 Estimate from ARB's statewide GHG emissions inventory the growth in emissions between 1990 and 2020 attributable to "land use-driven" sectors of the emission inventory as defined by OPR's guidance document (*CEQA and Climate Change*). Land use-driven emission sectors include Transportation (On-Road Passenger Vehicles; On-Road Heavy Duty), Electric Power (Electricity; Cogeneration), Commercial and Residential (Residential Fuel Use; Commercial Fuel Use) and Recycling and Waste (Domestic Waste Water Treatment).
 - Result: 1990 GHG emissions were 295.53 MMT CO₂e/yr and projected 2020 business-as-usual GHG emissions would be 400.22 MMT CO₂e/yr; thus a 26.2 percent reduction from statewide land use-driven GHG emissions would be necessary to meet the AB 32 goal of returning to 1990 emission levels by 2020. (See Table 2)
- Step 2 Estimate the anticipated GHG emission reductions affecting the same land usedriven emissions inventory sectors associated with adopted statewide regulations identified in the AB 32 Scoping Plan.
 - Result: Estimated a 23.9 percent reduction can be expected in the land usedriven GHG emissions inventory from adopted Scoping Plan regulations, including AB 1493 (Pavley), LCFS, Heavy/Medium Duty Efficiency, Passenger Vehicle Efficiency, Energy-Efficiency

Measures, Renewable Portfolio Standard, and Solar Roofs. (See Table 3)

- Step 3 Determine any short fall or "gap" between the 2020 statewide emission inventory estimates and the anticipated emission reductions from adopted Scoping Plan regulations. This "gap" represents additional GHG emission reductions needed statewide from the land use-driven emissions inventory sectors, which represents new land use development's share of the emission reductions needed to meet statewide GHG emission reduction goals.
 - Result: With the 23.9 percent reductions from AB 32 Scoping Measures, there is a "gap" of 2.3 percent in necessary additional GHG emissions reductions to meet AB 32 goals of a 26.2 percent reduction from statewide land use-driven GHG emissions to return to 1990 levels in 2020. (See Table 2)
- Step 4 Determine the percent reduction this "gap" represents in the "land use-driven" emissions inventory sectors from BAAQMD's 2020 GHG emissions inventory. Identify the mass of emission reductions needed in the SFBAAB from land use-driven emissions inventory sectors.
 - Result: Estimated that a 2.3 percent reduction in BAAQMD's projected 2020 emissions projections requires emissions reductions of 1.6 MMT CO_2e/yr from the land use-driven sectors. (See Table 4)
- Step 5 Assess BAAQMD's historical CEQA database (2001-2008) to determine the frequency distribution trend of project sizes and types that have been subject to CEQA over the past several years.
 - Result: Determined historical patterns of residential, commercial and industrial development by ranges of average sizes of each development type. Results were used in Step 6 below to distribute anticipated Bay Area growth among different future project types and sizes.
- Step 6 Forecast new land use development for the Bay Area using DOF/EDD population and employment projections and distribute the anticipated growth into appropriate land use types and sizes needed to accommodate the anticipated growth (based on the trend analysis in Step 5 above). Translate the land use development projections into land use categories consistent with those contained in the Urban Emissions Model (URBEMIS).
 - Result: Based on population and employment projections and the trend analysis from Step 5 above, forecasted approximately 4,000 new development projects, averaging about 400 projects per year through 2020 in the Bay Area.

- Step 7 Estimate the amount of GHG emissions from each land use development project type and size using URBEMIS and post-model manual calculation methods (for emissions not included in URBEMIS. Determine the amount of GHG emissions that can reasonably and feasibly be reduced through currently available mitigation measures ("mitigation effectiveness") for future land use development projects subject to CEQA (based on land use development projections and frequency distribution from Step 6 above).
 - Result: Based on the information available and on sample URBEMIS calculations, found that mitigation effectiveness of between 25 and 30 percent is feasible.
- Step 8 Conduct a sensitivity analysis of the numeric GHG mass emissions threshold needed to achieve the desired emissions reduction (i.e., "gap") determined in Step 4. This mass emission GHG threshold is that which would be needed to achieve the emission reductions necessary by 2020 to meet the Bay Area's share of the statewide "gap" needed from the land use-driven emissions inventory sectors.
 - Result: The results of the sensitivity analysis conducted in Step 8 found that reductions between about 125,000 MT/yr (an aggregate of 1.3 MMT in 2020) and over 200,000 MT/yr (an aggregate of over 2.0 MMT in 2020) were achievable and feasible. A mass emissions threshold of 1,100 MT of CO_2e/yr would result in approximately 59 percent of all projects being above the significance threshold (e.g., this is approximately the operational GHG emissions that would be associated with a 60 residential unit subdivision) and must implement feasible mitigation measures to meet CEQA requirements. With estimated 26 percent mitigation effectiveness, the 1,100 MT threshold would achieve 1.6 MMT CO_2e/yr in GHG emissions reductions.

2.3.2.2 DETAILED BASIS AND ANALYSIS

Derivation of Greenhouse Gas Reduction Goal

To meet the target emissions limit established in AB 32 (equivalent to levels in 1990), total GHG emissions would need to be reduced by approximately 28 percent from projected 2020 forecasts (ARB 2009a). The AB 32 Scoping Plan is ARB's plan for meeting this mandate (ARB 2008). While the Scoping Plan does not specifically identify GHG emission reductions from the CEQA process for meeting AB 32 derived emission limits, the scoping plan acknowledges that "other strategies to mitigate climate change . . . should also be explored." The Scoping Plan also acknowledges that "Some of the measures in the plan may deliver more emission reductions than we expect; others less . . . and new ideas and strategies will emerge." In addition, climate change is considered a significant environmental issue and, therefore, warrants consideration under CEQA. SB 97 represents the State Legislature's confirmation of this fact, and it directed the Governor's Office of Planning and Research (OPR) to develop CEQA Guidelines for

evaluation of GHG emissions impacts and recommend mitigation strategies. In response, OPR released the *Technical Advisory: CEQA and Climate Change* (OPR 2008), and has released proposed CEQA guidelines (April 14, 2009) for consideration of GHG emissions. It is known that new land use development must also do its fair share toward achieving AB 32 goals (or, at a minimum, should not hinder the State's progress toward the mandated emission reductions).

Foreseeable Scoping Plan Measures Emission Reductions and Remaining "Gap"

Step 1 of the Gap Analysis entailed estimating from ARB's statewide GHG inventory the growth in emissions between 1990 and 2020 attributable to land use driven sectors of the emissions inventory. As stated above, to meet the requirements set forth in AB 32 (i.e., achieve California's 1990-equivalent GHG emissions levels by 2020) California would need to achieve an approximate 28 percent reduction in emissions across all sectors of the GHG emissions inventory compared with 2020 projections. However, to meet the AB 32 reduction goals in the emissions sectors that are related to land use development (e.g., onroad passenger and heavy-duty motor vehicles, commercial and residential area sources [i.e., natural gas], electricity generation/consumption, wastewater treatment, and water distribution/consumption), staff determined that California would need to achieve an approximate 26 percent reduction in GHG emissions from these land use-driven sectors (ARB 2009a) by 2020 to return to 1990 land use emission levels.

Next, in Step 2 of the Gap Analysis, Staff determined the GHG emission reductions within the land use-driven sectors that are anticipated to occur from implementation of the Scoping Plan measures statewide, which are summarized in Table 2 and described below. Since the GHG emission reductions anticipated with the Scoping Plan were not accounted for in ARB's or BAAQMD's 2020 GHG emissions inventory forecasts (i.e., business as usual), an adjustment was made to include (i.e., give credit for) GHG emission reductions associated with key Scoping Plans measures, such as the Renewable Portfolio Standard, improvements in energy efficiency through periodic updates to Title 24, AB 1493 (Pavley) (which recently received a federal waiver to allow it to be enacted in law), the Low Carbon Fuel Standard (LCFS), and other measures. With reductions from these State regulations (Scoping Plan measures) taken into consideration and accounting for an estimated 23.9% reduction in GHG emissions, in Step 3 of the Gap Analysis Staff determined that the Bay Area would still need to achieve an additional 2.3 percent reduction from projected 2020 GHG emissions to meet the 1990 GHG emissions goal from the land-use driven sectors. This necessary 2.3 percent reduction in projected GHG emissions from the land use sector is the "gap" the Bay Area needs to fill to do its share to meet the AB 32 goals. Refer to the following explanation and Tables 2 through 4 for data used in this analysis.

Because the transportation sector is the largest emissions sector of the state's GHG emissions inventory, it is aggressively targeted in early actions and other priority actions in the Scoping Plan including measures concerning gas mileage (Pavley), fuel carbon intensity (LCFS) and vehicle efficiency measures.

Table 2 – California 1990, 2002-2004, and 2020 Land Use Sector GHG ¹ (MMT CO ₂ e/yr)						
Sector	1990 Emissions	2002-2004 Average	2020 BAU Emissions Projections	% of 2020 Total		
Transportation	168.66	209.06	52%			
On-Road Passenger Vehicles	108.95	133.95	160.78	40%		
On-Road Heavy Duty	29.03	34.69	48.28	12%		
Electric Power	110.63	110.04	140.24	35%		
Electricity	95.39	88.97	107.40	107.40 27%		
Cogeneration ²	Cogeneration ² 15.24 21.07 32.84 8%					
Commercial and Residential	40.96	46.79	12%			
Residential Fuel Use	29.66	28.52	32.10	8%		
Commercial Fuel Use 14.43 12.45 14.63		4%				
Recycling and Waste¹	2.83	3.39	4.19	1%		
Domestic Wastewater Treatment	2.83	3.39	4.19	1%		
TOTAL GROSS EMISSIONS	295.53	323.05	400.22			
% Reduction Goal from Statewide levels to reach 1990 levels in thes	e land use driven sec e emission inventory	ctors (from 2020 y sectors)	26.2	%		
% Reduction from AB32 Scoping Plan measures applied to land use -23.9%						
% Reduction needed statewide beyond Scoping Plan measures (Gap) 2.3%						
Notes: MMT CO_2e /yr = million metric tons of carbon dioxide equivalent emissions per year. ¹ Landfills not included. See text.						

 2 Cogeneration included due to many different applications for electricity, in some cases provides substantial power for grid use, and because electricity use served by cogeneration is often amenable to efficiency requirements of local land use authorities.

Sources: Data compiled by EDAW and ICF Jones & Stokes from ARB data.

<u>Pavley Regulations</u>. The AB 32 Scoping Plan assigns an approximate 20 percent reduction in emissions from passenger vehicles associated with the implementation of AB 1493. The AB 32 Scoping Plan also notes that "AB 32 specifically states that if the Pavley regulations do not remain in effect, ARB shall implement alternative regulations to control mobile sources to achieve equivalent or greater reductions of greenhouse gas emissions (HSC §38590)." Thus, it is reasonable to assume full implementation of AB 1493 standards, or equivalent programs that would be implemented by ARB. While the Obama administration has proposed national CAFE standards that may be equivalent to or even surpass AB 1493, the timing for implementation of the proposed federal standards is uncertain such that development of thresholds based on currently unadopted federal standards come on line, particularly if such standards are more aggressive than that forecast under state law.

Table 3 – 2020 Land Use Sector GHG Emission Reductions from State Regulations and AB 32 Measures				
Affected Emissions Source	California Legislation	% Reduction from 2020 GHG inventory	End Use Sector (% of Bay Area LU Inventory)	Scaled % Emissions Reduction (credit)
	AB 1493 (Pavley)	19.7%	On road passenger/light truck transportation (45%)	8.9%
	LCFS	7.2%	On road passenger/light truck transportation (45%)	3.2%
Mobile	LCFS	7.2%	On road Heavy/Medium Duty Transportation (5%)	0.4%
	Heavy/Medium Duty Efficiency	2.9%	On road Heavy/Medium Duty Transportation (5%)	0.2%
	Passenger Vehicle Efficiency	2.8%	On road passenger/light truck transportation (45%)	1.3%
Area	Energy-Efficiency	9.5%	Natural gas (Residential, 10%)	1.0%
mea	Measures		Natural gas (Non-residential,13%)	1.2%
	Renewable Portfolio Standard	21.0%	Electricity (excluding cogen) (17%)	3.5%
Indirect	Energy-Efficiency Measures	15.7%	Electricity (26%)	4.0%
	Solar Roofs	1.5%	Electricity (excluding cogen) (17%)	0.2%
Total credits given to land use-driven emission inventory sectors from Scoping Plan 23.9%				
Notes: AB = Assembly Bill; LCFS = Low Carbon Fuel Standard; SB = Senate Bill; RPS = Renewable Portfolio Standard Please refer to Appendix D for detailed calculations. Sources: Data compiled by ICE Jones & Stokes				

<u>LCFS</u>. According to the adopted LCFS rule (CARB, April 2009), the LCFS is expected to result in approximately 10 percent reduction in the carbon intensity of transportation fuels. However, a portion of the emission reductions required from the LCFS would be achieved over the life cycle of transportation fuel production rather than from mobile-source emission factors. Based on CARB's estimate of nearly 16 MMT reductions in on-road emissions from implementation of the LCFS and comparison to the statewide on-road emissions sector, the LCFS is assumed to result in a 7.2 percent reduction compared to 2020 BAU conditions (CARB 2009e).

Table 4 – SFBAAB 1990, 2007, and 2020 Land Use Sector GHG Emissions Inventories and Projections (MMT CO ₂ e/yr)					
Sector	1990 Emissions	2007 Emissions	2020 Emissions Projections	% of 2020 Total ²	
Transportation	26.1	30.8	35.7	50%	
On-Road Passenger Vehicles	23.0	27.5	32.0		
On-Road Heavy Duty	3.1	3.3	3.7		
Electric Power	25.1	15.2	18.2	26%	
Electricity	16.5	9.9	11.8		
Cogeneration	8.6	5.3	6.4		
Commercial and Residential	8.9	15.0	16.8	24%	
Residential Fuel Use	5.8	7.0	7.5		
Commercial Fuel Use	3.1	8.0	9.3		
Recycling and Waste¹	0.2	0.4	0.4	1%	
Domestic Waste Water Treatment	0.2	0.4	0.4		
TOTAL GROSS EMISSIONS60.361.471.1					
SFBAAB's "Fair Share" % Reduction (from 2020 levels to reach 1990 levels) with AB-32 Reductions (from Table 3) 2.3%					
SFBAAB's Equivalent Mass Emissions Land Use Reduction Target at 1.6					
Notes: MMT CO ₂ e /yr = million m San Francisco Bay Area Air Basin. ¹ Landfills not included. ² Percentages do not sum exactly to Please refer to Appendix D for deta Sources: Data compiled by EDAW	etric tons of carbo	e to rounding.	ent emissions per ye	ear; SFBAAB =	

<u>Renewable Portfolio Standard, Energy Efficiency and Solar Roofs</u>. Energy efficiency and renewable energy measures from the Scoping Plan were also included in the gap analysis. The Renewable Portfolio Standard (rules) will require the renewable energy portion of the retail electricity portfolio to be 33 percent in 2020. For PG&E, the dominant electricity provider in the Basin, approximately 12 percent of their current portfolio qualifies under the RPS rules and thus the gain by 2020 would be approximately 21 percent. The Scoping Plan also estimates that energy efficiency gains with periodic improvement in building and appliance energy standards and incentives will reach 10 to 15 percent for natural gas and electricity respectively. The final state measure included in this gap analysis is the solar roof initiative, which is estimated to result in reduction of the overall electricity inventory of 1.5 percent.

Landfill emissions are excluded from this analysis. While land use development does generate waste related to both construction and operations, CIWMB has mandatory diversion requirements that will, in all probability, increase over time to promote waste reductions, reuse, and recycle. The Bay Area has relatively high levels of waste diversion and extensive recycling efforts. Further, ARB has established and proposes to increase methane capture requirements for all major landfills. Thus, at this time, landfill emissions

associated with land use development waste generation is not included in the land use sector inventory used to develop this threshold approach.

Industrial stationary sources thresholds were developed separately from the land use threshold development using a market capture approach as described below. However, mobile source and area source emissions, as well as indirect electricity emissions that derive from industrial use are included in the land use inventory above as these particular activities fall within the influence of local land use authorities in terms of the affect on trip generation and energy efficiency.

AB 32 mandates reduction to 1990-equivalent GHG levels by 2020, with foreseeable emission reductions from State regulations and key Scoping Plan measures taken into account, were applied to the land use-driven emission sectors within the SFBAAB (i.e., those that are included in the quantification of emissions from a land use project pursuant to a CEQA analysis [on-road passenger vehicles, commercial and residential natural gas, commercial and residential electricity consumption, and domestic waste water treatment], as directed by OPR in the Technical Advisory: *Climate Change and CEQA* [OPR 2008]). This translates to a 2.3 percent gap in necessary GHG emission reductions by 2020 from these sectors.

2.3.2.3 LAND USE PROJECTS BRIGHT LINE THRESHOLD

In Steps 4 and 5 of the gap analysis, Staff determined that applying a 2.3 percent reduction to these land use emissions sectors in the SFBAAB's GHG emissions inventory would result in an equivalent fair share of 1.6 million metric tons per year (MMT/yr) reductions in GHG emissions from new land use development. As additional regulations and legislation aimed at reducing GHG emissions from land use-related sectors become available in the future, the 1.6 MMT GHG emissions reduction goal may be revisited and recalculated by BAAQMD.

In order to derive the 1.6 MMT "gap," a projected development inventory for the next ten years in the SFBAAB was calculated. (See Table 4 and *Revised Draft Options and Justifications Report* (BAAQMD 2009).) CO₂e emissions were modeled for projected development in the SFBAAB and compiled to estimate the associated GHG emissions inventory. The GHG (i.e., CO₂e) CEQA threshold level was adjusted for projected land use development that would occur within BAAQMD's jurisdiction over the period from 2010 through 2020.

Projects with emissions greater than the threshold would be required to mitigate to the threshold level or reduce project emissions by a percentage (mitigation effectiveness) deemed feasible by the Lead Agency under CEQA compared to a base year condition. The base year condition is defined by an equivalent size and character of project with annual emissions using the defaults in URBEMIS and the California Climate Action Registry's General Reporting Protocol for 2008. By this method, land use project mitigation subject to CEQA would help close the "gap" remaining after application of the key regulations and measures noted above supporting overall AB 32 goals.

This threshold takes into account Steps 1-8 of the gap analysis described above to arrive at a numerical mass emissions threshold. Various mass emissions significance threshold levels (i.e., bright lines) could be chosen based on the mitigation effectiveness and performance anticipated to be achieved per project to meet the aggregate emission reductions of 1.6 MMT needed in the SFBAAB by 2020. (See Table 5 and *Revised Draft Options and Justifications Report* (BAAQMD 2009).) Staff recommends a 1,100 MT CO₂e per year threshold. Choosing a 1,100 MT mass emissions (equivalent to approximately 60 single-family units), significance threshold level would result in about 59 percent of all projects being above the significance threshold and having to implement feasible mitigation measures to meet their CEQA obligations. These projects account for approximately 92 percent of all GHG emissions anticipated to occur between now and 2020 from new land use development in the SFBAAB.

Project applicants and lead agencies could use readily available computer models to estimate a project's GHG emissions, based on project specific attributes, to determine if they are above or below the bright line numeric threshold. With this threshold, projects that are above the threshold level would have to reduce their emissions to below the threshold to be considered less than significant.

Establishing a "bright line" to determine the significance of a project's GHG emission impact provides a level of certainty to lead agencies in determining if a project needs to reduce its GHG emissions through mitigation measures and when an EIR is required.

Table 5 – Operational GHG Threshold Sensitivity Analysis								
	Mitigation Effectiver	ness Assumptions					A	
Option	Performance Standards Applied to All Projects with Emissions < Threshold Level	Mitigation Effectiveness Applied to Emissions > Threshold Level	Mass Emission Threshold Level (MT CO ₂ e/yr)	% of Projects Captured (>threshold)	% of Emissions Captured (> threshold)	Emissions Reduction per year (MT/yr)	Emissions Reduction (MMT) at 2020	Threshold Project Size Equivalent (single family dwelling units)
1A	N/A	30%	975	60%	93%	201,664	2.0	53
1A	N/A	25%	110	96%	100%	200,108	2.0	66
1A	N/A	30%	1,225	21%	67%	159,276	1.6	67
1A	N/A	26%	1,100	59%	92%	159,877	1.6	60
1A	N/A	30%	2,000	14%	61%	143,418	1.4	109
1A	N/A	25%	1,200	58%	92%	136,907	1.4	66
1A	N/A	30%	3,000	10%	56%	127,427	1.3	164
1A	N/A	25%	1,500	20%	67%	127,303	1.3	82
1B	26%	N/A	N/A	100%	100%	208,594	2.1	N/A ¹
1C	5%	30%	1,900	15%	62%	160,073	1.6	104
1C	10%	25%	1,250	21%	67%	159,555	1.6	68
1C	5%	30%	3,000	10%	56%	145,261	1.5	164
1C	10%	25%	2,000	4%	61%	151,410	1.5	109
1C	10%	30%	10,000	2%	33%	125,271	1.3	547

Notes: MMT = million metric tons per year; MT CO₂e/yr = metric tons of carbon dioxide equivalent emissions per year; MT/yr = metric tons per year; N/A = not applicable.

¹ Any project subject to CEQA would trigger this threshold.

Please refer to Appendix E for detailed calculations.

Source: Data modeled by ICF Jones & Stokes.

2.3.2.4 LAND USE PROJECTS EFFICIENCY-BASED THRESHOLD

GHG efficiency metrics can also be utilized as thresholds to assess the GHG efficiency of a project on a per capita basis (residential only projects) or on a "service population" basis (the sum of the number of jobs and the number of residents provided by a project) such that the project will allow for consistency with the goals of AB 32 (i.e., 1990 GHG emissions levels by 2020). GHG efficiency thresholds can be determined by dividing the GHG emissions inventory goal (allowable emissions), by the estimated 2020 population and employment. This method allows highly efficient projects with higher mass emissions to meet the overall reduction goals of AB 32. Staff believes it is more appropriate to base the land use efficiency threshold on the service population metric for the land use-driven emission inventory. This approach is appropriate because the threshold can be applied evenly to all project types (residential or commercial/retail only and mixed use) and uses only the land use emissions inventory that is comprised of all land use projects. Staff will provide the methodology to calculate a project's GHG emissions in the revised CEQA Guidelines, such as allowing infill projects up to a 50 percent reduction in daily vehicle trips if the reduction can be supported by close proximity to transit and support services or a traffic study prepared for the project.

Table 6 – California 2020 GHG Emissions, Population Projections and GHG EfficiencyThresholds - Land Use Inventory Sectors				
Land Use Sectors Greenhouse Gas Emissions Target	295,530,000			
Population	44,135,923			
Employment	20,194,661			
California Service Population (Population + Employment)	64,330,584			
AB 32 Goal GHG emissions (metric tons CO ₂ e)/SP ¹	4.6			
Notes: $AB = Assembly Bill$; $CO_2e = carbon dioxide equivalent$; $Copolation$. ¹ Greenhouse gas efficiency levels were calculated using only the emissions inventory.	GHG = greenhouse gas; SP = service "land use-related" sectors of ARB's			

Please refer to Appendix D for detailed calculations.

Sources: Data compiled by EDAW 2009, ARB 2009a, DOF 2009, EDD 2009, ICF Jones & Stokes 2009.

Staff proposes a project-level efficiency threshold of 4.6 MT CO₂e/SP, the derivation of which is shown Table 6. This efficiency-based threshold reflects very GHG-efficient projects. As stated previously and below, staff anticipates that significance thresholds (rebuttable presumptions of significance at the project level) will function on an interim basis only until adequate programmatic approaches are in place at the city, county, and regional level that will allow the CEQA streamlining of individual projects. (See Draft CEQA Guidelines, proposed section 15183.5 ["Tiering and Streamlining the Analysis of Greenhouse Gas Emissions"]). In advance of such programmatic approaches, local agencies may wish to apply this efficiency-based recommended threshold with some discretion, taking into account not only the project's efficiency, but also its total GHG emissions. Even where a project is relatively GHG-efficient as compared to other projects, in approving the project, the lead agency is committing to use what is essentially

its GHG "budget" in a given way. Expending this "budget" on the proposed project may affect other development opportunities and associated obligations to mitigate or conflict with other actions that the community may wish to take to reduce its overall GHG emissions after it has conducted its programmatic analysis.

Accordingly, in applying the efficiency-based threshold of 4.6 MT CO₂e/SP, the lead agency might also wish to consider the project's total emissions. Where a project meets the efficiency threshold but would still have very large GHG emissions, the lead agency may wish to consider whether the project's contributions to climate change might still be cumulatively considerable and whether additional changes to the project or mitigation should be required. Staff notes that even where the project may be significant as it relates to climate change, the lead agency may find that the project should nonetheless be approved in light of its benefits; in that case, the lead agency may wish to note the project's efficiency and any innovative design features in the Statement of Overriding Considerations.

2.3.3 PLAN-LEVEL GHG THRESHOLDS

Staff proposes using a two step process for determining the significance of proposed plans and plan amendments for GHG. As discussed above for project-level GHG impacts, Staff is proposing an efficiency threshold to assess plan-level impacts. In addition, as a first step in assessing plan-level impacts, Staff is proposing that agencies that have adopted a qualified climate action plan (or have incorporated similar criteria in their General Plan) and the General Plan or Transportation Plan are consistent with the climate action plan, the General Plan or Transportation Plan would be considered less than significant. Staff believes a programmatic approach to limiting GHG emissions is appropriate at the plan-level. Thus, as projects consistent with the climate action plan are proposed, they may be able to tier off the plan and its environmental analysis.

2.3.3.1 GHG EFFICIENCY METRICS FOR PLANS

For local land use plans, a GHG-efficiency metric (e.g., GHG emissions per unit) would enable comparison of a proposed general plan to its alternatives and to determine if the proposed general plan meets AB 32 emission reduction goals.

AB 32 identifies local governments as essential partners in achieving California's goal to reduce GHG emissions. Local governments have primary authority to plan, zone, approve, and permit how and where land is developed to accommodate population growth and the changing needs of their jurisdiction. ARB has developed the Local Government Operations Protocol and is developing a protocol to estimate community-wide GHG emissions. ARB encourages local governments to use these protocols to track progress in reducing GHG emissions. ARB encourages local governments to institutionalize the community's strategy for reducing its carbon footprint in its general plan. SB 375 creates a process for regional integration of land development patterns and transportation infrastructure planning with the primary goal of reducing GHG emissions from the largest sector of the GHG emission inventory, light duty vehicles.

If the statewide AB 32 GHG emissions reduction context is established, GHG efficiency can be viewed independently from the jurisdiction in which the plan is located. Expressing projected 2020 mass of emissions from land use-related emissions sectors by comparison to a demographic unit (e.g., population and employment) provides evaluation of the GHG efficiency of a project in terms of what emissions are allowable while meeting AB 32 targets.

Two approaches were considered for efficiency metrics. The "service population" (SP) approach would consider efficiency in terms of the GHG emissions compared to the sum of the number of jobs and the number of residents at a point in time. The per capita option would consider efficiency in terms of GHG emissions per resident only. Staff recommends that the efficiency threshold for plans be based on all emission inventory sectors because, unlike land use projects, community-wide or regional plans comprise more than just land use related emissions (e.g. industrial). Further, Staff recommends that plan threshold be based on the service population metric as community-wide plans or regional plans include a mix of residents and employees. The Service Population metric would allow decision makers to compare GHG efficiency of general plan alternatives that vary residential and non-residential development totals, encouraging GHG efficiency through improving jobs/housing balance. This approach would not give preference to communities that accommodate more residential (population-driven) land uses than non-residential (employment driven) land uses which could occur with the per capita approach.

A SP-based GHG efficiency metric was (see Table 7) for the emissions rates at the State level that would accommodate projected growth (as indicated by population and employment growth) under trend forecast conditions, and the emission rates needed to accommodate growth while allowing for consistency with the goals of AB 32 (i.e., 1990 GHG emissions levels by 2020).

Table 7 – California 2020 GHG Emissions, Population Pro Thresholds - All Inventory Sect	ojections and GHG Efficiency ors
All Inventory Sectors Greenhouse Gas Emissions Target	426,500,000
Population	44,135,923
Employment	20,194,661
California Service Population (Population + Employment)	64,330,584
AB 32 Goal GHG emissions (metric tons CO ₂ e)/SP ¹	6.6
Notes: $AB = Assembly Bill$; $CO_2e = carbon dioxide equivalent$; G population. ¹ Greenhouse gas efficiency levels were calculated using only the emissions inventory.	HG = greenhouse gas; SP = service "land use-related" sectors of ARB's
Please refer to Appendix D for detailed calculations	

Sources: Data compiled by EDAW 2009, ARB 2009a, DOF 2009, EDD 2009, ICF Jones & Stokes 2009.

If a general plan demonstrates, through dividing the emissions inventory projections (MT CO_2e) by the amount of growth that would be accommodated in 2020, that it could meet the GHG efficiency metrics proposed in this section (6.6 MT CO_2e /SP from all emission

Bay Area AQMD Proposed Air Quality CEQA Thresholds of Significance November 2, 2009

sectors, as noted in Table 7), then the amount of GHG emissions associated with the general plan would be considered less than significant, regardless of its size (and magnitude of GHG emissions). In other words, the general plan would accommodate growth in a manner that would not hinder the State's ability to achieve AB 32 goals, and thus, would be less than significant for GHG emissions and their contribution to climate change. The efficiency metric would not penalize well-planned communities that propose a large amount of development. Instead, the SP-based GHG efficiency metric acts to encourage the types of development that BAAQMD and OPR support (i.e., infill and transit-oriented development) because it tends to reduce GHG and other air pollutant emissions overall, rather than discourage large developments for being accompanied by a large mass of GHG emissions. Plans that are more GHG efficient would have no or limited mitigation requirements which would help them complete the CEQA process for General Plans and other plans more readily than plans that promote GHG inefficiencies which will require detailed design of mitigation during the CEQA process and could subject a plan to potential challenge as to whether all feasible mitigation was identified and adopted. This type of threshold can shed light on a well-planned general plan that accommodates a large amount of growth in a GHG-efficient way.

When analyzing long-range plans, such as general plans, it is important to note that the planning horizon will often surpass the 2020 timeframe for implementation of AB 32. Executive Order S-3-05 establishes a more aggressive emissions reduction goal for the year 2050 of 80 percent below 1990 emissions levels. The year 2020 should be viewed as a milestone year, and the general plan should not preclude the community from a trajectory toward the 2050 goal. However, the 2020 timeframe is examined in this threshold evaluation because doing so for the 2050 timeframe (with respect to population, employment, and GHG emissions projections) would be too speculative. Advances in technology and policy decisions at the state level will be needed to meet the aggressive 2050 goals. It is beyond the scope of the analysis tools available at this time to examine reasonable emissions reductions that can be achieved through CEQA analysis in the year 2050. As the 2020 timeframe draws nearer, BAAQMD will need to reevaluate the threshold to better represent progress toward 2050 goals.

2.3.4 CLIMATE ACTION PLANS

Finally, many local agencies have already undergone or plan to undergo efforts to create general or other plans that are consistent with AB 32 goals. The District encourages such planning efforts and recognizes that careful upfront planning by local agencies is invaluable to achieving the state's GHG reduction goals. If a project is consistent with an adopted Qualified Climate Action Plan or a Sustainable Communities Strategy (SCS) or Alternative Planning Strategy (APS) developed pursuant to SB 375 that addresses the project's GHG emissions, it can be presumed that the project will not have significant GHG emission impacts. This approach is consistent with CEQA Guidelines Section 15064(h)(3), which provides that a "lead agency may determine that a project's incremental contribution to a cumulative effect is not cumulatively considerable if the project will comply with the requirements in a previously approved plan or mitigation

program which provides specific requirements that will avoid or substantially lessen the cumulative problem."

A qualified Climate Action Plan (or similar adopted policies, ordinances and programs) is one that is consistent with all of the AB 32 Scoping Plan measures and goals. The Climate Action Plan should identify a land use design, transportation network, goals, policies and implementation measures that would achieve AB 32 goals. Plans with horizon years beyond 2020 should consider continuing the downward reduction path set by AB 32 and move toward climate stabilization goals established in Executive Order S-3-05.

Qualified Climate Action Plans

A qualified Climate Action Plan adopted by a local jurisdiction should include the following. The District's revised CEQA Guidelines will provide the methodology to determine if a Climate Action Plan meets these requirements.

- GHG Inventory for Current Year and Forecast for 2020 (and for 1990 if the reduction goal is based on 1990 emission levels).
- An adopted GHG Reduction Goal for 2020 for the jurisdiction from all sources (existing and future) which is at least one of the following: 1990 GHG emission levels, 15 percent below 2008 emission levels, or 28 percent below BAU Forecasts for 2020 (if including non-land use sector emissions in the local inventory; otherwise can use 26.2 percent if only including land use sector emissions).
- Identification of feasible reduction measures to reduce GHG emissions for 2020 to the identified target.
- ► Application of relevant reduction measures included in the AB 32 Scoping Plan that are within the jurisdiction of the local land use authority (such as building energy efficiency, etc.).
- Quantification of the reduction effectiveness of each of the feasible measures identified including disclosure of calculation method and assumptions.
- Identification of implementation steps and financing mechanisms to achieve the identified goal by 2020.
- Procedures for monitoring and updating the GHG inventory and reduction measures at least twice before 2020 or at least every five years.
- ► Identification of responsible parties for Implementation.
- Schedule of implementation.
- ► Certified CEQA document, or equivalent process (see below).

Local Climate Action Policies, Ordinances and Programs

Air District staff recognizes that many communities in the Bay Area have been proactive in planning for climate change but have not yet developed a stand-alone Climate Action Plan that meets the above criteria. Many cities and counties have adopted climate action policies, ordinances and program that may in fact achieve the goals of a qualified climate action plan. Staff recommends that if a local jurisdiction can demonstrate that its collective set of climate action policies, ordinances and other programs is consistent with AB 32, includes requirements or feasible measures to reduce GHG emissions and achieves one of the following GHG emission reduction goals,³ the AB 32 consistency demonstration should be considered equivalent to a qualified climate action plan:

- ► 1990 GHG emission levels,
- ▶ 15 percent below 2008 emission levels, or
- 28 percent below BAU Forecasts for 2020 (if including non-land use sector emissions in the local inventory; otherwise can use 26.2 percent if only including land use sector emissions).

Sustainable Communities Strategy or Alternative Planning Strategy

A SCS (or APS) adopted pursuant to SB 375 must have the following characteristics:

- ► must meet the ARB identified reduction target;
- ▶ must have been adopted by the Metropolitan Planning Organization (MPO); and
- certification of the EIR for the associated Regional Transportation Plan (RTP) must be completed.

Qualified Climate Action Plans, SCSs or APSs are tied to the AB 32 reduction goals, would promote reductions on a plan level without impeding the implementation of GHG– efficient development, and would recognize the initiative of many Bay Area communities who have already developed or are in the process of developing a GHG reduction plan. The details required above for a qualified Climate Action Plan (or similar adopted policies, ordinances and programs) would provide the evidentiary basis for making CEQA findings that development consistent with the plan would result in feasible, measureable, and verifiable GHG reductions consistent with broad state goals such that projects approved under qualified Climate Action Plans or equivalent demonstrations would achieve their fair share of GHG emission reductions.

³ Lead agencies using consistency with their jurisdiction's climate action policies, ordinances and programs as a measure of significance under CEQA Guidelines section 15064(h)(3) should check to make sure that the policies, ordinances and programs satisfy all of the requirements of that subsection before relying on them in a CEQA analysis.

2.3.5 STATIONARY SOURCE GHG THRESHOLD

Staff's recommended threshold for stationary source GHG emissions is based on estimating the GHG emissions from combustion sources for all permit applications submitted to the Air District in 2005, 2006 and 2007. The analysis is based only on CO_2 emissions from stationary sources, as that would cover the vast majority of the GHG emissions due to stationary combustion sources in the SFBAAB. The estimated CO_2 emissions were calculated for the maximum permitted amount, i.e. emissions that would be emitted if the sources applying for a permit application operate at maximum permitted load and for the total permitted hours. All fuel types are included in the estimates. For boilers burning natural gas is not available. Emission values are estimated before any offsets (i.e., Emission Reduction Credits) are applied. GHG emissions from mobile sources, electricity use and water delivery associated with the operation of the permitted sources are not included in the estimates.

It is projected that a threshold level of 10,000 metric tons of CO_2e per year would capture approximately 95 percent of all GHG emissions from stationary sources in the SFBAAB. That threshold level was calculated as an average of the combined CO_2 emissions from all stationary source permit applications submitted to the Air District during the three year analysis period.



Figure 1 – Natural Gas Combustion Emissions from Stationary Sources in the SFBAAB

Staff recommends this 10,000 MT of CO_2/yr as it would address a broad range of combustion sources and thus provide for a greater amount of GHG reductions to be captured and mitigated through the CEQA process. As documented in the Scoping Plan, in order to achieve statewide reduction targets, emissions reductions need to be obtained through a broad range of sources throughout the California economy and this threshold would achieve this purpose.

This threshold would be considered an interim threshold and Air District staff will reevaluate the threshold as AB 32 Scoping Plan measures such as Cap and Trade are more fully developed at the state level.

2.3.6 SUMMARY OF JUSTIFICATION FOR GHG THRESHOLDS

The bright-line numeric threshold of 1.100 MT CO_{2} e/vr is a numeric emissions level below which a project's contribution to global climate change would be less than "cumulatively considerable." This emissions rate is equivalent to a project size of approximately 60 single-family dwelling units, and approximately 59 percent of all future projects and 92 percent of all emissions from future projects would exceed this level. For projects that are above this bright-line cutoff level, emissions from these projects would still be less than cumulatively significant if the project as a whole would result in an efficiency of 4.6 MT CO₂e per service population or better for mixed-use projects. Projects with emissions above 1,100 MT CO₂e/yr would therefore still be less than significant if they achieved project efficiencies below these levels. If projects as proposed exceed these levels, they would be required to implement mitigation measures to bring them back below the 1,100 MT CO₂e/yr bright-line cutoff or within the 4.6 MT CO₂e Service Population efficiency threshold. If mitigation did not bring a project back within the threshold requirements, the project would be cumulatively significant and could be approved only with a Statement of Overriding Considerations and a showing that all feasible mitigation measures have been implemented. A projects' GHG emissions would also be less than significant if they comply with a Qualified Climate Action Plan, SCS or APS that applies to the project.

As explained in the preceding analyses of these thresholds, the greenhouse gas emissions from land use projects expected between now and 2020 built in compliance with these thresholds would be approximately 26 percent below BAU 2020 conditions and thus would be consistent with achieving an AB 32 equivalent reduction. The 26 percent reduction from BAU 2020 from new projects built in conformance with these proposed thresholds would achieve an aggregate reduction of approximately 1.6 MMT CO_2e/yr , which is the level of emission reductions from new Bay Area land use sources needed to meet the AB 32 goals, per ARB's Scoping Plan as discussed above.

Projects with greenhouse gas emissions in conformance with these proposed thresholds would therefore not be considered significant for purposes of CEQA. Although the emissions from such projects would add an incremental amount to the overall greenhouse gas emissions that cause global climate change impacts, emissions from projects consistent with these thresholds would not be a "cumulatively considerable" contribution under CEQA. Such projects would not be "cumulatively considerable" because they would be helping to solve the cumulative problem as a part of the AB 32 process.

California's response to the problem of global climate change is to reduce greenhouse gas emissions to 1990 levels by 2020 under AB 32 as a near-term measure and ultimately to 80 percent below 1990 levels by 2050 as the long-term solution to stabilizing greenhouse gas concentrations in the atmosphere at a level that will not cause unacceptable climate change impacts. To implement this solution, the Air Resources Board has adopted a Scoping Plan and budgeted emissions reductions that will be needed from all sectors of society in order to reach the interim 2020 target.

The land-use sector in the Bay Area needs to achieve aggregate emission reductions of approximately 1.6 MMT CO₂e/yr from new projects between now and 2020 to achieve this goal, as noted above, and each individual new project will need to achieve its own respective portion of this amount in order for the Bay Area land use sector as a whole to achieve its allocated emissions target. Building all of the new projects expected in the Bay Area between now and 2020 in accordance with the thresholds that District staff are proposing will achieve the overall appropriate share for the land use sector, and building each individual project in accordance with the proposed thresholds will achieve that individual project's respective portion of the emission reductions needed to implement the AB 32 solution. For these reasons, projects built in conformance with the proposed thresholds will be part of the solution to the cumulative problem, and not part of the continuing problem. They will allow the Bay Area's land use sector to achieve the emission reductions necessary from that sector for California to implement its solution to the cumulative problem of global climate change. As such, even though such projects will add an incremental amount of greenhouse gas emissions, their incremental contribution will be less than "cumulatively considerable" because they are helping to achieve the cumulative solution, not hindering it. Such projects will therefore not be "significant" for purposes of CEQA. (See CEQA Guidelines §15064(h)(1).)

The conclusion that land use projects that comply with these proposed thresholds is also supported by CEQA Guidelines Section 15030(a)(3), which provides that a project's contribution to a cumulative problem can be less that cumulatively considerable "if the project is required to implement or fund its fair share of a mitigation measure or measures designed to alleviate the cumulative impact." In the case of greenhouse gas emissions associated with land use projects, achieving the amount of emission reductions below BAU that will be required to achieve the AB 32 goals is the project's "fair share" of the overall emission reductions needed under ARB's scoping plan to reach the overall statewide AB 32 emissions levels for 2020. If a project is designed to implement greenhouse gas mitigation measures that achieve a level of reductions consistent with what is required from all new land use projects to achieve the land use sector "budget" – *i.e.*, keeping overall project emissions below 1,100 MT CO₂e/yr or ensuring that project efficiency is better than 4.6 MT CO₂e/service population – then it will be implementing its share of the mitigation measures necessary to alleviate the cumulative impact, as shown in the analyses set forth above.

It is also worth noting that this "fair share" approach is flexible and will allow a project's significance to be determined by how well it is designed from a greenhouse-gas efficiency standpoint, and not just by the project's size. For example, a large high-density infill project located in an urban core nearby to public transit and other alternative transportation options, and built using state-of-the-art energy efficiency methods and improvements such as solar panels, as well as all other feasible mitigation measures, would not become significant for greenhouse gas purposes (and thus require a Statement of Overriding Considerations in order to be approved) simply because it happened to be a large project. Projects such as this hypothetical development with low greenhouse-gas emissions per service population are what California will need in the future in order to do its part in achieving a solution to the problem of global climate change. The determination of significance under CEQA should therefore take these factors into account, and staff's proposed significance thresholds would achieve this important policy goal.

3 COMMUNITY RISK AND HAZARD THRESHOLDS

To address community risk from air toxics, the Air District initiated the Community Air Risk Evaluation (CARE) program in 2004 to identify locations with high levels of risk from ambient toxic air contaminants (TAC) co-located with sensitive populations and use the information to help focus mitigation measures. In the first phase of the CARE program, the Air District developed an inventory of TAC emissions for 2005 and compiled demographic and heath indicator data. According to the findings of the Air District's Community Air Risk Evaluation (CARE) Program, diesel PM—mostly from on and off-road mobile sources—accounts for over 80 percent of the inhalation cancer risk from TACs in the Bay Area.

The Air District applied a regional air quality model using the 2005 emission inventory data to estimate excess cancer risk from ambient concentrations of important TAC species, including diesel PM, 1,3-butadiene, benzene, formaldehyde and acetaldehyde. Priority communities within the Bay Area defined as having higher emitting sources, highest air concentrations, and nearby low income and sensitive populations include the urban core areas of Concord, eastern San Francisco, western Alameda County, Redwood City/East Palo Alto, Richmond/San Pablo, and San Jose (BAAQMD 2006). The highest cancer risk levels from ambient TAC in the Bay Area also tend to occur in the core urban areas, along major roadways and adjacent to freeways. Cancer risks in areas along these major freeways are estimated to range from 200 to over 500 excess cases in a million.

Fifty percent of BAAQMD's population is estimated to have an ambient background inhalation cancer risk of less than 500 cases in one million. Table 8 presents a summary of percentages of the population exposed to varying levels of cancer risk from ambient TACs. Approximately two percent of the SFBAAB population is exposed to background risk levels of less than 200 excess cases in one million. This is in contrast to the upper percentile ranges where eight percent of the SFBAAB population is exposed to background risk levels of greater than 1,000 excess cases per one million.

Table 8 – Statistical Summary of Population-Weighted Ambient Cancer Risk				
Percentage of Population (Percent below level of ambient risk)	Ambient Cancer Risk (inhalation cancer cases in one million)			
92	1,000			
90	900			
83	800			
77	700			
63	600			
50	500			
32	400			
13	300			
2	200			
0	100			
Source: Data compiled by EDAW 2009.				

3.2 PROPOSED THRESHOLDS OF SIGNIFICANCE

Project Type	Individual Project Threshold	Cumulative Threshold
	Compliance with Qualified Community Risk Reduction Plan	Compliance with Qualified Community Risk Reduction Plan
Construction	OR	OR
Land Use (Source and Receptor) Stationary Source	Cancer Risk >10 in a million and Non-Cancer Hazard Index >1.0 and PM _{2.5} level > 0.3 µg/m ³ (annual average)	Cancer Risk > 100 in a million and Non-cancer Hazard Index > 1.0 and $PM_{2.5}$ level > 0.8 µg/m ³ (annual average)
	Zone of Influence: 1,000-foot radius from fence line of source or receptor	Zone of Influence: 1,000-foot radius from fence line of source or receptor
Accidental Release of Acutely Hazardous Air Pollutants	Storage or use of acutely hazardous materials locating near receptors or receptors locating near stored or used acutely hazardous materials considered significant	
Plans	 <u>Identify (Overlay Zones) and include policies to reduce the impacts for:</u> 1. Existing or planned sources of risks and hazards; 2. Community Risk Reduction Plan areas; and 3. 500 feet (or Air District-approved modeled distance) on each side of all freeways and high volume roadways 	

3.3 JUSTIFICATION AND SUBSTANTIAL EVIDENCE SUPPORTING THRESHOLDS

The goal of the proposed thresholds is to ensure that no source creates, or receptor endures, a significant adverse impact from any individual project, and that the total of all nearby directly emitted risk and hazard emissions is also not significantly adverse.

A project proposing a new source or receptor would need to assess their impact within 1,000 feet, taking into account both its individual and nearby cumulative sources (i.e. proposed project plus existing and foreseeable future projects). Cumulative sources are the combined total risk values of each individual source within the 1,000-foot evaluation zone. A lead agency is encouraged to enlarge the 1,000-foot radius on a case-by-case basis if an unusually large source of risk or hazard emissions that may affect a proposed project is beyond the recommended radius.

The 1,000 foot distance was selected based on several factors. A summary of research findings in CARB's Land Use Compatibility Handbook (CARB 2005) indicates that traffic-related pollutants were higher than regional levels within approximately 1,000 feet downwind and that differences in health-related effects (such as asthma, bronchitis, reduced lung function, and increased medical visits) could be attributed in part to the proximity to heavy vehicle and truck traffic within 300 to 1,000 feet of receptors. Although CARB has recommended avoiding siting sensitive land uses within 500 feet of a freeway or high-volume urban roads, this approach uses 1,000 feet based on research that has indicated increased health effects in some cases out to as far as 1,000 feet. In the same study, CARB recommended avoiding siting sensitive land uses within 1,000 feet of a distribution center and major rail yard, which supports the use of a 1,000 feet evaluation distance in case such sources may be relevant to a particular project setting. A second consideration is that studies have shown that the concentrations of particulate matter tends to be reduced substantially or can even be indistinguishable from upwind background concentrations a distance 1,000 feet downwind from sources such as freeways or large distribution centers (Zhu et al. 2002, CARB 2005). Finally, a 1,000 foot zone of influence is also supported by Health & Safety Code §42301.6 (Notice for Possible Source Near School).

3.3.1 CONSTRUCTION, LAND USE AND STATIONARY SOURCE RISK AND HAZARD THRESHOLDS

Staff is proposing thresholds based on EPA's guidance for conducting air toxics analyses and making risk management decisions at the facility and community-scale level. The proposed thresholds would apply to both siting new sources and siting new receptors.

The proposed thresholds would consider projects consistent with a qualified Community Risk Reduction Plan (CRRP) adopted by the local jurisdiction that includes enforceable measures to reduce the community risk to acceptable levels to be less than significant. Proposed development projects that are not consistent with a CRRP that has been adopted for the area where the project is proposed to be located would be considered to have a significant impact.

Projects proposed in areas where a CRRP has not been adopted and the potential exits to expose sensitive receptors or the general public to emissions-related risk in excess of the following thresholds from any source would be considered to have a significant air quality impact:

- ► Increased Cancer Risk to Maximally Exposed Individual (MEI) Emissions from a new source or emissions affecting a new receptor would be considered significant where ground-level concentrations of carcinogenic TACs from any source result in an increased cancer risk greater than 10.0 in one million.
- ► Increased Non-Cancer Risk to MEI Emissions from a new source or emissions affecting a new receptor would be considered significant where ground-level concentrations of non-carcinogenic TACs result in an increased chronic or acute Hazard Index from any source greater than 1.0.
- Increased Ambient Concentration of $PM_{2.5}$ Emissions from a new source or emissions affecting a new receptor would be considered significant where ground-level concentrations of $PM_{2.5}$ from any source would result in an average annual increase greater than $0.3 \ \mu g/m^3$.

The conclusion that land use projects that comply with qualified Community Risk Reduction Plans are less than significant is supported by CEQA Guidelines Sections 15030(a)(3) and 15064(h)(3), which provides that a project's contribution to a cumulative problem can be less that cumulatively considerable if the project is required to implement or fund its fair share of a mitigation measure or measures designed to alleviate the cumulative impact.

The 10.0 in one million cancer risk and 1.0 hazard index threshold is supported by EPA's guidance for conducting air toxics analyses and making risk management decisions at the facility and community-scale level which considers a range of acceptable cancer risks from one in a million to one in ten thousand (100 in a million). The guidance considers an acceptable range of cancer risks to be from one in a million to one in ten thousand. In protecting public health with an ample margin of safety, EPA strives to provide maximum feasible protection against risks to health from hazardous air pollutants (HAPs) by limiting risk to a level no higher than the one in ten thousand estimated risk that a person living near a source would be exposed to at the maximum pollutant concentrations for 70 years. This goal is described in the preamble to the benzene National Emissions Standards for Hazardous Air Pollutants (NESHAP) rulemaking (54 Federal Register 38044, September 14, 1989) and is incorporated by Congress for EPA's residual risk program under Clean Air Act (CAA) section 112(f).

The proposed thresholds would be protective of ambient air quality through the inclusion of a $PM_{2.5}$ threshold. Further, by providing an ambient threshold for $PM_{2.5}$, this approach

would establish a bright line standard concerning particulate exposure that is consistent with EPA permitting requirements for stationary sources. The proposed threshold is an annual average increase in PM_{2.5} emissions of $0.3 \ \mu g/m^3$. This concentration is the U.S. EPA Significant Impact level (SIL) for PM_{2.5}. The SIL is a threshold applied to individual facilities that apply for a permit to emit a regulated pollutant in an area that meets the NAAQS. The state and EPA must determine if emissions from that facility will cause the air quality to worsen. If an individual facility projects an increase in emissions that result in ambient impacts greater than the established SIL, the permit applicant would be required to perform additional analyses to determine if those impacts will be more than the amount of the PSD increment. This analysis would combine the impact of the proposed facility when added on to all other sources in the area.

3.3.1.1 ACCIDENTAL RELEASE OF ACUTELY HAZARDOUS AIR EMISSIONS

The BAAQMD currently recommends, at a minimum, that the lead agency, in consultation with the administering agency of the Risk Management Prevention Program (RMPP), find that any project resulting in receptors being within the Emergency Response Planning Guidelines (ERPG) exposure level 2 for a facility has a significant air quality impact. ERPG exposure level 2 is defined as "the maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour without experiencing or developing irreversible or other serious health effects or symptoms which could impair an individual's ability to take protective action."

Staff proposes continuing with the current threshold for the accidental release of hazardous air pollutants. Staff recommends that agencies consult with the California Emergency Management Agency for the most recent guidelines and regulations for the storage of hazardous materials. Staff proposes that projects using or storing acutely hazardous materials locating near existing receptors, and projects resulting in receptors locating near facilities using or storing acutely hazardous materials be considered significant.

The current Accidental Release/Hazardous Air Emissions threshold of significance could affect all projects, regardless of size, and require mitigation for Accidental Release/Hazardous Air Emissions impacts.

3.3.2 CUMULATIVE RISK AND HAZARD THRESHOLDS

Projects consistent with a qualified CRRP adopted by the local jurisdiction that includes enforceable measures to reduce the community risk to acceptable levels would be considered less than significant.

Proposed development projects that are not consistent with a CRRP that has been adopted for the area where the project is proposed to be located would be considered to have a significant impact.

Projects proposed in areas where a CRRP has not been adopted and the potential to expose sensitive receptors or the general public to emissions-related risk in excess of the

following thresholds from the aggregate of cumulative sources would be considered to have a significant air quality impact.

- ► Increased Cancer Risk to Maximally Exposed Individual (MEI) Emissions from a new source or emissions affecting a new receptor would be considered significant where ground-level concentrations of carcinogenic TACs from any source result in an increased cancer risk greater than 100.0 in one million.
- ► Increased Non-Cancer Risk to MEI Emissions from a new source or emissions affecting a new receptor would be considered significant where ground-level concentrations of non-carcinogenic TACs result in an increased chronic or acute Hazard Index from any source greater than 1.0.
- Increased Ambient Concentration of $PM_{2.5}$ Emissions from a new source or emissions affecting a new receptor would be considered significant where ground-level concentrations of $PM_{2.5}$ from any source would result in an average annual increase greater than $0.8 \,\mu\text{g/m}^3$.

The significance threshold of 100 in a million increased excess cancer risk and Hazard Index of 1.0 would be applied to the cumulative emissions. The 100 in a million threshold is based on EPA guidance for conducting air toxics analyses and making risk management decisions at the facility and community-scale level. The guidance considers an acceptable range of cancer risks to be from one in a million to one in ten thousand. In protecting public health with an ample margin of safety, EPA strives to provide maximum feasible protection against risks to health from hazardous air pollutants (HAPs) by limiting risk to a level no higher than the one in ten thousand (100 in a million) estimated risk that a person living near a source would be exposed to at the maximum pollutant concentrations for 70 years. This goal is described in the preamble to the benzene National Emissions Standards for Hazardous Air Pollutants (NESHAP) rulemaking (54 Federal Register 38044, September 14, 1989) and is incorporated by Congress for EPA's residual risk program under Clean Air Act (CAA) section 112(f). The 100 in a million excess cancer cases is also consistent with the ambient cancer risk in the most pristine portions of the Bay Area based on the District's recent regional modeling analysis.

The 0.8 μ g/m³ threshold is supported by EPA's proposed cumulative PSD threshold for all PM_{2.5} sources and studies that examined the potential health impacts of roadway particles. This threshold level is appropriate for promoting review of emissions sources to prevent deterioration of air quality. Using existing and EPA-proposed environmental standards in this way to establish CEQA thresholds of significance is an appropriate and effective means of promoting consistency in significance determinations and integrating CEQA environmental review activities with other areas of environmental regulation.

The PM_{2.5} concentration level of 0.8 μ g/m³ is based on a proposed rule being evaluated by U.S. EPA in developing significant impacts levels (SILs) for prevention of significant deterioration for particulate matter less than 2.5 micrometers (Federal Register 40 CFR Parts 51 and 52, September 21, 2007). EPA is proposing a PSD threshold of 0.8 μ g/m³ as the cumulative threshold for all $PM_{2.5}$ sources. The 0.8 µg/m³ standard was developed by scaling the PM_{10} SIL values by the ratio of direct $PM_{2.5}$ to direct PM_{10} emissions. The $PM_{2.5}/PM_{10}$ emissions ratio is based on the national average derived from the 2001 extrapolation of the EPA's 1999 National Emissions Inventory. The District believes that the 0.80 µg/m³, which is based on direct PM emissions, is more representative of the mixture of PM sources in the Bay Area. In a recent PM study, the Air District found that direct emissions from wood burning and fossil fuel combustion contribute over one-half of annual $PM_{2.5}$ emissions. This threshold is also consistent with the estimated California background level and the estimated background level of the more remote areas of the Bay Area. The rationale for selecting 1,000 feet was explained in the discussion of Option 2 for siting new receptors above.

This threshold is also supported from several medical research studies that have linked near-road pollution exposure to a variety of adverse health outcomes impacting children and adults. One notable study conducted by Dr. Michael Kleinman and colleagues at the EPA-funded Southern California Particle Center studied the potential of roadway particles to aggravate allergic and immune responses in mice. Using mice that were not inherently susceptible, the researchers placed these mice at various distances downwind of State Road 60 and Interstate 5 freeways to test the effect these roadway particles have on their immune system. They found that within 5 meters of the roadway, there was a significant allergic response and elevated production of specific antibodies. At 150 meters (492 feet) and 500 meters (1,640 feet) downwind of the roadway, these effects were not statistically significant.

In another significant study, the University of Washington (Ven Hee et al, 2009) conducted a survey involving 3,827 participants that aimed to determine the effect of residential traffic exposure on two preclinical indicators of heart failure; left ventricular mass index (LVMI), measured by the cardiac magnetic resonance imaging (MRI), and ejection fraction. The studies classified participants based on the distance between their residence and the nearest interstate highway, state or local highway, or major arterial road. Four distance groups were defined: less than 50 meters (165 feet), 50-100 meters, 101-150 meters, and greater than 150 meters. After adjusting for demographics, behavioral, and clinical covariates, the study found that living within 50 meters of a major roadway was associated with a 1.4 g/m^2 higher LVMI than living more than 150 meters from one. This suggests an association between traffic-related air pollution and increased prevalence of a preclinical predictor of heart failure among people living near roadways.

To quantify the roadway concentrations that are contributing to the health impacts, the Air District modeled the scenario studied by Dr. Kleinman. In Dr. Kleinman's study emissions were estimated for Los Angeles using the EMFAC model. Annual average vehicle traffic data taken from Caltrans was used in the roadway model (CAL3QHCR) to estimate the downwind $PM_{2.5}$ concentrations at 50 meters and 150 meters. Additionally, emissions were assumed to occur from 10:00 a.m. to 2:00 p.m. corresponding to the time in which the mice were exposed during the study. The results of the modeling indicate

that at 150 meters, the downwind concentration is 0.78 μ g/m³, which is consistent with the EPA-recommended SIL of 0.8 μ g/m³.

3.3.3 PLAN-LEVEL RISK AND HAZARD THRESHOLDS

Staff proposes plan-level thresholds that will encourage a programmatic approach to addressing the overall adverse conditions resulting from risks and hazards that many Bay Area communities experience. By designating overlay zones in land use plans, local land use jurisdictions can take preemptive action before project-level review to reduce the potential for significant exposures to risk and hazard emissions. While this will require more up-front work at the general plan level, in the long-run this approach is a more feasible approach consistent with District and CARB guidance about siting sources and sensitive receptors that is more effective than project by project consideration of effects that often has more limited mitigation opportunities. This approach would also promote more robust cumulative consideration of effects of both existing and future development for the plan-level CEQA analysis as well as subsequent project-level analysis.

For local plans to have a less-than-significant impact with respect to potential risks and hazards, overlay zones would have to be established around existing and proposed land uses that would emit these air pollutants. Overlay zones to avoid risk impacts should be reflected in local plan policies, land use map(s), and implementing ordinances (e.g., zoning ordinance). The overlay zones around existing and future risk sources would be delineated using the quantitative approaches described above for project-level review and the resultant risk buffers would be included in the General Plan (or the EIR for the General Plan) to assist in site planning. BAAQMD will provide guidance as to the methods used to establish the TAC buffers and what standards to be applied for acceptable exposure level in the updated CEQA Guidelines document. Special overlay zones of at least 500 feet (or an appropriate distance determined by modeling and approved by the Air District) on each side of all freeways and high volume roadways would be included in this proposed threshold.

The threshold of significance for plan impacts could affect all plan adoptions and amendments and require mitigation for a plan's air quality impacts. Where sensitive receptors would be exposed above the acceptable exposure level, the plan impacts would be considered significant and mitigation would be required to be imposed either at the plan level (through policy) or at the project level (through project level requirements).

3.3.4 COMMUNITY RISK REDUCTION PLANS

The goal of a Community Risk Reduction Plan would be to bring TAC and $PM_{2.5}$ concentrations for the entire community covered by the Plan down to acceptable levels as identified by the local jurisdiction and approved by the Air District. This approach provides local agencies a proactive alternative to addressing communities with high levels of risk on a project-by-project approach. This approach is supported by CEQA Guidelines Section 15030(a)(3), which provides that a project's contribution to a cumulative problem can be less than cumulatively considerable "if the project is required

to implement or fund its fair share of a mitigation measure or measures designed to alleviate the cumulative impact." This approach is also further supported by CEQA Guidelines Section 15064(h)(3), which provides that a project's contribution to a cumulative effect is not considerable "if the project will comply with the requirements in a previously approved plan or mitigation program which provides specific requirements that will avoid or substantially lessen the cumulative problem."

Qualified Community Risk Reduction Plans

A qualified Community Risk Reduction Plan adopted by a local jurisdiction should:

- ► Evaluate current and future emissions and concentrations of TACs and PM_{2.5}.
- Establish risk and exposure reduction targets for the community, including for subareas located near sources of air pollution.
- ► Identify measures to reduce exposures.
- ► Identify implementation measures to reduce exposures.
- Includes procedures for monitoring and updating the TAC inventory, modeling and reduction measures, in coordination with Air District staff.
- ► Include a certified CEQA document.

4 CRITERIA POLLUTANT THRESHOLDS

4.2 **PROPOSED THRESHOLDS OF SIGNIFICANCE**

Project Construction				
Pollutant	Average Daily (pounds/day)			
ROG (reactive organic gases)	54			
NO_X (nitrogen oxides)	54			
PM ₁₀ (exhaust) (particulate matter-10 microns)	82			
PM _{2.5} (exhaust) (particulate matter-2.5 microns)	54			
$PM_{10}/PM_{2.5}$ (fugitive dust)	Best Management Practices			
Local CO (carbon monoxide)	None			

Project Operations			
Pollutant	Average Daily (pounds/day)	Maximum Annual (tons/year)	
ROG	54	10	
NO _X	54	10	
PM_{10}	82	15	
PM _{2.5}	54	10	
Local CO	9.0 ppm (8-hour average), 20.0 ppm (1-hour average)		

Plans 1. Consistency with Current Air Quality Plan control measures 2. Projected VMT or vehicle trip increase is less than or equal to projected population increase

4.3 JUSTIFICATION AND SUBSTANTIAL EVIDENCE SUPPORTING THRESHOLDS

4.3.1 **PROJECT CONSTRUCTION CRITERIA POLLUTANT THRESHOLDS**

Staff proposes criteria pollutant construction thresholds that add significance criteria for exhaust emissions to the existing fugitive dust criteria employed by the Air District. While our current Guidelines considered construction exhaust emissions controlled by the overall air quality plan, the implementation of new and more stringent state and federal standards over the past ten years now warrants additional control of this source of emissions.

The average daily criteria air pollutant and precursor emission levels shown above are recommended as the thresholds of significance for construction activity for exhaust emissions. These thresholds represent the levels above which a project's individual emissions would result in a considerable contribution (i.e., significant) to the SFBAAB's existing non-attainment air quality conditions and thus establish a nexus to regional air quality impacts that satisfies CEQA requirements for evidence-based determinations of significant impacts.

For fugitive dust emissions, staff recommends following the current best management practices approach which has been a pragmatic and effective approach to the control of fugitive dust emissions. Studies have demonstrated (Western Regional Air Partnership, U.S.EPA) that the application of best management practices at construction sites have significantly controlled fugitive dust emissions. Individual measures have been shown to reduce fugitive dust by anywhere from 30 percent to more than 90 percent. In the aggregate best management practices will substantially reduce fugitive dust emissions from construction sites. These studies support staff's recommendation that projects implementing construction best management practices will reduce fugitive dust emissions to a less than significant level.

4.3.2 **PROJECT OPERATION CRITERIA POLLUTANT THRESHOLDS**

The proposed thresholds for project operations are the average daily and maximum annual criteria air pollutant and precursor levels shown above. These thresholds are based on the federal BAAQMD Offset Requirements to ozone precursors for which the SFBAAB is designated as a non-attainment area which is an appropriate approach to prevent further deterioration of ambient air quality and thus has nexus and proportionality to prevention of a regionally cumulative significant impact (e.g. worsened status of nonattainment). Despite non-attainment area for state PM_{10} and pending nonattainment for federal PM_{2.5}, the federal NSR Significant Emission Rate annual limits of 15 and 10 tons per year, respectively, are proposed thresholds as BAAQMD has not established an Offset Requirement limit for PM_{2.5} and the existing limit of 100 tons per year is much less stringent and would not be appropriate in light of our pending nonattainment designation for the federal 24-hour PM_{2.5} standard. These thresholds represent the emission levels above which a project's individual emissions would result in a cumulatively considerable contribution to the SFBAAB's existing air quality conditions. The thresholds would be an evaluation of the incremental contribution of a project to a significant cumulative impact. These threshold levels are well-established in terms of existing regulations as promoting review of emissions sources to prevent cumulative deterioration of air quality. Using existing environmental standards in this way to establish CEOA thresholds of significance under Guidelines section 15067.4 is an appropriate and effective means of promoting consistency in significance determinations and integrating CEQA environmental review activities with other areas of environmental regulation. (See Communities for a Better Environment v. California Resources Agency (2002) 103 Cal. App. 4th 98, 111.⁴)

⁴ The Court of Appeal in the *Communities for a Better Environment* case held that existing regulatory standards could not be used as a definitive determination of whether a project would be significant under CEQA where there is substantial evidence to the contrary. Staff's proposed thresholds would not do that. The thresholds are levels at which a project's emissions would normally be significant, but would not be binding on a lead agency if there is contrary evidence in the record.

4.3.3 LOCAL CARBON MONOXIDE THRESHOLDS

The proposed carbon monoxide thresholds are based solely on ambient concentration limits set by the California Clean Air Act for Carbon Monoxide and Appendix G of the State of California CEQA Guidelines.

Since the ambient air quality standards are health-based (i.e., protective of public health), there is substantial evidence (i.e., health studies that the standards are based on) in support of their use as CEQA significance thresholds. The use of the ambient standard would relate directly to the CEQA checklist question. By not using a proxy standard, there would be a definitive bright line about what is or is not a significant impact and that line would be set using a health-based level.

The CAAQS of 20.0 ppm and 9 ppm for 1-hour and 8-hour CO, respectively, would be used as the thresholds of significance for localized concentrations of CO. Carbon monoxide is a directly emitted pollutant with primarily localized adverse effects when concentrations exceed the health based standards established by the California Air Resources Board (ARB).

In addition, Appendix G of the State of California CEQA Guidelines includes the checklist question: Would the project violate any air quality standard or contribute substantially to an existing or projected air quality violation? Answering yes to this question would indicate that the project would result in a significant impact under CEQA. The use of the ambient standard would relate directly to this checklist question.

4.3.4 PLAN-LEVEL CRITERIA POLLUTANT THRESHOLDS

This proposed threshold achieves the same goals as the Air District's current approach while alleviating the existing analytical difficulties and the inconsistency of comparing a plan update with AQP growth projections that may be up to several years old. Eliminating the analytical inconsistency provides better nexus and proportionality for evaluating air quality impacts for plans.

Over the years staff has received comments on the difficulties inherent in the current approach regarding the consistency tests for population and VMT growth. First, the population growth estimates used in the most recent AQP can be up to several years older than growth estimates used in a recent plan update, creating an inconsistency in this analysis. Staff recommends that this test of consistency be eliminated because the Air District and local jurisdictions all use regional population growth estimates that are disaggregated to local cities and counties. In addition, the impact to air quality is not necessarily growth but where that growth is located. The second test, rate of increase in vehicle use compared to growth rate, will determine if planned growth will impact air quality. Compact infill development inherently has less vehicle travel and more transit opportunities than suburban sprawl. Second, the consistency test of comparing the rate of increase in VMT to the rate of increase in population has been problematic at times for practitioners because VMT is not always available with the project analysis. Staff recommends that either the rate of increase in VMT or vehicle trips be compared to the rate of increase in population. Staff also recommends that the growth estimates used in this analysis be for the years covered by the plan. Staff also recommends that the growth estimates be obtained from the Association of Bay Area Governments since the Air District uses ABAG growth estimates for air quality planning purposes.

5 ODOR THRESHOLDS

5.2 **PROPOSED THRESHOLDS OF SIGNIFICANCE**

Project Operations – Source or Receptor	Plans
 More than one confirmed complaint per year averaged over a three year period; or More than three unconfirmed complaints per year averaged over a three year period 	Identify (Overlay Zones) and include policies to reduce the impacts of existing or planned sources of odors

5.3 JUSTIFICATION AND SUBSTANTIAL EVIDENCE SUPPORTING THRESHOLDS

Staff proposes continuing the current CEQA significance threshold for odors (based on complaint history). The current approach has proven adaptable to different projects and locations and thus continuation of the current approach with more qualitative guidance is considered an appropriate approach to CEQA evaluation.

Odors are generally considered a nuisance, but can result in a public health concern. Some land uses that are needed to provide services to the population of an area can result in offensive odors, such as filling portable propane tanks or recycling center operations. When a proposed project includes the siting of sensitive receptors in proximity to an existing odor source, or when siting a new source of potential odors, the following qualitative evaluation should be performed.

When determining whether potential for odor impacts exists, it is recommended that Lead Agencies consider the following factors and make a determination based on evidence in each qualitative analysis category:

• **Distance**: Use the screening-level distances in Table 9.

- Wind Direction: Consider whether sensitive receptors are located upwind or downwind from the source for the most of the year. If odor occurrences associated with the source are seasonal in nature, consider whether sensitive receptors are located downwind during the season in which odor emissions occur.
- Complaint History: Consider whether there is a history of complaints associated with the source. If there is no complaint history associated with a particular source (perhaps because sensitive receptors do not already exist in proximity to the source), consider complaint-history associated with other similar sources in BAAQMD's jurisdiction with potential to emit the same or similar types of odorous chemicals or compounds, or that accommodate similar types of processes.
- Character of Source: Consider the character of the odor source, for example, the type of odor events according to duration of exposure or averaging time (e.g., continuous release, frequent release events, or infrequent events).
- **Exposure:** Consider whether the project would result in the exposure of a substantial number of people to odorous emissions.

Table 9 – Screening Distances for Potential Odor Sources			
Type of Operation Project Screening	Distance		
Wastewater Treatment Plant	2 miles		
Wastewater Pumping Facilities	1 mile		
Sanitary Landfill	2 miles		
Transfer Station	1 mile		
Composting Facility	1 mile		
Petroleum Refinery	2 miles		
Asphalt Batch Plant	2 miles		
Chemical Manufacturing	2 miles		
Fiberglass Manufacturing	1 mile		
Painting/Coating Operations	1 mile		
Rendering Plant	2 miles		
Coffee Roaster	1 mile		
Food Processing Facility	1 mile		
Confined Animal Facility/Feed Lot/Dairy	1 mile		
Green Waste and Recycling Operations	1 mile		
Coffee Roaster	1 mile		

REFERENCES

ARB. See California Air Resources Board.

Asante-Duah K. 2002. Public Health Risk Assessment for Human Exposure to Chemicals. Springer. 56-57.

BAAQMD. See Bay Area Air Quality Management District.

Bay Area Air Quality Management District. 1999 (December). BAAQMD CEQA Guidelines. San Francisco, CA.

_____. 2005. Regulation 2, Rule 2. New Source Review. Available: http://www.baaqmd.gov/dst/regulations/rg0202.pdf>. Accessed February 2009.

_____. 2006. CARE Phase 1 Findings and Policy Recommendations. Available: <<u>http://baaqmd.gov/CARE/documents/care_p1_findings_recommendations_v2.pdf</u>>. Accessed March 2009.

_____. 2008. Source Inventory of Bay Area Greenhouse Gas Emissions. San Francisco, CA.

. 2009. Revised Draft Options and Justifications Report – California Environmental Quality Act Thresholds of Signficance (http://www.baaqmd.gov/~/media/Files/Planning%20and%20Research/CEQA/Revised% 20Draft%20CEQA%20Thresholds%20%20Justification%20Report%20Oct%202009.ash <u>x</u>)

- California Air Pollution Control Officers Association. 2008 (January). CEQA and Climate Change. Sacramento, CA. Available: http://www.capcoa.org/CEQA/CAPCOA%20White%20Paper.pdf>. Accessed April 10, 2009.
- California Air Resources Board. 2000. Risk Reduction Plan to Reduce Particulate Matter Emissions from Diesel-Fueled Engines and Vehicles. Stationary Source Division. Mobile Source Control Division. October.

. 2002. Staff Report: Public Hearing to Consider Amendments to the Ambient Air Quality Standards for Particulate Matter and Sulfates. Available: http://www.arb.ca.gov/research/aaqs/std-rs/pm-final/pm-final.htm.

_____. 2005. Land Use Compatibility Handbook. A Community Health Perspective. Sacramento, CA.

_____. 2008. Climate Change Proposed Scoping Plan. Sacramento, CA. Adopted in December 2008Available: <<u>http://www.arb.ca.gov/cc/scopingplan/document/scopingplandocument.htm</u>>. Accessed March 2009.

_____. 2009a. Greenhouse Gas Inventory and Forecast. Available: <<u>http://www.arb.ca.gov/cc/inventory/data/tables/arb_ghg_inventory_forecast_2008_06_2</u> <u>6.xls</u>>. Accessed March 2009.

______. 2009b. Preliminary Draft Staff Proposal: Recommended Approaches for Setting Interim Significance Thresholds for Greenhouse Gases under the California Environmental Quality Act. Available: <<u>http://www.arb.ca.gov/cc/localgov/ceqa/meetings/10270prelimdraftproposal102408.pdf</u> >. Accessed March 2009.

. 2009c. Area Designations and Maps. Available: http://www.arb.ca.gov/desig/desig.htm, Accessed April 10.

. 2009d. Proposed Regulation to Implement the Low Carbon Fuel Standard, Staff Report Initial Statement Reasons. March 5. Available: <u>http://www.arb.ca.gov/fuels/lcfs/lcfs.htm</u>. Accessed, August 20, 2009.

- CEC. See California Energy Commission.
- CEC. 2007. Impact Analysis 2008 Update to the California Energy Efficiency Standards for Residential and Nonresidential Buildings. Available: <<u>http://www.energy.ca.gov/title22008standards/rulemaking/documents/2007-11-</u> 07_IMPACT_ANALYSIS.PDF>. Accessed March 2009.
- California Department of Finance. 2009. Residential Development Data: E5 City and County Population Estimates. 2000-2050 - Race and Ethnic Populations Totals. Available: <<u>http://www.labormarketinfo.edd.ca.gov/?pageid=145</u> >. Accessed February 2009.
- California Economic Development Department. 2009. Commercial/Industrial Employment Data: Projections of Employment by Industry and Occupation. Available: <<u>http://www.labormarketinfo.edd.ca.gov/?pageid=145</u>>. Accessed February 2009.
- City and County of San Francisco Department of Public Health. 2009. Assessment and Mitigation of Air Pollutant Health Effects from Intra-urban Roadways: Guidance for Land Use Planning and Environmental Review. Program on Health, Equity, & Sustainability. Occupational & Environmental Health Section. Prepared by Rajiv Bhatia and Thomas Rivard. May 6.
- EPA. See U.S. Environmental Protection Agency.
- Governor's Office of Planning and Research. 2008 (June 19). *Technical Advisory: CEQA and Climate Change: Addressing Climate Change Through California Environmental Quality Act (CEQA) Review.* Sacramento, CA. Available: <<u>http://opr.ca.gov/ceqa/pdfs/june08-ceqa.pdf</u>>. Accessed February 2009.
- Intergovernmental Panel on Climate Change. 2007a (February). *Climate Change* 2007: *The Physical Science Basis. Contribution of Working Group I to the Fourth Assessment Report of the IPCC.* Geneva, Switzerland.

2007a (February). Climate Change 2007: Climate Change 2007:Synthesis

Report

Summary for Policymakers. Geneva, Switzerland.

IPCC. See Intergovernmental Panel on Climate Change.

- Jerrett M et al. 2005. Spatial Analysis of Air Pollution and Mortality in Los Angeles. Epidemiology. 16: 727-736
- Kleinman, M.T., Sioutas, C., Froines, J.R., Fanning, E., Hamade, A., Mendez, L., Meacher, D., Oldham, M. Inhalation of Concentrated Ambient Particulate Matter Near a Heavily Trafficked Road Simulates Antigen-Induced Airway Responses in Mice; Inhal. Toxicol. 2007, 19 (Supp. 1), 117-126.

OPR. See Governor's Office of Planning and Research.

Rimpo and Associates. 2009. BAAQMD CEQA Projects Database. Orangevale, CA.

SFDPH. See City and County of San Francisco Department of Public Health.

UNFCCC. See United Nations Framework Convention on Climate Change.

- United Nations Framework Convention on Climate Change. 2009. Article 1 of the UNFCCC. Available: http://unfccc.int/essential_background/convention/background/items/2536.php. Accessed April 8, 2009.
- U.S. Environmental Protection Agency. 2008. Federal Register: Implementation of the New Source Review (NSR) Program for Particulate Matter (PM_{2.5}) less than 2.5 Micrometers. Available: http://www.epa.gov/fedrgstr/EPA-AIR/200May/Day-1a10768.pdf>. Accessed February 2009.

_____. 2009. Monitor Values Report Data. Available: <http://www.epa.gov/air/data/index.html>. Accessed April 8, 2009.

_____. 1988. C. Cowherd, et al., *Control of Open Fugitive Dust Sources*, EPA-450/3-88-008, U. S. Environmental Protection Agency, Research Triangle Park, NC, September 1988.

- Van Hee, V.C., Adar, S.D., Szpiro, A.A., Barr, R.G., Bluemke, D.A., Diez Roux, A.V., Gill, E.A., Sheppard, L., Kaufman, J.D. Exposure to Traffic and Left Ventricular Mass and Function; Am. J. Respir. Crit. Care Med. 2009, 179 (9), 827-834.
- Western Regional Air Partnership. 2006. WRAP Fugitive Dust Handbook. September 7, 2006. Available: <u>http://www.wrapair.org/forums/dejf/fdh/content/FDHandbook_Rev_06.pdf</u>. Accessed September 2009.
- Zhu, Y. Hinds, W.C., Kim S, and Sioutas, C. 2002. Concentration and size distribution of ultrafine particles near a major highway. Journal of Air and Waste Management Association. 2002 Sep; 52 (9): 1032-42.