



**BAY AREA
AIR QUALITY
MANAGEMENT
DISTRICT**

ALAMEDA COUNTY

John J. Bauters
(Secretary)
Pauline Russo Cutter
David Haubert
Nate Miley

CONTRA COSTA COUNTY

John Gioia
David Hudson
Karen Mitchoff
(Vice Chair)
Mark Ross

MARIN COUNTY

Katie Rice

NAPA COUNTY

Brad Wagenknecht

SAN FRANCISCO COUNTY

Myrna Melgar
Shamann Walton
Tyrone Jue
(SF Mayor's Appointee)

SAN MATEO COUNTY

David J. Canepa
Carole Groom
Davina Hurt

SANTA CLARA COUNTY

Margaret Abe-Koga
Cindy Chavez
(Chair)
Rich Constantine
Rob Rennie

SOLANO COUNTY

Erin Hannigan
Lori Wilson

SONOMA COUNTY

Teresa Barrett
Lynda Hopkins

Jack P. Broadbent
EXECUTIVE OFFICER/APCO

Connect with the
Bay Area Air District:



October 6, 2021

Gordon Johnson
Manager, Environmental Affairs Department
Martinez Refining Company – Martinez Refinery
P.O. Box 711
Martinez, CA 94553-0071

**RE: Air Monitoring Plan – Notification of Extension for H₂S Monitoring
Selection Submittal**

Dear Mr. Johnson:

On December 6, 2018 the Bay Area Air Quality Management District (Air District) sent an Air Monitoring Plan (AMP) – Notification of Extension for H₂S Monitoring Selection Submittal. The letter extended the deadline and revised the timeline to allow an additional 3 months for the selection of an H₂S monitoring method. Subsequent extension letters were sent on March 6, 2019, September 17, 2019, December 19, 2019, March 20, 2020, June 19, 2020, September 21, 2020, December 17, 2020, March 18, 2021, and June 22, 2021.

This letter serves to notify Martinez Refining that the Air District will not be issuing any further extensions to the deadline to select an approach to monitor H₂S. The Air District has identified an open path tuneable diode laser (TDL) monitoring system for H₂S that has successfully completed a 6-month proof of performance field study at a California refinery. The system evaluated met Air District minimum expectations and indicates this open path technology has advanced to the point that open path monitoring can be successfully implemented. To encourage the use of open path H₂S monitoring, the Air District will allow up to 15 months from the date of this letter to begin operation of such monitoring. Martinez Refining may request a deadline beyond 15 months after the date of this letter if it can show that additional time is needed due to factors beyond its control.

The H₂S TDL field study confirmed that the following instrument checks can be achieved in practice:

- Continuous data validation and quality checks using ambient methane measurement to confirm reliable system operation and response
- Routine system calibration and audits using sealed H₂S calibration gas cells which allow quality checks for precision, accuracy, and linearity

- Routine detection limit verification checks and confirmed detection limits which ranged from 3 to 25 ppb H₂S, depending on environmental and operational conditions, with an average integrated path detection limit of 15 ppb H₂S over the study period. A repeatable detection limit of 25 ppb was achieved at a light transmission less than 1%. The study presenters indicated that these detection limits could be further reduced by installing a larger retroreflector and the study detection limits should be considered worst-case
- Path integrated measurement range of 3 to 5000 ppb H₂S with an accuracy of 2% of reading and repeatability of 1% of reading
- The system remained in optical alignment throughout the study period with no major adjustments

The Air District is expecting the selection, installation, and startup of an open path H₂S monitoring system to meet the following implementation schedule beginning as of the date of this letter:

February 1, 2022	Select open path monitoring system and provide specifications to Air District for approval
May 1, 2022	Following Air District approval, purchase instrumentation and provide installation schedule/timelines to Air District
June 1, 2022	Submit draft AMP revisions, incorporating H ₂ S monitoring, to Air District for review and approval, including Quality Assurance Project Plan (QAPP) revisions incorporating key parameters bulletized above
October 1, 2022	Complete installation and begin field validation of equipment, including quality and operational metrics identified in AMP and QAPP
January 1, 2023	Commence operation and data reporting/posting to refinery fence line monitoring website

H₂S monitoring data shall be included in the quarterly fence line reports upon commencement of operation, regardless of final AMP/QAPP approval status. Any open path H₂S monitoring system that can be shown to meet the specifications detailed above can be submitted to the Air District for a determination of equivalency. If existing monitoring systems can be optimized to meet the specifications detailed in this letter, Martinez Refining should submit the details of the modifications and optimizations that will be

implemented to the Air District for determination of equivalency. Following review, any existing system deemed by the Air District to not be capable of meeting equivalency will need to be replaced with a monitoring system that does meet equivalency standards.

The specifications above represent the minimum acceptable standards for any open path H₂S monitoring system. Open path H₂S monitoring systems should include the following:

- Sealed gas cell, or equivalent, 3-point calibration checks should be performed quarterly at a minimum
- Audit bump checks should be performed at least monthly at a unique concentration that differs from the calibration checks
- Real time validation of TDL data should include measurement of another common ambient air component, such as methane, water, or carbon monoxide if present in the spectra
- Detection limit quantification and verification should be performed continuously in real time, reported in near real time on the refinery fence line monitoring website, and included in the quarterly reports along with the measurement data
- Signal intensity should be measured in real time and provided in the quarterly reports
- Raw spectral data files should be saved as single files and made available to the Air District upon request
- All quality assurance and quality control metrics and procedures should be fully documented in the AMP and integrated QAPP
- The Air District recommends that system operation and performance is based on a standardized method, such as EPA Method TO-16, or a method developed by a credible standardization body, such as ASTM International or the International Organization for Standardization (ISO)

If Martinez Refining instead chooses to use fixed measurements for H₂S monitoring using the EPA MACT siting procedures for benzene sampling at refineries, then such monitoring must be operational within 6 months of the date of this letter. Martinez Refining may request a deadline beyond 6 months if it can show that additional time is needed due to factors beyond its control. Martinez Refining's selection and implementation of H₂S monitoring will be reviewed as an element of the AMP implementation. Failure to implement H₂S

monitoring in a timely and adequate manner would be basis for withdrawal of approval.

If you have any questions regarding this notification, please contact Chris Crowley at 415-749-5118 for compliance issues or me at 415-749-4601 for technical issues.

Sincerely,

Jerry Bovee, P.E., QSTI
Air Quality Engineering Manager
Meteorology and Measurement Division
Bay Area Air Quality Management District
375 Beale Street, Suite 600
San Francisco, CA 94105
Office: 415.749.4601
Fax: 415.749.4922
jbovee@baaqmd.gov / www.baaqmd.gov