

**BAY AREA AIR QUALITY MANAGEMENT DISTRICT
Best Available Control Technology (BACT) Guideline**

Source Category

Source: <i>Concrete Batch Plants</i>	Revision: <i>1</i>
	Document #: <i>49.1</i>
Class: <i>< 5 cubic yards per batch</i>	Date: <i>09/04/91</i>

Determination

POLLUTANT	BACT 1. Technologically Feasible/ Cost Effective 2. Achieved in Practice	TYPICAL TECHNOLOGY
POC	1. <i>n/a</i> 2. <i>n/a</i>	1. <i>n/a</i> 2. <i>n/a</i>
NO_x	1. <i>n/a</i> 2. <i>n/a</i>	1. <i>n/a</i> 2. <i>n/a</i>
SO₂	1. <i>n/a</i> 2. <i>n/a</i>	1. <i>n/a</i> 2. <i>n/a</i>
CO	1. <i>n/a</i> 2. <i>n/a</i>	1. <i>n/a</i> 2. <i>n/a</i>
PM₁₀	1. <i>n/d</i> 2. <i>Water spray for aggregate handling, aggregate storage piles, and site road surfaces; and Enclosure and venting of cement handling and storage to baghouse w/ ≤0.01 gr/dscf^a</i>	1. <i>n/d</i> 2. <i>BAAQMD Approved Design and Operation^a</i>
NPOC	1. <i>n/a</i> 2. <i>n/a</i>	1. <i>n/a</i> 2. <i>n/a</i>

References

a. BAAQMD