

**ENGINEERING EVALUATION REPORT
VALERO REFINING COMPANY – CALIFORNIA
PLANT NO. – 12626
APPLICATION NO. 19792**

INTRODUCTION

This application is to bank Interchangeable Emission Reduction Credits (IERCs), in accordance with District Regulation 2, Rule 9, from the carbon monoxide furnaces listed below at the Valero Refining Company in Benicia, CA.

- S-3 Crude Preheat Furnace, F-101
- S-4 Reduced Crude Preheat Furnace, F-102

The emission reductions are the result of the Thermal De-NOx system (A-25). Sources S-3 and S-4 share a common stack with source S-7 (Jet Fuel Hydrofining Furnace). The Thermal De-NOx system is located downstream from S-3 and S-4, and upstream of S-7. Emissions from S-3 and S-4 are the difference between total emissions from the common stack and emissions from S-7.

Since December 1994, Valero has measured the NOx concentration from the common stack using a continuous emission monitor (CEM). Prior to that time, source tests were performed to determine the NOx concentration. In October 1999, Valero installed a flue gas flow meter to measure exhaust flow from the stack.

Under application numbers 19971, 4398, 11890, 15662 and 18880, the District has already approved IERCs from S-3 & S-4 for 11 credit generation periods (CGPs). This application is to bank IERCs from an additional credit generation period that has elapsed since the prior banking applications. The credit generation period for this application is calendar year 2008 (CGP₁₂).

IERC CALCULATIONS

The procedure for calculating IERCs is described in Regulation 2, Rule 9, Sections 602 and 603. This application relies on baseline data that was established in AN 19971. The IERC calculations to follow are based on daily NOx CEM concentrations, production rates and other data provided by Valero. District staff audited this data by comparing it with data previously submitted as part of the annual permit renewal process, and by auditing raw data from Valero's recording keeping system for select days during the credit generation period. The evaluation procedure that follows is the same procedure that was used in AN 19971, and subsequent applications.

Baseline Data:

The baseline data from AN 19971 is summarized below:

Baseline Period	January 1, 1992 through December 31, 1996
Baseline Throughput	127,300 barrels/day
Baseline Emissions	12,622 lb NOx/day (2303.5 tons of NOx)
Baseline Emission Rate	0.09915 lb NOx / bbl of crude

Determine the Baseline Adjusted Emission Rate:

S-3 and S-4 have been subject to the 300 ppm NO_x limit (at 3% oxygen) in Regulation 9, Rule 10, Section 303.1 since May 31, 1995. On July 1, 2002, the 150 ppm limit in Reg. 9-10-304 became effective. Therefore, it is necessary to adjust the baseline emission rate to account for the 150 ppm limit.

From AN 11971, the baseline emission rate was 0.09915 lb/barrel. The average NO_x concentration during the baseline period was 264 ppm @ 3% O₂. Therefore, the adjusted baseline emission rate that is equivalent to 150 ppm is:

$$(150 \text{ ppm} / 264 \text{ ppm}) (0.09915 \text{ lb/bbl}) = 0.0563 \text{ lb NO}_x/\text{bbl}$$

Determine the Baseline Adjusted Emissions (A):

Baseline adjusted emissions are calculated by multiplying the baseline throughput by the baseline adjusted emission rate for that particular CGP. The baseline adjusted emissions (A_x where x is the CGP number) are:

$$A_{12} = (127,300 \text{ bbl/day}) (366 \text{ days}) (0.0563 \text{ lb NO}_x/\text{bbl}) (\text{ton}/2000 \text{ lb}) = \mathbf{1311.6 \text{ tons NO}_x}$$

Determine the Actual Emissions (B) During the Credit Generation Period:

The credit generation period (CGP) covered by this banking application is:

CGP₁₂ – Jan. 1 through Dec. 31, 2008 (366 days, due to leap year)

Emissions are calculated from data provided by Valero in this banking application. The NO_x concentrations were measured by a continuous emission monitor (CEM). The exhaust flow rates were measured by a pitot tube flow meter.

As discussed above, sources S-3 and S-4 share a common stack (Main Stack) with source S-7. Valero measures NO_x concentration and exhaust flow rate for the Main Stack. To calculate emissions from S-3 and S-4, first calculate emissions from the Main Stack, and then subtract emissions from S-7.

Main Stack Emissions:

Actual emissions are determined by multiplying the annual average NO_x concentration (Attachment B-7, in application file) and exhaust flow rate (Attachment B-2). The actual exhaust flow rate is first adjusted to dry standard cubic feet per minute (dscfm) using the annual average temperature (Attachment B-3), and the exhaust water content of 13.3%.

There was a Field Accuracy Test conducted by the District on 10/30/08. Valero's measured NO_x concentrations were lower than the District's measurements by 5.7%. To be most conservative, the NO_x concentrations for the CGP will be adjusted (increased) by 5.7%, yielding fewer IERCs.

CGP₁₂

$$\text{Standard flow} = (884,600 \text{ acfm}) \left[\frac{(460+70)}{(460+633)} \right] (1.0 - 0.133) \\ = 371,896 \text{ dscfm}$$

Emissions =

$$(54 \times 10^{-6}) (1.057) (371,896 \text{ cfm}) (1440 \text{ m/d}) (366 \text{ d/yr}) (\text{lb-mol}/387 \text{ cf}) (46 \text{ lb/lb-mol}) \\ = 1,329,782 \text{ lbs NO}_x (664.9 \text{ tons of NO}_x)$$

S-7 Emissions:

Emissions from S-7 are calculated from fuel usage (Attachment B-5), fuel heat content (Attachment B-6), and a NOx emission factor of 0.14 lb/MM BTU, which is based on the average of two source tests conducted on S-7 during 2008 (6/4/08: 0.16 lb/MM BTU; 11/8/08: 0.12 lb/MM BTU).

$$\begin{aligned} & \text{CGP}_{12} \\ & (323,000 \text{ cf/d}) (1042 \text{ BTU/cf}) (0.14 \text{ lb NOx/MM BTU}) (\text{MM}/10^6) (366 \text{ d}) (\text{ton}/2000 \text{ lb}) \\ & = 8.6 \text{ tons NOx} \end{aligned}$$

Actual emissions from S-3 and S-4 (B_x where x represents the CGP number) are:

$$B_{12} = 664.9 - 8.6 = \mathbf{656.3 \text{ tons NOx}}$$

Determine Credit Generation Period Non-Curtailment Emissions (C):

The non-curtailment emission rate (C) for a given credit generation period (CGP) is calculated by multiplying the baseline throughput (127,300 bbl/day) by the emission rate for that CGP. The emission rate for the CGP_{12} is calculated by dividing annual emissions by annual crude throughput.

Emission rate:

$$\text{CGP}_{12} \text{ Em. Rate} = [(656.3 \text{ ton}) (2000 \text{ lb/ton})] / [(120400 \text{ bbl/day}) (366 \text{ days})] = 0.0298 \text{ lb / bbl}$$

$$C_{12} = (127,300 \text{ bbl/day}) (0.0298 \text{ lb/bbl}) (366 \text{ days}) (\text{ton}/2000 \text{ lb}) = \mathbf{694.2 \text{ tons}}$$

Calculate IERCs for each Credit Generation Period:

IERCs are calculated by subtracting the greater of either the actual emissions (B) or the non-curtailment emissions (C) from the baseline emissions (A).

As indicated above, $A_{12} = \mathbf{1311.6 \text{ tons}}$

For CGP_{12} , C_{12} is greater than B_{12} . Therefore, the amount of IERCs is:

$$A_{12} - C_{12} = 1311.6 - 694.2 = \mathbf{617.4 \text{ tons}}$$

STATEMENT OF COMPLIANCE

For an emission reduction to be banked as an IERC, the reduction must be real, permanent, quantifiable, enforceable and surplus (Section 2-1-301.2).

Real: As defined in Section 2-9-214, real means that the emission reduction constitutes an actual decrease in air emissions. There was an actual decrease in emissions to the atmosphere, as is evident from source testing and continuous emission monitoring (CEM) data. The emission reductions evaluated in this application are real.

Permanent: As defined in Section 2-9-213, permanent means that the emission reduction exists for the duration of the credit generation period (CGP). Since the CGP has already ended, the emission reductions are permanent.

Quantifiable: Quantifiable means that the emission reductions are based on data from emissions measurements. The emission calculations were performed using crude throughput records, source test data and continuous emission monitoring data. These emission reductions evaluated in this application are quantifiable.

Enforceable: As defined in Section 2-9-209, enforceable means that there is credible evidence during the credit generation period to verify compliance with Regulation 2, Rule 9. The evaluation of this banking application is based on actual crude throughput records, source test data and CEM data. The emission reductions evaluated in this application are enforceable.

Surplus: As defined in Section 2-9-218, surplus means that the emission reductions are not required by Reasonably Available Control Technology (RACT), Best Available Retrofit Control Technology (BARCT), or any other rule in effect during the credit generation period. In addition, emissions reductions must exceed any reduction required by the most recent Clean Air Plan or Air Quality Management Plan.

Regulation 9, Rule 10, Section 304.1 contains a limit of 150 ppm, which became effective on July 1, 2002. The District considers this limit to constitute BARCT. The baseline emissions have been adjusted to reflect this BARCT limit.

The amount of IERCs generated in 2008 exceeds the amount of IERCs used in 2008. Therefore, the IERCs requested in this application are surplus. The District's most recent plan is the 2005 Ozone Strategy, which was adopted January 4, 2006. This plan contains a base-year emission inventory for 2002, and projected emission inventories for subsequent years broken out by source category. The emission inventory includes a category for IERCs. The 2008 IERC inventory exceeds the sum of IERCs that were actually used and banked in 2008.

PUBLIC COMMENT

IERCs for CGP₁₂ exceed 40 tons. Therefore, this application is subject to the public comment provisions of Section 2-9-405.

RECOMENDATION

Staff recommends the District issue a 30-day public notice regarding the preliminary decision to approve the following IERCs for Credit Generation Period 12 for emission reductions that occurred at the Valero refinery.

Credit Generation Period #12: January 1 through December 31, 2008

IERCs = 617.4 Tons of Nitrogen Oxides

Effective Date: January 1, 2009

Expiration Date: December 31, 2013

By: _____
Supervising Air Quality Engineer

Date: June 30, 2009