

**Engineering Evaluation
McCarthy Santa Cruz Avenue
216 North Santa Cruz Avenue
Las Gatos, CA 95030
Plant # 23435; Application Number 27760**

1. Background:

McCarthy Santa Cruz Avenue has applied for an Authority to Construct/Permit to Operate the following Soil Vapor Extraction System (SVE) system located at 216 North Sana Cruz avenue, Las Gatos, CA 95030. The site was a former dry cleaning facility.

S-1: Soil Vapor Extraction System Consisting of a 250 SCFM Dresser Industries Frame 56 RAI Blower, abated by A-1

A-1: 2-1000 Pound Activated Carbon Vessels in Series, Model VF-1000 Lb

The SVE system will be operated within 1000 feet of the following School and thus a Public Notice is required.

Fusion Academy
50 University Avenue
Los Gatos, CA 95030

2. Emission Calculations

Table 1, shows calculated Toxic Air Contaminant (TAC) emissions. The TAC emissions are based on the highest pilot test results submitted by the applicant. Thus the maximum amount that can potentially be emitted is calculated below. With the two 1000 pound activated carbon abatement system in series a 98.5% abatement efficiency is expected. The calculations demonstrate that the TACs do not trigger a risk screen.

For a conservative estimate of yearly emissions, we shall assume that the system is operated for an entire year with an inlet concentration corresponding to the initial soil concentration level:

TAC emission, lb/y = ($\mu\text{g}/\text{m}^3$ of the TAC) X (6.243 E-11 lb/ft³/ $\mu\text{g}/\text{m}^3$) (250 ft³/m) (60 m/h)(24h/d)(365 d/y)

Thus, TAC Emission before abatement, lb/y = (0.0082) X ($\mu\text{g}/\text{m}^3$ of the TAC)

With 98.5% abatement, abated TAC emission to the atmosphere, lb/y = (0.015) X (0.0082) X ($\mu\text{g}/\text{m}^3$ of the TAC)
= (1.23 E-4) X ($\mu\text{g}/\text{m}^3$ of the TAC)

4. Compliance Statements:

Toxics

Perchloroethylene is emitted at the source. Trace amounts of other TACs are also emitted and are insignificant. Perchloroethylene emission after abatement is below the toxic trigger level at 98.5% abatement efficiency. This facility would have perchloroethylene emission below the trigger level listed in Regulation 2-5, Table 2-5-1. Therefore, the emissions of toxic substances are not considered significant to warrant a risk screen analysis.

However, the following school is within 1000 feet of the source S-1 and since there are TAC emissions from the source a Public Notification is triggered in accordance with Regulation 2-1-412 irrespective of the amount of TAC emitted.

Fusion Academy
50 University Avenue
Los Gatos, CA 95030

New Source Review

Best Available Control Technology (BACT)

In accordance with Regulation 2, Rule 2, Section 301, BACT is triggered for any new or modified source with the potential to emit 10 pounds or more per day of POC, NPOC, NO_x, CO, SO₂ or PM₁₀.

This proposed project will not emit over 10 pounds per day of POC, NPOC, NO_x, CO, SO₂ or PM₁₀. Thus BACT is not triggered. The source is equipped with a carbon system that will abate the emissions further reducing the TAC emissions to the atmosphere.

Offsets

Offsets must be provided for any new or modified source at a facility that emits more than 10 tons per year of POC or NO_x per Regulation 2-2-302. Table 2 above summarizes increases in criteria pollutant emissions at the plant. Offsets are not applicable to this application, since the emissions do not exceed 10 tons/yr. Thus this facility is not subject to Regulation 2-2-302.

California Environmental Quality Act (CEQA)

The project is considered to be ministerial under the Districts proposed CEQA Regulation 2-1-311 and therefore is not subject to CEQA review. The engineering review for this project requires only the application of standard permit conditions and standard emission factors and therefore is not discretionary as defined by CEQA. This project is in compliance with Chapter 9.2 of the permit handbook.

District Regulations

Based on the information submitted, this operation is expected to be in compliance with Regulation 8-47-301, and 8-47-302 since the POC and NPOC emissions are vented through a carbon adsorption system at all times of operation.

Prevention of Significant Deterioration (PSD), New Source Performance Standards (NSPS), and National Emission Standards for Hazardous Air Pollutants (NESHAPS) are not triggered.

5. Condition

Condition # 26255 applies to the following source:

- S-1: Soil Vapor Extraction System Consisting of a 250 SCFM Dresser Industries Frame 56 RAI Blower, abated by A-1
- A-1: 2-1000 Pound Activated Carbon Vessels in Series, Model VF-1000 Lb

1. The owner/operator shall abate the Precursor Organic Compound (POC) and non-precursor organic compound (NPOC) emissions from Source S-1 by A-1, SVE Abatement System, consisting of two 1000 pound Activated Carbon Vessels in series during all periods of operation. Start-up and subsequent operation of each abatement device shall take place only after written notification of same has been

received by the District's Engineering Division. The owner/operator shall operate the sources such that the soil vapor flow rate from S-1 shall not exceed 250 scfm. [Basis: Cumulative Increase, Regulation 8-47-301 and 302, TBACT]

2. During operation of the Activated Carbon Vessels, the owner/operator of this source shall monitor with a photo-ionization detector (PID), flame-ionization detector (FID), or other method approved in writing by the District's Source Test Manager at the following locations:
 - a. At the inlet to the second to last Carbon vessel in series.
 - b. At the inlet to the last Carbon vessel in series.
 - c. At the outlet of the Carbon vessel that is last in series prior to venting to the atmosphere.

When using an FID to monitor breakthrough, readings may be taken with and without a Carbon filter tip fitted on the FID probe. Concentrations measured with the Carbon filter tip in place shall be considered methane for the purpose of these permit conditions. [Basis: Cumulative Increase, Regulation 2-5, TBACT]

3. The owner/operator shall record these monitor readings in a monitoring log at the time they are taken. The owner/operator shall use the monitoring results to estimate the frequency of Carbon change-out necessary to maintain compliance with parts 2, 4 and 5, and shall be conducted on a daily basis. The owner/operator of this source may propose for District review, based on actual measurements taken at the site during operation of the source, that the monitoring schedule be changed based on the decline in organic emissions and/or the demonstrated breakthrough rates of the carbon vessels. Written approval by the District's Engineering Division must be received by the owner/operator prior to a change to the monitoring schedule. [Basis: Cumulative Increase, Regulation 2-5, TBACT]
4. The owner/operator shall immediately change out the second to last Carbon vessel with unspent carbon upon breakthrough, defined as the detection at its outlet of the higher of the following:
 - a. 10 % of the inlet stream concentration to the carbon bed.
 - b. 10 ppmv (measured as hexane).[Basis: Cumulative Increase, Regulation 2-5, TBACT]
5. The owner/operator shall immediately change out the last Carbon vessel with unspent Carbon upon detection at its outlet of 10 ppmv (measured as hexane). [Basis: Cumulative Increase, Regulation 2-5, TBACT]
6. The owner/operator of this source shall maintain the following information for each month of operation of the Activated Carbon Vessels:
 - a. Hours and time of operation.
 - b. Each emission test, analysis or monitoring results logged in for the day of operation they were taken.
 - c. The number of Carbon vessels removed from service.
 - d. Total throughput of soil vapor from source S-1 in Standard Cubic Feet.

Such records shall be retained and made available for inspection by the District for two years following the date the data is recorded. [Basis: Regulation 1-523]

7. The owner/operator shall report any non-compliance with these conditions to the Compliance and Enforcement Division at the time that it is first discovered. The owner/operator shall detail the corrective action taken and include the data showing the exceedance as well as the time of occurrence in the submittal. [Basis: Cumulative Increase, Regulation 2-5, TBACT]
8. The owner/operator shall maintain a file containing all measurements, records and other data that are required to be collected pursuant to the various provisions of this conditional Authority to Construct/Permit

to Operate. All measurements, records and data required to be maintained by the owner/operator shall be retained for at least two years following the date the data is recorded. [Basis: Regulation 1-523]

9. Upon final completion of the remediation project, the operator of Sources S-1 shall notify the Engineering Division within two weeks of decommissioning the operation. [Basis: Cumulative Increase, Regulation 2-5, TBACT]

6. Recommendation

The District has reviewed the material contained in the permit application for the proposed project and has made a preliminary determination that the project is expected to comply with all applicable requirements of District, state, and federal air quality-related regulations. The preliminary recommendation is to issue an Authority to Construct for the equipment listed below. However, the proposed source will be located within 1000 feet of a school, which triggers the public notification requirements of District Regulation 2-1-412. After the comments are received from the public and reviewed, the District will make a final determination on the permit. I recommend that the District initiate a public notice and consider any comments received prior to taking any final action on issuance of a Permit to Operate for the following source:

S-1: Soil Vapor Extraction System Consisting of a 250 SCFM Dresser Industries Frame 56 RAI Blower,
abated by A-1

A-1: 2-1000 Pound Activated Carbon Vessels in Series, Model VF-1000 Lb

by _____
By: Hari Doss

June 27, 2016