

Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-4 Decoration Oven, Line 1

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501.2	P/D	Coating Records ¹	Y
	BAAQMD 8-11-301.10	N	2.5 lbs/gal	BAAQMD 8-11-501.4	P/M	Coating Records ¹	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	SIP 8-11-301.9	Y	2.5 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 1		1400° F and inlet manifold pressure of -1.5 in of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	Y	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	P/M	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 13	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test	Y
	BAAQMD Condition #9904 Part 17	Y	47.37 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-4, S-12, & S-62)	BAAQMD Condition #9904, Part 17	P/M	Emission Records	Y
	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – B
Applicable Limits and Compliance Monitoring Requirements
S-5 Basecoat Oven, Line 2

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
POC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
POC	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition	N	1400°F and inlet manifold pressure of -	BAAQMD Condition	C	Temperature Chart Recorder	Y

¹ All coatings received are formulated to be less than the limits set forth in BAAQMD 8-11-301.

	#9904 Part I		1.5 in of water except during bypass as allowed in Condition #9904, Part 7	#9904, Part 2		and pressure monitor	
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	P/D	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test	Y
	BAAQMD Condition #9904 Part 22	Y	64.7 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-5, S-51,,)	BAAQMD Condition #9904, Part 25	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII - C
Applicable Limits and Compliance Monitoring Requirements
S-6 Interior Coating Oven, Line 1

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
POC	BAAQMD 8-11-301.4.1	N	3.5 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part I	N	1400°F and inlet manifold pressure of - 1.5 in of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	C	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test Report	Y
	BAAQMD Condition #9904 Part 10	Y	119 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-6 & S-16)	BAAQMD Condition #9904, Part 17	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII – D
Applicable Limits and Compliance Monitoring Requirements
S-7 Interior Coating Oven, Line 2**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.4.1	N	3.5 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	40 CFR 60, Subpart WW, Section 60.492(a)	Y	0.29 kg VOC/l	40 CFR 60 Subpart WW, Section 60.495	P/Q	Coating Records ¹	Y
	BAAQMD Condition #9904 Part I	N	1400°F and inlet manifold pressure of - 1.5 in of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	P/W	Monitor damper position	Y
POC	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test	Y
	BAAQMD Condition #9904 Part 18	Y	288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-61)	BAAQMD Condition #9904, Part 21	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – E
Applicable Limits and Compliance Monitoring Requirements
S-12 Printer with Overvarnisher, Line 1

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD 8-11-301.10	N	2.5 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 14	Y	47.37 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-4, S-12, & S-62)	BAAQMD Condition #9904, Part 17	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – F
Applicable Limits and Compliance Monitoring Requirements
S-13 Printer with Overvarnisher, Line 2
S-27 Printer #32 with Overvarnisher, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
VOC	BAAQMD Condition #9904 Part 26	Y	83.31 tons/12 consecutive month period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, & S-55-60 except S-59)	BAAQMD Condition #9904 Part 31	P/M	Emission Records	Y
	BAAQMD Condition #9904 Part 27	Y	31.35 tons/12 consecutive month period prior to control due to ink usage, excluding clean-up solvent (combined limit for S-13, S-25, S-27, S-53, & S-60)	BAAQMD Condition #9904 Part 31	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – G
Applicable Limits and Compliance Monitoring Requirements
S-16 Interior Coating Spray Bank, Line 1

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.4.1	N	3.5 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 13	Y	119 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-6 & S-16)	BAAQMD Condition #9904 Part 17	P/M	Emission Records	Y
TSP	BAAQMD 6-310	Y	0.15 gr/dscf	BAAQMD Condition #16289 Part 3(b)	P	Baghouse Filter Bag Inspection	Y
	BAAQMD Condition #16289 Part 3(a)	Y	≥ 0.2 inches of H ₂ O, and < 5 inches of H ₂ O	BAAQMD Condition #16289 Part 3(b)	P/W	pressure drop inspection	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – H
Applicable Limits and Compliance Monitoring Requirements
S-17 Interior Coating Spray Bank, Line 2

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.4.1	N	3.5 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 18	Y	288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-61)	BAAQMD Condition #9904 Part 21	P/M	Emission Records	Y
TSP	BAAQMD 6-310	Y	0.15 gr/dscf	BAAQMD Condition #16289 Part 3(b)	P	Baghouse Filter Bag Inspection	Y
	BAAQMD Condition #16289 Part 3(a)	Y	≥ 0.2 inches of H ₂ O, and < 5 inches of H ₂ O	BAAQMD Condition #16289 Part 3(b)	P/W	pressure drop inspection	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – I
Applicable Limits and Compliance Monitoring Requirements
S-24 Interior Coating Spray Bank, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.4.1	Y	2.1 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 18	Y	288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-61)	BAAQMD Condition #9904 Part 21	P/M	Emission Records	Y
TSP	BAAQMD 6-310	Y	0.15 gr/dscf	BAAQMD Condition #16291 Part 3(b)	P	Baghouse Filter Bag Inspection	Y
	BAAQMD Condition #16291 Part 3(a)	Y	≥ 0.2 inches of H ₂ O, and < 5 inches of H ₂ O	BAAQMD Condition #16291 Part 3(b)	P/W	pressure drop inspection	Y
HAP	BAAQMD Condition #21993 Part 1	Y	<u>9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs</u>	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – J
Applicable Limits and Compliance Monitoring Requirements
S-56 Decorator Oven #31, Line 3
S-58 Decorator Oven #32, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part I	N	1400°F and inlet manifold pressure of - 1.5 in of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	C	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test Report	Y

	BAAQMD Condition #9904 Part 26	Y	83.31 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, S-55-56 except S-60)	BAAQMD Condition #9904, Part 31	P/M	Emission Records	Y
POC	BAAQMD Condition #9904 Part 27	Y	31.35 tons/12 consecutive month period prior to control due ink usage, excluding clean-up solvent (combined limit for S-13, S-56, S-58, S-27, S-53 & S-60)	BAAQMD Condition #9904, Part 31	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII – K
Applicable Limits and Compliance Monitoring Requirements
S-35 Wipe Cleaning Operation**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD Condition #1701 Part 1	Y	16.830 tons clean-up solvent/12 consecutive month period for operations associated with S-12-17, S-24, S-28, S-35, S-41-46, S-51, S-52, S-54, S-55, S-57, S-59, & S-60.	BAAQMD Condition 1701 Part 2	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII – L
Applicable Limits and Compliance Monitoring Requirements
S-51 Basecoater, Line 2**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	40 CFR 60, Subpart WWW, Section 60.492(a)	Y	0.29 kg VOC/l	40 CFR 60, Subpart WWW, Section 60.495	P/Q	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y

	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test Report	Y
	BAAQMD Condition #9904 Part 22	Y	64.7 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-5 and S-51)	BAAQMD Condition #9904 Part 25	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII – M
Applicable Limits and Compliance Monitoring Requirements
S-53 Decoration Oven, Line 2**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 1	N	1400°F and inlet manifold pressure of -1.5 in of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	C	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test Report	Y
	BAAQMD Condition #9904 Part 26	Y	83.31 tons/12 consecutive month period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, S-55-58 and S-60)	BAAQMD Condition #9904, Part 31	P/M	Emission Records	Y
	BAAQMD Condition #9904 Part 24		31.35 tons/12 consecutive month period prior to control due to ink usage,	BAAQMD Condition #9904, Part 28	P/M	Emission Records	Y

			excluding clean-up solvent (combined limit for S-13, S-27, S-53, S-56, S-58 and S-60)				
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – N
Applicable Limits and Compliance Monitoring Requirements
S-52 Bottom Coater, Line 2
S-55 Bottom Coater at Basecoater #31, Line 3
S-57 Bottom Coater at Basecoater #32, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	40 CFR 60, Subpart WW, Section 60.492(b)	Y	0.46 kg VOC/l	40 CFR 60, Subpart WW, Section 60.495	P/Q	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 26	Y	83.31 tons/12 consecutive month period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, and S-55-60 except 59)	BAAQMD Condition #9904, Part 31	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – O
Applicable Limits and Compliance Monitoring Requirements
S-60 Printer #32 with Overvarnisher, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	40 CFR 60, Subpart WW, Section 60.492(b)	Y	0.46 kg VOC/l	40 CFR 60, Subpart WW, Section 60.495	P/Q	Coating Records ¹	Y
	BAAQMD Condition	Y	83.31 tons/12 consecutive month	BAAQMD Condition	P/M	Emission Records	Y

	#9904 Part 26		period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, S-55-60 except S-59)	#9904, Part 31			
	BAAQMD Condition #9904 Part 27	Y	31.35 tons/12 consecutive month period prior to control due to ink usage, excluding clean-up solvent (combined limit for S-13, S-27, S-53, S-56, S-58 & S-60)	BAAQMD Condition #9904, Part 31	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII – P
Applicable Limits and Compliance Monitoring Requirements
S-61 Interior Coating Oven, Line 3**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.4	Y	3.5 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	40 CFR 60, Subpart WW, Section 60.492(b)	Y	0.89 kg VOC/l	40 CFR 60, Subpart WW, Section 60.495	P/Q	Coating Records ¹	Y
	BAAQMD Condition #9904 Part I	N	1400°F and inlet manifold pressure of - 1.5 in of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	C	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test Report	Y
	BAAQMD Condition #9904 Part 18	Y	288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-61)	BAAQMD Condition #9904, Part 21	P/M	Emission Records	Y

HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y
-----	--------------------------------	---	---	---------------------------------	-----	------------------	---

**Table VII – Q
Applicable Limits and Compliance Monitoring Requirements
S-62 Bottom Coater, Line 1**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	40 CFR 60, Subpart WWW, Section 60.492(a)	Y	0.41 kg VOC/l	40 CFR 60, Subpart WWW, Section 60.495	P/Q	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 14	Y	47.37 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-4, S-12, & S-62)	BAAQMD Condition #9904 Part 17	P/M	Emission Records	Y
	BAAQMD Condition #14836 Part 1	Y	4.45 tons/12 consecutive month period prior to control, excluding clean-up solvent for bottomcoating	BAAQMD Condition #14836 Part 4	P/M	Coating Records ¹	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII-R
Applicable Limits and Compliance Monitoring Requirements
S-63 Interior Coating Storage Tank
S-64 Interior Coating Storage Tank**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD Condition #18728 Part 1		275,000 gallons/12 consecutive month period	BAAQMD Condition #18728, Part 3	P/M	Usage Records	Y
	BAAQMD Condition #18728 Part 2		Use only water reducible liner coating	BAAQMD Condition #18728, Part 3	C	VOC records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII-S
Applicable Limits and Compliance Monitoring Requirements
S-65 Emergency Standby Generator
S-66 Emergency Standby Generator**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
FP	BAAQMD 6-310	Y	0.15 gr/dscf	N	N	N	Y
FP	BAAQMD 6-310	Y	No. 2 on Ringelmann Chart for 3 minutes in any hour	N	N	N	Y
FP	BAAQMD 6-310	Y	0.15 gr/dscf	N	N	N	Y
SO ₂	BAAQMD 9-1-301	Y	Ground level concentration of 0.5 ppm continuously for 3 consecutive minutes, or 0.25 ppm averaged over 60 consecutive minutes, or 0.05ppm averaged over 24 hours				Y
SO ₂	BAAQMD 9-1-302	Y	30 ppm in the gas stream	N	N	N	Y
NO _x	BAAQMD 9-8-301.2	Y	140 ppmv @ 15% O ₂ , dry		P/A		Y
	BAAQMD 9-8-302.1	Y	140 ppmv @ 15% O ₂ , dry		P/A		Y
CO	BAAQMD 9-8-301.3	Y	2000 ppmv @ 15% O ₂ , dry		P/A		Y
	BAAQMD 9-8-302.3	Y	2000 ppmv @ 15% O ₂ , dry		P/A		Y
PM, NO _x , CO, POC	BAAQMD Condition #18729 Part 2	Y	100 hrs/yr for reliability-related activities	BAAQMD Condition #18729, Part 4 & 5	P/M	Totalizer counter and records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII - T
Applicable Limits and Compliance Monitoring Requirements
S-67 Video Jet Printer**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-305	Y	2.1 lb/gal	BAAQMD 8-11-501	P/M	Coating Records ¹	Y
	40 CFR 60, Subpart WW,	Y	0.46 kg VOC/l	40 CFR 60, Subpart WW,	P/Q	Coating Records ¹	Y

	Section 60.492(a)			Section 60.495			
	BAAQMD Condition #18544 Part 1	Y	5 gallons / 12 consecutive month period	BAAQMD Condition #18544, Part 3	P/M	Records	Y
	BAAQMD Condition #18544 Part 2	Y	1 gallon / 12 consecutive month period	BAAQMD Condition #18544, Part 3	P/M	Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII – U
Applicable Limits and Compliance Monitoring Requirements
S-68 Ink Dot System, Line 3**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-305	Y	2.1 lb/gal	BAAQMD 8-11-501	P/M	Coating Records ¹	Y
	40 CFR 60, Subpart WWW, Section 60.492(b)	Y	0.46 kg VOC/l	40 CFR 60, Subpart WWW, Section 60.495	P/Q	Coating Records ¹	Y
	BAAQMD Condition #18645 Part 1	Y	75 gallons / 12 consecutive month period	BAAQMD Condition #18645, Part 3	P/M	Records	Y
	BAAQMD Condition #18545 Part 2	Y	15 gallon / 12 consecutive month period	BAAQMD Condition #18545, Part 3	P/M	Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII – V
Applicable Limits and Compliance Monitoring Requirements
S-68 Ink Dot System, Line 1 & 2**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-305	Y	2.1 lb/gal	BAAQMD 8-11-501	P/M	Coating Records ¹	Y
	40 CFR 60, Subpart WWW, Section 60.492(b)	Y	0.46 kg VOC/l	40 CFR 60, Subpart WWW, Section 60.495	P/Q	Coating Records ¹	Y
	BAAQMD Condition #20955 Part 1	Y	60 gallons / 12 consecutive month period	BAAQMD Condition #20955, Part 3	P/M	Records	Y

	BAAQMD Condition #20955 Part 2	Y	14 gallon / 12 consecutive month period	BAAQMD Condition #20955, Part 3	P/M	Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Footnote 1: All coatings received are formulated to be less than the limits set forth in BAAQMD 8-11-301.