



**Ball Corporation**  
Metal Beverage Packaging Division, Americas  
2400 Huntington Drive, Fairfield, CA 94533-9734, (707) 437-5411

RECEIVED  
2012 JUL 19 AM 11 05  
BAY AREA AIR QUALITY  
MANAGEMENT DISTRICT

July 17, 2012

5412-L-024  
Certified

Director of Compliance and Enforcement  
Bay Area Air Quality Management District  
939 Ellis Street  
San Francisco, CA 94109

ATTN: Title V Reports

**RE: Title V Semi-Annual Monitoring Report Period (1/1/2012 to 6/30/2012)  
for Facility #A0148, Pursuant to Section I, Condition F of the Title V Permit.**

To Whom It May Concern:

Ball Metal Beverage Container Corp., Fairfield Can Plant is submitting the semi-annual monitoring report required by Section I, Condition F of our Title V permit.

There have been no instances of breakdown during this reporting period. Ball currently complies with all applicable limits and monitoring requirements.

If you have any questions, please call Stan Nakayama at (707) 437-7583 or Bob Hall at (303) 460-5445.

**COMPLIANCE CERTIFICATION**

*Based on information and belief formed after reasonable inquiry, the statements and information in this monitoring report are true, accurate and complete.*

David R. Trujillo

Name of responsible official

Signature

Enclosures

cc: Bob Hall with attachments  
Faye Bruno, BAAQMD

**Table VII – A**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-4 Decoration Oven, Line 1**

| Pollutant | Emission Limit Citation        | FE Y/N | Emission Limit   | Monitoring Requirement Citation | Monitoring Frequency (P/C/N) | Monitoring Type                                 | Continuous Compliance? (Y/N) |
|-----------|--------------------------------|--------|--|---------------------------------|------------------------------|---|------------------------------|
| VOC       | BAAQMD 8-11-301.3              | Y      | 2.1 lbs/gal  | BAAQMD 8-11-501.2               | P/D                          | Coating Records <sup>1</sup>                    | Y                            |
|           | BAAQMD 8-11-301.10             | N      | 2.5 lbs/gal  | BAAQMD 8-11-501.4               | P/M                          | Coating Records <sup>1</sup>                    | Y                            |
|           | BAAQMD 8-11-502                | Y      | 90% (wt) or greater VOC destruction efficiency   | BAAQMD 8-11-504                 | C                            | Temperature Chart Recorder                      | Y                            |
|           | SIP 8-11-301.9                 | Y      | 2.5 lbs/gal  | BAAQMD 8-11-501                 | P/W                          | Coating Records <sup>1</sup>                    | Y                            |
|           | BAAQMD Condition #9904 Part 1  |        | 1400° F and inlet manifold pressure of -1.5 in of water except during bypass as allowed in Condition #9904, Part 7         | BAAQMD Condition #9904, Part 2  | C                            | Temperature Chart Recorder and pressure monitor | Y                            |
|           | BAAQMD Condition #9904 Part 1a | Y      | Oven damper closed position during normal operation  | BAAQMD Condition #9904, Part 2  | P/M                          | Monitor damper position                         | Y                            |
|           | BAAQMD Condition #9904 Part 10 | Y      | 95% (wt) or greater destruction efficiency   | BAAQMD Condition #9904, Part 2  | C                            | Temperature Chart Recorder                      | Y                            |
|           | BAAQMD Condition #9904 Part 13 | Y      | 95% (wt) or greater destruction efficiency   | BAAQMD Condition #9904, Part 11 | P/A                          | Source Test                                     | Y                            |
|           | BAAQMD Condition #9904 Part 17 | Y      | 47.37 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-4, S-12, & S-62) | BAAQMD Condition #9904, Part 17 | P/M                          | Emission Records                                | Y                            |
|           | BAAQMD Condition #21993 Part 1 | Y      | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs   | BAAQMD Condition #21993, Part 2 | P/M                          | Emission Records                                | Y                            |

**Table VII – B**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-5 Basecoat Oven, Line 2**

| Pollutant | Emission Limit Citation | FE Y/N | Emission Limit                                 | Monitoring Requirement Citation | Monitoring Frequency (P/C/N) | Monitoring Type                                 | Continuous Compliance? (Y/N) |
|-----------|-------------------------|--------|--|---------------------------------|------------------------------|---|------------------------------|
| POC       | BAAQMD 8-11-301.3       | Y      | 2.1 lbs/gal                                    | BAAQMD 8-11-501                 | P/W                          | Coating Records <sup>1</sup>                    | Y                            |
| POC       | BAAQMD 8-11-302         | Y      | 90% (wt) or greater VOC destruction efficiency | BAAQMD 8-11-504                 | C                            | Temperature Chart Recorder and pressure monitor | Y                            |
|           | BAAQMD                  | N      | 1400°F and inlet                               | BAAQMD                          | C                            | Temperature                                     | Y                            |

<sup>1</sup> All coatings received are formulated to be less than the limits set forth in BAAQMD 8-11-301.

|     |                                |   |   |                                 |     |                                     |   |
|-----|--------------------------------|---|---|---------------------------------|-----|-------------------------------------|---|
|     | Condition #9904 Part 1         |   | manifold pressure of - 1.5 in of water except during bypass as allowed in Condition #9904, Part 7                   | Condition #9904, Part 2         |     | Chart Recorder and pressure monitor |   |
|     | BAAQMD Condition #9904 Part 1a | N | Oven damper closed position during normal operation   | BAAQMD Condition #9904, Part 2  | P/D | Monitor damper position             | Y |
|     | BAAQMD Condition #9904 Part 10 | Y | 95% (wt) or greater destruction efficiency  | BAAQMD Condition #9904, Part 2  | C   | Temperature Chart Recorder          | Y |
|     | BAAQMD Condition #9904 Part 10 | Y | 95% (wt) or greater destruction efficiency  | BAAQMD Condition #9904, Part 11 | P/A | Source Test                         | Y |
|     | BAAQMD Condition #9904 Part 22 | Y | 54.7 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-5, S-51,.) | BAAQMD Condition #9904, Part 25 | P/M | Emission Records                    | Y |
| HAP | BAAQMD Condition #21993 Part 1 | Y | 9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs   | BAAQMD Condition #21993, Part 2 | P/M | Emission Records                    | Y |

**Table VII - C  
Applicable Limits and Compliance Monitoring Requirements  
S-8 Interior Coating Oven, Line 1**

| Pollutant | Emission Limit Citation        | FE Y/N | Emission Limit   | Monitoring Requirement Citation | Monitoring Frequency (P/C/N) | Monitoring Type                                 | Continuous Compliance? (Y/N) |
|-----------|--------------------------------|--------|--|---------------------------------|------------------------------|---|------------------------------|
| POC       | BAAQMD 8-11-301.4.1            | N      | 3.5 lb/gal   | BAAQMD 8-11-501                 | P/W                          | Coating Records <sup>1</sup>                    | Y                            |
|           | BAAQMD 8-11-302                | Y      | 90% (wt) or greater VOC destruction efficiency   | BAAQMD 8-11-504                 | C                            | Temperature Chart Recorder                      | Y                            |
|           | BAAQMD Condition #9904 Part 1  | N      | 1400°F and inlet manifold pressure of - 1.5 in of water except during bypass as allowed in Condition #9904, Part 7 | BAAQMD Condition #9904, Part 2  | C                            | Temperature Chart Recorder and pressure monitor | Y                            |
|           | BAAQMD Condition #9904 Part 1a | N      | Oven damper closed position during normal operation  | BAAQMD Condition #9904, Part 2  | C                            | Monitor damper position                         | Y                            |
|           | BAAQMD Condition #9904 Part 10 | Y      | 95% (wt) or greater destruction efficiency   | BAAQMD Condition #9904, Part 2  | C                            | Temperature Chart Recorder                      | Y                            |
|           | BAAQMD Condition #9904 Part 10 | Y      | 95% (wt) or greater destruction efficiency   | BAAQMD Condition #9904, Part 11 | P/A                          | Source Test Report                              | Y                            |
|           | BAAQMD Condition #9904 Part 10 | Y      | 119 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-6 & S-16)  | BAAQMD Condition #9904, Part 17 | P/M                          | Emission Records                                | Y                            |
| HAP       | BAAQMD Condition #21993 Part 1 | Y      | 9 tons/yr of any single HAP or 23 ton/yr of any  | BAAQMD Condition #21993, Part 2 | P/M                          | Emission Records                                | Y                            |

|  |  |  |                     |  |  |  |
|--|--|--|---------------------|--|--|--|
|  |  |  | combination of HAPs |  |  |  |
|--|--|--|---------------------|--|--|--|

**Table VII – D  
Applicable Limits and Compliance Monitoring Requirements  
S-7 Interior Coating Oven, Line 2**

| Pollutant | Emission Limit Citation                   | FE Y/N | Emission Limit  | Monitoring Requirement Citation       | Monitoring Frequency (P/C/N) | Monitoring Type                                 | Continuous Compliance? (Y/N) |
|-----------|---|--------|---|---------------------------------------|------------------------------|---|------------------------------|
| VOC       | BAAQMD 8-11-301.4.1                       | N      | 3.5 lb/gal  | BAAQMD 8-11-501                       | P/W                          | Coating Records <sup>1</sup>                    | Y                            |
|           | BAAQMD 8-11-302                           | Y      | 90% (wt) or greater VOC destruction efficiency  | BAAQMD 8-11-504                       | C                            | Temperature Chart Recorder                      | Y                            |
|           | 40 CFR 60, Subpart WWW, Section 60.492(a) | Y      | 0.29 kg VOC/l   | 40 CFR 60 Subpart WWW, Section 60.495 | P/D                          | Coating Records <sup>1</sup>                    | Y                            |
|           | BAAQMD Condition #9904 Part 1             | N      | 1400°F and inlet manifold pressure of -1.5 in of water except during bypass as allowed in Condition #9904, Part 7                 | BAAQMD Condition #9904, Part 2        | C                            | Temperature Chart Recorder and pressure monitor | Y                            |
|           | BAAQMD Condition #9904 Part 1a            | N      | Oven damper closed position during normal operation   | BAAQMD Condition #9904, Part 2        | P/W                          | Monitor damper position                         | Y                            |
| POC       | BAAQMD Condition #9904 Part 10            | Y      | 95% (wt) or greater destruction efficiency  | BAAQMD Condition #9904, Part 2        | C                            | Temperature Chart Recorder                      | Y                            |
|           | BAAQMD Condition #9904 Part 10            | Y      | 95% (wt) or greater destruction efficiency  | BAAQMD Condition #9904, Part 11       | P/A                          | Source Test                                     | Y                            |
|           | BAAQMD Condition #9904 Part 18            | Y      | 288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-61) | BAAQMD Condition #9904, Part 21       | P/M                          | Emission Records                                | Y                            |
| HAP       | BAAQMD Condition #21993 Part 1            | Y      | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs  | BAAQMD Condition #21993, Part 2       | P/M                          | Emission Records                                | Y                            |

**Table VII – E**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-12 Printer with Overvarnisher, Line 1**

| Pollutant | Emission Limit Citation        | FE Y/N | Emission Limit   | Monitoring Requirement Citation | Monitoring Frequency (P/C/N) | Monitoring Type              | Continuous Compliance? (Y/N) |
|-----------|--------------------------------|--------|--|---------------------------------|------------------------------|------------------------------|------------------------------|
| VOC       | BAAQMD 8-11-301.3              | Y      | 2.1 lb/gal   | BAAQMD 8-11-501                 | P/W                          | Coating Records <sup>1</sup> | Y                            |
|           | BAAQMD 8-11-301.10             | N      | 2.5 lbs/gal  | BAAQMD 8-11-501                 | P/W                          | Coating Records <sup>1</sup> | Y                            |
|           | BAAQMD Condition #9904 Part 14 | Y      | 47.97 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-4, S-12, & S-62) | BAAQMD Condition #9904, Part 17 | P/M                          | Emission Records             | Y                            |
| HAP       | BAAQMD Condition #21993 Part 1 | Y      | 9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs  | BAAQMD Condition #21993, Part 2 | P/M                          | Emission Records             | Y                            |

**Table VII – F**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-13 Printer with Overvarnisher, Line 2**  
**S-27 Printer #32 with Overvarnisher, Line 3**

| Pollutant | Emission Limit Citation        | FE Y/N | Emission Limit  | Monitoring Requirement Citation | Monitoring Frequency (P/C/N) | Monitoring Type  | Continuous Compliance? (Y/N) |
|-----------|--------------------------------|--------|---|---------------------------------|------------------------------|------------------|------------------------------|
| VOC       | BAAQMD 8-11-301.3              | Y      | 2.1 lb/gal  | BAAQMD 8-11-501                 | P/W                          | Coating Records  | Y                            |
| VOC       | BAAQMD Condition #9904 Part 26 | Y      | 83.31 tons/12 consecutive month period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, & S-55-60 except S-59) | BAAQMD Condition #9904 Part 31  | P/M                          | Emission Records | Y                            |
|           | BAAQMD Condition #9904 Part 27 | Y      | 31.35 tons/12 consecutive month period prior to control due to ink usage, excluding clean-up solvent (combined limit for S-13, S-25, S-27, S-53, & S-60)  | BAAQMD Condition #9904 Part 31  | P/M                          | Emission Records | Y                            |
| HAP       | BAAQMD Condition #21993 Part 1 | Y      | 9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs   | BAAQMD Condition #21993, Part 2 | P/M                          | Emission Records | Y                            |

**Table VII – G**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-16 Interior Coating Spray Bank, Line 1**

| Pollutant | Emission Limit Citation           | FE Y/N | Emission Limit  | Monitoring Requirement Citation   | Monitoring Frequency (P/C/N) | Monitoring Type                | Continuous Compliance? (Y/N) |
|-----------|-----------------------------------|--------|---|-----------------------------------|------------------------------|--------------------------------|------------------------------|
| VOC       | BAAQMD 8-11-301.4.1               | N      | 3.5 lb/gal  | BAAQMD 8-11-501                   | P/W                          | Coating Records <sup>1</sup>   | Y                            |
|           | BAAQMD Condition #9904 Part 13    | Y      | 119 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-6 & S-16) | BAAQMD Condition #9904 Part 17    | P/M                          | Emission Records               | Y                            |
| TSP       | BAAQMD 6-310                      | Y      | 0.15 gr/dscf  | BAAQMD Condition #16289 Part 3(b) | P                            | Baghouse Filter Bag Inspection | Y                            |
|           | BAAQMD Condition #16289 Part 3(a) | Y      | ≥ 0.2 inches of H <sub>2</sub> O, and<br>< 5 inches of H <sub>2</sub> O   | BAAQMD Condition #16289 Part 3(b) | P/W                          | pressure drop inspection       | Y                            |
| HAP       | BAAQMD Condition #21993 Part 1    | Y      | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs  | BAAQMD Condition #21993, Part 2   | P/M                          | Emission Records               | Y                            |

**Table VII – H**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-17 Interior Coating Spray Bank, Line 2**

| Pollutant | Emission Limit Citation           | FE Y/N | Emission Limit  | Monitoring Requirement Citation   | Monitoring Frequency (P/C/N) | Monitoring Type                | Continuous Compliance? (Y/N) |
|-----------|-----------------------------------|--------|---|-----------------------------------|------------------------------|--------------------------------|------------------------------|
| VOC       | BAAQMD 8-11-301.4.1               | N      | 3.5 lb/gal  | BAAQMD 8-11-501                   | P/W                          | Coating Records <sup>1</sup>   | Y                            |
|           | BAAQMD Condition #9904 Part 18    | Y      | 288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-31) | BAAQMD Condition #9904 Part 21    | P/M                          | Emission Records               | Y                            |
| TSP       | BAAQMD 6-310                      | Y      | 0.15 gr/dscf  | BAAQMD Condition #16289 Part 3(b) | P                            | Baghouse Filter Bag Inspection | Y                            |
|           | BAAQMD Condition #16289 Part 3(a) | Y      | ≥ 0.2 inches of H <sub>2</sub> O, and<br>< 5 inches of H <sub>2</sub> O   | BAAQMD Condition #16289 Part 3(b) | P/W                          | pressure drop inspection       | Y                            |
| HAP       | BAAQMD Condition #21993 Part 1    | Y      | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs  | BAAQMD Condition #21993, Part 2   | P/M                          | Emission Records               | Y                            |

**Table VII – I**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-24 Interior Coating Spray Bank, Line 3**

| Pollutant | Emission Limit Citation           | FE Y/N | Emission Limit  | Monitoring Requirement Citation   | Monitoring Frequency (P/C/N) | Monitoring Type                | Continuous Compliance? (Y/N) |
|-----------|-----------------------------------|--------|---|-----------------------------------|------------------------------|--------------------------------|------------------------------|
| VOC       | BAAQMD 8-11-301.4.1               | Y      | 2.1 lbs/gal   | BAAQMD 8-11-501                   | P/W                          | Coating Records <sup>1</sup>   | Y                            |
|           | BAAQMD Condition #9904 Part 18    | Y      | 288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-61) | BAAQMD Condition #9904 Part 21    | P/M                          | Emission Records               | Y                            |
| TSP       | BAAQMD 8-310                      | Y      | 0.15 gr/dscf  | BAAQMD Condition #16291 Part 3(b) | P                            | Baghouse Filter Bag Inspection | Y                            |
|           | BAAQMD Condition #16291 Part 3(a) | Y      | ≥ 0.2 inches of H <sub>2</sub> O, and < 5 inches of H <sub>2</sub> O  | BAAQMD Condition #16291 Part 3(b) | P/W                          | pressure drop inspection       | Y                            |
| HAP       | BAAQMD Condition #21993 Part 1    | Y      | 9 tons/yr of any single HAP or 21 tons/yr of any combination of HAPs  | BAAQMD Condition #21993, Part 2   | P/M                          | Emission Records               | Y                            |

**Table VII – J**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-56 Decorator Oven #31, Line 3**  
**S-58 Decorator Oven #32, Line 3**

| Pollutant | Emission Limit Citation        | FE Y/N | Emission Limit  | Monitoring Requirement Citation | Monitoring Frequency (P/C/N) | Monitoring Type                                 | Continuous Compliance? (Y/N) |
|-----------|--------------------------------|--------|---|---------------------------------|------------------------------|---|------------------------------|
| VOC       | BAAQMD 8-11-301.3              | Y      | 2.1 lbs/gal   | BAAQMD 8-11-501                 | P/W                          | Coating Records <sup>1</sup>                    | Y                            |
|           | BAAQMD 8-11-302                | Y      | 90% (wt) or greater VOC destruction efficiency  | BAAQMD 8-11-504                 | C                            | Temperature Chart Recorder                      | Y                            |
|           | BAAQMD Condition #9904 Part 1  | N      | 1400°F and inlet manifold pressure of -1.5 in of water except during bypass as allowed in Condition #9904, Part 7 | BAAQMD Condition #9904, Part 2  | C                            | Temperature Chart Recorder and pressure monitor | Y                            |
|           | BAAQMD Condition #9904 Part 1a | N      | Oven damper closed position during normal operation   | BAAQMD Condition #9904, Part 2  | C                            | Monitor damper position                         | Y                            |
|           | BAAQMD Condition #9904 Part 10 | Y      | 95% (wt) or greater destruction efficiency  | BAAQMD Condition #9904, Part 2  | C                            | Temperature Chart Recorder                      | Y                            |
|           | BAAQMD Condition #9904 Part 10 | Y      | 95% (wt) or greater destruction efficiency  | BAAQMD Condition #9904, Part 11 | P/A                          | Source Test Report                              | Y                            |

|     |                                |   |  |                                 |     |                  |   |
|-----|--------------------------------|---|--|---------------------------------|-----|------------------|---|
|     | BAAQMD Condition #9904 Part 25 | Y | 53.31 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, S-55-56 except S-60)       | BAAQMD Condition #9904, Part 31 | P/M | Emission Records | Y |
| POC | BAAQMD Condition #9904 Part 27 | Y | 31.35 tons/12 consecutive month period prior to control due ink usage, excluding clean-up solvent (combined limit for S-13, S-56, S-58, S-27, S-53 & S-60) | BAAQMD Condition #9904, Part 31 | P/M | Emission Records | Y |
| HAP | BAAQMD Condition #21993 Part 1 | Y | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs   | BAAQMD Condition #21993, Part 2 | P/M | Emission Records | Y |

**Table VII – K  
Applicable Limits and Compliance Monitoring Requirements  
S-35 Wipe Cleaning Operation**

| Pollutant | Emission Limit Citation        | FE Y/N | Emission Limit  | Monitoring Requirement Citation | Monitoring Frequency (P/C/N) | Monitoring Type  | Continuous Compliance? (Y/N) |
|-----------|--------------------------------|--------|---|---------------------------------|------------------------------|------------------|------------------------------|
| VOC       | BAAQMD Condition #1701 Part 1  | Y      | 16,830 tons clean-up solvent/12 consecutive month period for operations associated with S-12-17, S-24, S-28, S-35, S-41-46, S-51, S-52, S-54, S-55, S-57, S-59, & S-60. | BAAQMD Condition 1701 Part 2    | P/M                          | Emission Records | Y                            |
| HAP       | BAAQMD Condition #21993 Part 1 | Y      | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs  | BAAQMD Condition #21993, Part 2 | P/M                          | Emission Records | Y                            |

**Table VII – L  
Applicable Limits and Compliance Monitoring Requirements  
S-51 Basecoater, Line 2**

| Pollutant | Emission Limit Citation                   | FE Y/N | Emission Limit                             | Monitoring Requirement Citation        | Monitoring Frequency (P/C/N) | Monitoring Type              | Continuous Compliance? (Y/N) |
|-----------|---|--------|--|--|------------------------------|------------------------------|------------------------------|
| VOC       | BAAQMD 8-11-301.3                         | Y      | 2.1 lbs/gal                                | BAAQMD 8-11-501                        | P/W                          | Coating Records <sup>1</sup> | Y                            |
|           | 40 CFR 60, Subpart WWW, Section 60.492(a) | Y      | 0.29 kg VOC/l                              | 40 CFR 60, Subpart WWW, Section 60.495 | P/Q                          | Coating Records <sup>1</sup> | Y                            |
|           | BAAQMD Condition #9904 Part 10            | Y      | 95% (wt) or greater destruction efficiency | BAAQMD Condition #9904, Part 2         | C                            | Temperature Chart Recorder   | Y                            |



|     |                                |   |  |                                 |     |                    |   |
|-----|--------------------------------|---|--|---------------------------------|-----|--------------------|---|
|     | BAAQMD Condition #9904 Part 10 | Y | 95% (wt) or greater destruction efficiency   | BAAQMD Condition #9904, Part 11 | P/A | Source Test Report | Y |
|     | BAAQMD Condition #9904 Part 22 | Y | 64.7 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-5 and S-51) | BAAQMD Condition #9904 Part 25  | P/M | Emission Records   | Y |
| HAP | BAAQMD Condition #21993 Part 1 | Y | 9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs  | BAAQMD Condition #21993, Part 2 | P/M | Emission Records   | Y |

**Table VII - M**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-53 Decoration Oven, Line 2**

| Pollutant | Emission Limit Citation        | FE Y/N | Emission Limit   | Monitoring Requirement Citation | Monitoring Frequency (P/C/N) | Monitoring Type                                 | Continuous Compliance ? (Y/N) |
|-----------|--------------------------------|--------|--|---------------------------------|------------------------------|---|-------------------------------|
| VOC       | BAAQMD 8-11-301.3              | Y      | 2.1 lbs/gal  | BAAQMD 8-11-501                 | P/W                          | Coating Records <sup>1</sup>                    | Y                             |
|           | BAAQMD 8-11-302                | Y      | 90% (wt) or greater VOC destruction efficiency   | BAAQMD 8-11-504                 | C                            | Temperature Chart Recorder                      | Y                             |
|           | BAAQMD Condition #9904 Part 1  | N      | 1400°F and inlet manifold pressure of -1.5 in of water except during bypass as allowed in Condition #9904, Part 7  | BAAQMD Condition #9904, Part 2  | C                            | Temperature Chart Recorder and pressure monitor | Y                             |
|           | BAAQMD Condition #9904 Part 1a | N      | Oven damper closed position during normal operation  | BAAQMD Condition #9904, Part 2  | C                            | Monitor damper position                         | Y                             |
|           | BAAQMD Condition #9904 Part 10 | Y      | 95% (wt) or greater destruction efficiency   | BAAQMD Condition #9904, Part 2  | C                            | Temperature Chart Recorder                      | Y                             |
|           | BAAQMD Condition #9904 Part 10 | Y      | 95% (wt) or greater destruction efficiency   | BAAQMD Condition #9904, Part 11 | P/A                          | Source Test Report                              | Y                             |
|           | BAAQMD Condition #9904 Part 26 | Y      | 83.31 tons/12 consecutive month period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-62, S-53, S-55-58 and S-60) | BAAQMD Condition #9904, Part 31 | P/M                          | Emission Records                                | Y                             |
|           | BAAQMD Condition #9904 Part 24 |        | 31.35 tons/12 consecutive month period prior to control due to ink usage,  | BAAQMD Condition #9904, Part 26 | P/M                          | Emission Records                                | Y                             |

|     |                                |   |   |                                 |     |                  |   |
|-----|--------------------------------|---|---|---------------------------------|-----|------------------|---|
|     |                                |   | excluding clean-up solvent (combined limit for S-13, S-27, S-53, S-56, S-58 and S-60) |                                 |     |                  |   |
| HAP | BAAQMD Condition #21993 Part 1 | Y | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs                  | BAAQMD Condition #21993, Part 2 | P/M | Emission Records | Y |

**Table VII – N**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-52 Bottom Coater, Line 2**  
**S-55 Bottom Coater at Basecoater #31, Line 3**  
**S-57 Bottom Coater at Basecoater #32, Line 3**

| Pollutant | Emission Limit Citation                   | FE Y/N | Emission Limit  | Monitoring Requirement Citation        | Monitoring Frequency (P/C/N) | Monitoring Type              | Continuous Compliance ? (Y/N) |
|-----------|---|--------|---|--|------------------------------|------------------------------|-------------------------------|
| VOC       | BAAQMD 8-11-301.3                         | Y      | 2.1 lbs/gal   | BAAQMD 8-11-501                        | P/W                          | Coating Records <sup>1</sup> | Y                             |
|           | 40 CFR 60, Subpart WWW, Section 60.492(b) | Y      | 0.46 kg VOC/l   | 40 CFR 60, Subpart WWW, Section 60.495 | P/Q                          | Coating Records <sup>1</sup> | Y                             |
|           | BAAQMD Condition #9904 Part 2B            | Y      | 83.31 tons/12 consecutive month period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, and S-55-60 except 59) | BAAQMD Condition #9904, Part 31        | P/M                          | Emission Records             | Y                             |
| HAP       | BAAQMD Condition #21993 Part 1            | Y      | 8 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs  | BAAQMD Condition #21993, Part 2        | P/M                          | Emission Records             | Y                             |

**Table VII – O**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-60 Printer #32 with Overvarnisher, Line 3**

| Pollutant | Emission Limit Citation                   | FE Y/N | Emission Limit                  | Monitoring Requirement Citation        | Monitoring Frequency (P/C/N) | Monitoring Type              | Continuous Compliance ? (Y/N) |
|-----------|---|--------|---------------------------------|--|------------------------------|------------------------------|-------------------------------|
| VOC       | BAAQMD 8-11-301.3                         | Y      | 2.1 lbs/gal                     | BAAQMD 8-11-501                        | P/W                          | Coating Records <sup>1</sup> | Y                             |
|           | 40 CFR 60, Subpart WWW, Section 60.492(b) | Y      | 0.46 kg VOC/l                   | 40 CFR 60, Subpart WWW, Section 60.495 | P/Q                          | Coating Records <sup>1</sup> | Y                             |
|           | BAAQMD Condition                          | Y      | 83.31 tons/12 consecutive month | BAAQMD Condition                       | P/M                          | Emission Records             | Y                             |

|     |                                |   |   |                                 |     |                  |   |
|-----|--------------------------------|---|---|---------------------------------|-----|------------------|---|
|     | #9904 Part 26                  |   | period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, S-55-60 except S-59) | #9904, Part 31                  |     |                  |   |
|     | BAAQMD Condition #9904 Part 27 | Y | 31.35 tons/12 consecutive month period prior to control due to ink usage, excluding clean-up solvent (combined limit for S-13, S-27, S-53, S-56, S-58 & S-60)   | BAAQMD Condition #9904, Part 31 | P/M | Emission Records | Y |
| HAP | BAAQMD Condition #21993 Part 1 | Y | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs  | BAAQMD Condition #21993, Part 2 | P/M | Emission Records | Y |

**Table VII – P  
Applicable Limits and Compliance Monitoring Requirements  
S-61 Interior Coating Oven, Line 3**

| Pollutant | Emission Limit Citation                   | FE Y/N | Emission Limit  | Monitoring Requirement Citation        | Monitoring Frequency (P/C/N) | Monitoring Type                                 | Continuous Compliance ? (Y/N) |
|-----------|---|--------|---|--|------------------------------|---|-------------------------------|
| VOC       | BAAQMD 8-11-301.4                         | Y      | 3.5 lb/gal  | BAAQMD 8-11-501                        | P/W                          | Coating Records <sup>1</sup>                    | Y                             |
|           | BAAQMD 8-11-302                           | Y      | 90% (wt) or greater VOC destruction efficiency  | BAAQMD 8-11-504                        | C                            | Temperature Chart Recorder                      | Y                             |
|           | 40 CFR 60, Subpart WWW, Section 60.492(b) | Y      | 0.89 kg VOC/l   | 40 CFR 60, Subpart WWW, Section 60.495 | P/Q                          | Coating Records <sup>1</sup>                    | Y                             |
|           | BAAQMD Condition #9904 Part 1             | N      | 1400°F and inlet manifold pressure of -1.5 in. of water except during bypass as allowed in Condition #9904, Part 7                | BAAQMD Condition #9904, Part 2         | C                            | Temperature Chart Recorder and pressure monitor | Y                             |
|           | BAAQMD Condition #9904 Part 1a            | N      | Oven damper closed position during normal operation   | BAAQMD Condition #9904, Part 2         | C                            | Monitor damper position                         | Y                             |
|           | BAAQMD Condition #9904 Part 10            | Y      | 85% (wt) or greater destruction efficiency  | BAAQMD Condition #9904, Part 2         | C                            | Temperature Chart Recorder                      | Y                             |
|           | BAAQMD Condition #9904 Part 10            | Y      | 95% (wt) or greater destruction efficiency  | BAAQMD Condition #9904, Part 11        | P/A                          | Source Test Report                              | Y                             |
|           | BAAQMD Condition #9904 Part 18            | Y      | 286.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-81) | BAAQMD Condition #9904 Part 21         | P/M                          | Emission Records                                | Y                             |

|     |                                |   |  |                                |     |                  |   |
|-----|--------------------------------|---|--|--------------------------------|-----|------------------|---|
| HAP | BAAQMD Condition #21993 Part 1 | Y | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs | BAAQMD Condition #21993 Part 2 | P/M | Emission Records | Y |
|-----|--------------------------------|---|--|--------------------------------|-----|------------------|---|

**Table VII – Q  
Applicable Limits and Compliance Monitoring Requirements  
S-62 Bottom Coater, Line 1**

| Pollutant | Emission Limit Citation                  | FE Y/N | Emission Limit   | Monitoring Requirement Citation       | Monitoring Frequency (P/C/N) | Monitoring Type              | Continuous Compliance ? (Y/N) |
|-----------|--|--------|--|---------------------------------------|------------------------------|------------------------------|-------------------------------|
| VOC       | BAAQMD 8-11-301.3                        | Y      | 2.1 lb/gal   | BAAQMD 8-11-501                       | P/W                          | Coating Records <sup>1</sup> | Y                             |
|           | 40 CFR 60, Subpart WW, Section 60.492(a) | Y      | 0.41 kg VOC/l  | 40 CFR 60, Subpart WW, Section 60.495 | P/Q                          | Coating Records              | Y                             |
|           | BAAQMD Condition #9904 Part 14           | Y      | 47.37 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-4, S-12, & S-62) | BAAQMD Condition #9904 Part 17        | P/M                          | Emission Records             | Y                             |
|           | BAAQMD Condition #14636 Part 1           | Y      | 4.45 tons/12 consecutive month period prior to control, excluding clean-up solvent for bottomcoating                       | BAAQMD Condition #14636 Part 4        | P/M                          | Coating Records <sup>1</sup> | Y                             |
| HAP       | BAAQMD Condition #21993 Part 1           | Y      | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs   | BAAQMD Condition #21993 Part 2        | P/M                          | Emission Records             | Y                             |

**Table VII-R  
Applicable Limits and Compliance Monitoring Requirements  
S-63 Interior Coating Storage Tank  
S-64 Interior Coating Storage Tank**

| Pollutant | Emission Limit Citation        | FE Y/N | Emission Limit   | Monitoring Requirement Citation | Monitoring Frequency (P/C/N) | Monitoring Type  | Continuous Compliance ? (Y/N) |
|-----------|--------------------------------|--------|--|---------------------------------|------------------------------|------------------|-------------------------------|
| VOC       | BAAQMD Condition #18728 Part 1 |        | 275,000 gallons/12 consecutive month period                          | BAAQMD Condition #18728 Part 3  | P/M                          | Usage Records    | Y                             |
|           | BAAQMD Condition #18728 Part 2 |        | Use only water reducible liner coating                               | BAAQMD Condition #18728 Part 3  | C                            | VOC records      | Y                             |
| HAP       | BAAQMD Condition #21993 Part 1 | Y      | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs | BAAQMD Condition #21993 Part 2  | P/M                          | Emission Records | Y                             |

**Table VII-S  
Applicable Limits and Compliance Monitoring Requirements  
S-65 Emergency Standby Generator  
S-66 Emergency Standby Generator**

| Pollutant                     | Emission Limit Citation        | FE Y/N | Emission Limit   | Monitoring Requirement Citation     | Monitoring Frequency (P/C/N) | Monitoring Type               | Continuous Compliance ? (Y/N) |
|-------------------------------|--------------------------------|--------|--|-------------------------------------|------------------------------|-------------------------------|-------------------------------|
| FP                            | BAAQMD 8-310                   | Y      | 0.15 gr/dscf   | N                                   | N                            | N                             | Y                             |
| FP                            | BAAQMD 8-310                   | Y      | No. 2 on Ringelmann Chart for 3 minutes in any hour  | N                                   | N                            | N                             | Y                             |
| FP                            | BAAQMD 6-310                   | Y      | 0.15 gr/dscf   | N                                   | N                            | N                             | Y                             |
| SO <sub>2</sub>               | BAAQMD 9-1-301                 | Y      | Ground level concentration of 0.5 ppm continuously for 3 consecutive minutes, or 0.25 ppm averaged over 60 consecutive minutes, or 0.05 ppm averaged over 24 hours |                                     |                              |                               | Y                             |
| SO <sub>2</sub>               | BAAQMD 9-1-302                 | Y      | 30 ppm in the gas stream   | N                                   | N                            | N                             | Y                             |
| NO <sub>x</sub>               | BAAQMD 9-8-301.2               | Y      | 140 ppmv @ 15% O <sub>2</sub> , dry  |                                     | P/A                          |                               | Y                             |
|                               | BAAQMD 9-8-302.1               | Y      | 140 ppmv @ 15% O <sub>2</sub> , dry  |                                     | P/A                          |                               | Y                             |
| CO                            | BAAQMD 9-8-301.3               | Y      | 2000 ppmv @ 15% O <sub>2</sub> , dry   |                                     | P/A                          |                               | Y                             |
|                               | BAAQMD 9-8-302.3               | Y      | 2000 ppmv @ 15% O <sub>2</sub> , dry   |                                     | P/A                          |                               | Y                             |
| PM, NO <sub>x</sub> , CO, POC | BAAQMD Condition #18729 Part 2 | Y      | 100 hrs/yr for reliability-related activities  | BAAQMD Condition #18729, Part 4 & 5 | P/M                          | Totalizer counter and records | Y                             |
| HAP                           | BAAQMD Condition #21993 Part 1 | Y      | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs   | BAAQMD Condition #21993, Part 2     | P/M                          | Emission Records              | Y                             |

**Table VII - T  
Applicable Limits and Compliance Monitoring Requirements  
S-67 Video Jet Printer**

| Pollutant | Emission Limit Citation | FE Y/N | Emission Limit | Monitoring Requirement Citation | Monitoring Frequency (P/C/N) | Monitoring Type              | Continuous Compliance ? (Y/N) |
|-----------|-------------------------|--------|----------------|---------------------------------|------------------------------|------------------------------|-------------------------------|
| VOC       | BAAQMD 8-11-305         | Y      | 2.1 lb/gal     | BAAQMD 8-11-501                 | P/M                          | Coating Records <sup>1</sup> | Y                             |
|           | 40 CFR 60, Subpart WW,  | Y      | 0.46 kg VOC/l  | 40 CFR 60, Subpart WW,          | P/Q                          | Coating Records <sup>1</sup> | Y                             |

|     |                                |   |  |                                 |     |                  |   |
|-----|--------------------------------|---|--|---------------------------------|-----|------------------|---|
|     | Section 60.492(a)              |   |  | Section 60.495                  |     |                  |   |
|     | BAAQMD Condition #18544 Part 1 | Y | 5 gallons / 12 consecutive month period                              | BAAQMD Condition #18544, Part 3 | P/M | Records          | Y |
|     | BAAQMD Condition #18544 Part 2 | Y | 1 gallon / 12 consecutive month period                               | BAAQMD Condition #18544, Part 3 | P/M | Records          | Y |
| HAP | BAAQMD Condition #21993 Part 1 | Y | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs | BAAQMD Condition #21993, Part 2 | P/M | Emission Records | Y |

**Table VII – U  
Applicable Limits and Compliance Monitoring Requirements  
S-68 Ink Dot System, Line 3**

| Pollutant | Emission Limit Citation                  | FE Y/N | Emission Limit   | Monitoring Requirement Citation       | Monitoring Frequency (P/C/N) | Monitoring Type              | Continuous Compliance ? (Y/N) |
|-----------|--|--------|--|---------------------------------------|------------------------------|------------------------------|-------------------------------|
| VOC       | BAAQMD 8-11-305                          | Y      | 2.1 lb/gal   | BAAQMD 8-11-501                       | P/M                          | Coating Records <sup>1</sup> | Y                             |
|           | 40 CFR 60, Subpart WW, Section 60.492(b) | Y      | 0.46 kg VOC/l  | 40 CFR 60, Subpart WW, Section 60.495 | P/Q                          | Coating Records <sup>1</sup> | Y                             |
|           | BAAQMD Condition #18545 Part 1           | Y      | 75 gallons / 12 consecutive month period                             | BAAQMD Condition #18545, Part 3       | P/M                          | Records                      | Y                             |
|           | BAAQMD Condition #18545 Part 2           | Y      | 15 gallon / 12 consecutive month period                              | BAAQMD Condition #18545, Part 3       | P/M                          | Records                      | Y                             |
| HAP       | BAAQMD Condition #21993 Part 1           | Y      | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs | BAAQMD Condition #21993, Part 2       | P/M                          | Emission Records             | Y                             |

**Table VII – V  
Applicable Limits and Compliance Monitoring Requirements  
S-68 Ink Dot System, Line 1 & 2**

| Pollutant | Emission Limit Citation                  | FE Y/N | Emission Limit                           | Monitoring Requirement Citation       | Monitoring Frequency (P/C/N) | Monitoring Type              | Continuous Compliance ? (Y/N) |
|-----------|--|--------|--|---------------------------------------|------------------------------|------------------------------|-------------------------------|
| VOC       | BAAQMD 8-11-305                          | Y      | 2.1 lb/gal                               | BAAQMD 8-11-501                       | P/M                          | Coating Records <sup>1</sup> | Y                             |
|           | 40 CFR 60, Subpart WW, Section 60.492(b) | Y      | 0.46 kg VOC/l                            | 40 CFR 60, Subpart WW, Section 60.495 | P/Q                          | Coating Records <sup>1</sup> | Y                             |
|           | BAAQMD Condition #20955 Part 1           | Y      | 60 gallons / 12 consecutive month period | BAAQMD Condition #20955, Part 3       | P/M                          | Records                      | Y                             |

|     |                                |   |  |                                 |     |                  |   |
|-----|--------------------------------|---|--|---------------------------------|-----|------------------|---|
|     | BAAQMD Condition #20955 Part 2 | Y | 14 gallon / 12 consecutive month period                              | BAAQMD Condition #20955, Part 3 | P/M | Records          | Y |
| HAP | BAAQMD Condition #21995 Part 1 | Y | 9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs | BAAQMD Condition #21995, Part 2 | P/M | Emission Records | Y |

Footnote 1: All coatings received are formulated to be less than the limits set forth in BAAQMD 8-11-301.