



RECEIVED
2012 JUN 31 AM 11 39
BAY AREA AIR QUALITY
MANAGEMENT DISTRICT

Ball Corporation

Metal Beverage Packaging Division, Americas
2400 Huntington Drive, Fairfield, CA 94533-9734, (707) 437-5411

January 30, 2012

5412-L-003
Certified

Director of Compliance and Enforcement
Bay Area Air Quality Management District
939 Ellis Street
San Francisco, CA 94109

ATTN: Title V Reports

**RE: Title V Semi-Annual Monitoring Report Period (7/1/2011 to 12/31/2011)
for Facility #A0148, Pursuant to Section I, Condition F of the Title V Permit.**

To Whom It May Concern:

Ball Metal Beverage Container Corp., Fairfield Can Plant is submitting the semi-annual monitoring report required by Section I, Condition F of our Title V permit.

There have been no instances of breakdown during this reporting period. Ball currently complies with all applicable limits and monitoring requirements.

If you have any questions, please call Stan Nakayama at (707) 437-7583 or Bob Hall at (303) 460-5445.

COMPLIANCE CERTIFICATION

Based on information and belief formed after reasonable inquiry, the statements and information in this monitoring report are true, accurate and complete.

David R. Trujillo

Name of responsible official

Signature

Enclosures

cc: Bob Hall with attachments
Faye Bruno, BAAQMD

**Table VII – A
Applicable Limits and Compliance Monitoring Requirements
S-4 Decoration Oven, Line 1**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501.2	P/D	Coating Records ¹	Y
	BAAQMD 8-11-301.10	N	2.5 lbs/gal	BAAQMD 8-11-501.4	P/M	Coating Records ¹	Y
	BAAQMD 8-11-302	Y	99% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	SIP 8-11-301.9	Y	2.5 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 1		1400° F and inlet manifold pressure of -1.5 in of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9604 Part 1a	Y	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	P/M	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 13	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test	Y
	BAAQMD Condition #9904 Part 17	Y	47.37 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-4, S-12, & S-62)	BAAQMD Condition #9904, Part 17	P/M	Emission Records	Y
	BAAQMD Condition #21993 Part 1	Y	8 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII – B
Applicable Limits and Compliance Monitoring Requirements
S-5 Basecoat Oven, Line 2**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
POC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
POC	BAAQMD 8-11-302	Y	99% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD	N	1400°F and inlet	BAAQMD	C	Temperature	Y

¹ All coatings received are formulated to be less than the limits set forth in BAAQMD 8-11-301.

	Condition #9904 Part 1		manifold pressure of -1.5 in of water except during bypass as allowed in Condition #9904, Part 7	Condition #9904, Part 2		Chart Recorder and pressure monitor	
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	P/D	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test	Y
	BAAQMD Condition #9904 Part 22	Y	84.7 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-5, S-51,.)	BAAQMD Condition #9904, Part 25	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII - C
Applicable Limits and Compliance Monitoring Requirements
S-5 Interior Coating Oven, Line 1**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
POC	BAAQMD 8-11-301.4.1	N	3.5 lb/gal	BAAQMD 8-11-501	P/W	Coating Records	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 1	N	1400°F and inlet manifold pressure of -1.5 in of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	C	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test Report	Y
	BAAQMD Condition #9904 Part 10	Y	119 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-6 & S-16)	BAAQMD Condition #9904, Part 17	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

			combination of HAPs			
--	--	--	---------------------	--	--	--

Table VII – D
Applicable Limits and Compliance Monitoring Requirements
S-7 Interior Coating Oven, Line 2

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.4.1	N	3.5 lb/gal	BAAQMD 8-11-501	P/W	Coating Records	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	40 CFR 60, Subpart WWW, Section 60.492(a)	Y	0.29 kg VOC/l	40 CFR 60 Subpart WWW, Section 60.495	P/Q	Coating Records	Y
	BAAQMD Condition #9904 Part I	N	1400°F and inlet manifold pressure of -1.5 in. of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	P/W	Monitor damper position	Y
POC	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test	Y
	BAAQMD Condition #9904 Part 18	Y	288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-61)	BAAQMD Condition #9904, Part 21	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	8 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – E
Applicable Limits and Compliance Monitoring Requirements
S-12 Printer with Overvarnisher, Line 1

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD 8-11-301.10	N	2.5 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 14	Y	47.37 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-4, S-12, & S-62)	BAAQMD Condition #9904, Part 17	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – F
Applicable Limits and Compliance Monitoring Requirements
S-13 Printer with Overvarnisher, Line 2
S-27 Printer #32 with Overvarnisher, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
VOC	BAAQMD Condition #9904 Part 26	Y	83.31 tons/12 consecutive month period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, & S-55-60 except S-59)	BAAQMD Condition #9904 Part 31	P/M	Emission Records	Y
	BAAQMD Condition #9904 Part 27	Y	31.35 tons/12 consecutive month period prior to control due to ink usage, excluding clean-up solvent (combined limit for S-13, S-26, S-27, S-53, & S-60)	BAAQMD Condition #9904 Part 31	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – G
Applicable Limits and Compliance Monitoring Requirements
S-16 Interior Coating Spray Bank, Line 1

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.4 1	N	3.5 lb/gal	BAAQMD 8-11-501	P/W	Coating Records	Y
	BAAQMD Condition #9904 Part 13	Y	119 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-6 & S-16)	BAAQMD Condition #9904 Part 17	P/M	Emission Records	Y
TSP	BAAQMD 6-310	Y	0.15 gr/dscf	BAAQMD Condition #16289 Part 3(b)	P	Baghouse Filter Bag Inspection	Y
	BAAQMD Condition #16289 Part 3(a)	Y	≥ 0.2 inches of H ₂ O, and < 6 inches of H ₂ O	BAAQMD Condition #16289 Part 3(b)	P/W	pressure drop inspection	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII – H
Applicable Limits and Compliance Monitoring Requirements
S-17 Interior Coating Spray Bank, Line 2

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.4 1	N	3.5 lb/gal	BAAQMD 8-11-501	P/W	Coating Records	Y
	BAAQMD Condition #9904 Part 18	Y	288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-61)	BAAQMD Condition #9904 Part 21	P/M	Emission Records	Y
TSP	BAAQMD 6-310	Y	0.15 gr/dscf	BAAQMD Condition #16289 Part 3(b)	P	Baghouse Filter Bag Inspection	Y
	BAAQMD Condition #16289 Part 3(a)	Y	≥ 0.2 inches of H ₂ O and < 5 inches of H ₂ O	BAAQMD Condition #16289 Part 3(b)	P/W	pressure drop inspection	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII - I
Applicable Limits and Compliance Monitoring Requirements
S-24 Interior Coating Spray Bank, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.4.1	Y	2.1 lb/gal	BAAQMD 8-11-501	P/W	Coating Records	Y
	BAAQMD Condition #9904 Part 18	Y	288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-81)	BAAQMD Condition #9904 Part 21	P/M	Emission Records	Y
TSP	BAAQMD 6-310	Y	0.15 gr/dscf	BAAQMD Condition #18291 Part 3(b)	P	Baghouse Filter Bag Inspection	Y
	BAAQMD Condition #18291 Part 3(a)	Y	≥ 0.2 inches of H ₂ O, and < 5 inches of H ₂ O	BAAQMD Condition #18291 Part 3(b)	P/W	pressure drop inspection	Y
HAP	BAAQMD Condition #21993 Part 1	Y	8 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII - J
Applicable Limits and Compliance Monitoring Requirements
S-56 Decorator Oven #31, Line 3
S-58 Decorator Oven #32, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 1	N	1400°F and inlet manifold pressure of -1.5 in. of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	C	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test Report	Y

	BAAQMD Condition #9904 Part 28	Y	83.31 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, S-55-56 except S-60)	BAAQMD Condition #9904, Part 31	P/M	Emission Records	Y
POC	BAAQMD Condition #9904 Part 27	Y	31.35 tons/12 consecutive month period prior to control due ink usage, excluding clean-up solvent (combined limit for S-13, S-56, S-58, S-27, S-53 & S-60)	BAAQMD Condition #9904, Part 31	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII – K
Applicable Limits and Compliance Monitoring Requirements
S-35 Wipe Cleaning Operation**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD Condition #1701 Part 1	Y	16 830 tons clean-up solvent/12 consecutive month period for operations associated with S-12-17, S-24, S-28, S-35, S-41-46, S-51, S-52, S-54, S-55, S-57, S-59, & S-60.	BAAQMD Condition 1701 Part 2	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII – L
Applicable Limits and Compliance Monitoring Requirements
S-51 Basecoater, Line 2**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance? (Y/N)
VOC	BAAQMD S-11-301.3	Y	2.1 lbs/gal	BAAQMD S-11-501	P/W	Coating Records	Y
	40 CFR 60, Subpart WWW, Section 60.492(a)	Y	0.29 kg VOC/N	40 CFR 60, Subpart WWW, Section 60.495	P/Q	Coating Records	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y

	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test Report	Y
	BAAQMD Condition #9904 Part 22	Y	64.7 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-5 and S-51)	BAAQMD Condition #9904 Part 25	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	8 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII - M
Applicable Limits and Compliance Monitoring Requirements
S-53 Decoration Oven, Line 2**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency.	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 1	N	1400°F and inlet manifold pressure of -1.5 in of water except during bypass as allowed in Condition #9904, Part 7	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	C	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 11	P/A	Source Test Report	Y
	BAAQMD Condition #9904 Part 26	Y	83.31 tons/12 consecutive month period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, S-55-58 and S-60)	BAAQMD Condition #9904, Part 31	P/M	Emission Records	Y
	BAAQMD Condition #9904 Part 24		31.35 tons/12 consecutive month period prior to control due to ink usage.	BAAQMD Condition #9904, Part 28	P/M	Emission Records	Y

			excluding clean-up solvent (combined limit for S-13, S-27, S-53, S-58, S-58 and S-60)				
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII - N
Applicable Limits and Compliance Monitoring Requirements
S-52 Bottom Coater, Line 2
S-55 Bottom Coater at Basecoater #31, Line 3
S-57 Bottom Coater at Basecoater #32, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records	Y
	40 CFR 60, Subpart WW, Section 60.492(b)	Y	0.46 kg VOC/l	40 CFR 60, Subpart WW, Section 60.495	P/Q	Coating Records	Y
	BAAQMD Condition #9904 Part 25	Y	83.31 tons/12 consecutive month period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, and S-55-60 except 59)	BAAQMD Condition #9904, Part 31	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII - O
Applicable Limits and Compliance Monitoring Requirements
S-60 Printer #32 with Overvarnisher, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lbs/gal	BAAQMD 8-11-501	P/W	Coating Records	Y
	40 CFR 60, Subpart WW, Section 60.492(b)	Y	0.46 kg VOC/l	40 CFR 60, Subpart WW, Section 60.495	P/Q	Coating Records	Y
	BAAQMD Condition	Y	83.31 tons/12 consecutive month	BAAQMD Condition	P/M	Emission Records	Y

	#9904 Part 26		period prior to control due to overvarnish and bottomcoating usage, excluding clean-up solvent (combined limit for S-13, S-27, S-52, S-53, S-55-60 except S-59)	#9904, Part 31			
	BAAQMD Condition #9904 Part 27	Y	31.35 tons/12 consecutive month period prior to control due to ink usage, excluding clean-up solvent (combined limit for S-13, S-27, S-53, S-56, S-58 & S-60)	BAAQMD Condition #9904, Part 31	P/M	Emission Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII - P
Applicable Limits and Compliance Monitoring Requirements
S-81 Interior Coating Oven, Line 3

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.4	Y	3.5 lb/gal	BAAQMD 8-11-501	P/W	Coating Records ¹	Y
	BAAQMD 8-11-302	Y	90% (wt) or greater VOC destruction efficiency	BAAQMD 8-11-504	C	Temperature Chart Recorder	Y
	40 CFR 60, Subpart WWW, Section 60.492(b)	Y	0.89 kg VOC/l	40 CFR 60, Subpart WWW, Section 60.495	P/Q	Coating Records ¹	Y
	BAAQMD Condition #9904 Part 1	N	1400°F and inlet manifold pressure of -1.5 in. of water except during bypass as allowed in Condition #9904, Part 7.	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder and pressure monitor	Y
	BAAQMD Condition #9904 Part 1a	N	Oven damper closed position during normal operation	BAAQMD Condition #9904, Part 2	C	Monitor damper position	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904, Part 2	C	Temperature Chart Recorder	Y
	BAAQMD Condition #9904 Part 10	Y	95% (wt) or greater destruction efficiency	BAAQMD Condition #9904 Part 11	P/A	Source Test Report	Y
	BAAQMD Condition #9904 Part 18	Y	288.12 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-7, S-17, S-24, & S-61)	BAAQMD Condition #9904, Part 21	P/M	Emission Records	Y

HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y
-----	--------------------------------	---	--	---------------------------------	-----	------------------	---

Table VII - Q
Applicable Limits and Compliance Monitoring Requirements
S-62 Bottom Coater, Line 1

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-301.3	Y	2.1 lb/gal	BAAQMD 8-11-501	P/W	Coating Records	Y
	40 CFR 60, Subpart WWW, Section 60.492(a)	Y	0.41 kg VOC/l	40 CFR 60, Subpart WWW, Section 60.495	P/Q	Coating Records	Y
	BAAQMD Condition #9904 Part 14	Y	47.37 tons/12 consecutive month period prior to control, excluding clean-up solvent (combined limit for S-4, S-12, & S-62)	BAAQMD Condition #9904 Part 17	P/M	Emission Records	Y
	BAAQMD Condition #14836 Part 1	Y	4.45 tons/12 consecutive month period prior to control, excluding clean-up solvent for bottomcoating	BAAQMD Condition #14836 Part 4	P/M	Coating Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Table VII-R
Applicable Limits and Compliance Monitoring Requirements
S-63 Interior Coating Storage Tank
S-64 Interior Coating Storage Tank

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD Condition #18728 Part 1		275,000 gallons/12 consecutive month period	BAAQMD Condition #18728, Part 3	P/M	Usage Records	Y
	BAAQMD Condition #18728 Part 2		Use only water reducible liner coating	BAAQMD Condition #18728, Part 3	C	VOC records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII-S
Applicable Limits and Compliance Monitoring Requirements
S-65 Emergency Standby Generator
S-66 Emergency Standby Generator**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
FP	BAAQMD 6-310	Y	0.15 gr/dscf	N	N	N	Y
FP	BAAQMD 6-310	Y	No. 2 on Ringelmann Chart for 3 minutes in any hour	N	N	N	Y
FP	BAAQMD 6-310	Y	0.15 gr/dscf	N	N	N	Y
SO ₂	BAAQMD 9-1-301	Y	Ground level concentration of 0.5 ppm continuously for 3 consecutive minutes, or 0.25 ppm averaged over 60 consecutive minutes, or 0.05ppm averaged over 24 hours				Y
SO ₂	BAAQMD 9-1-302	Y	30 ppm in the gas stream	N	N	N	Y
NO _x	BAAQMD 9-8-301.2	Y	140 ppmv @ 15% O ₂ , dry		P/A		Y
	BAAQMD 9-8-302.1	Y	140 ppmv @ 15% O ₂ , dry		P/A		Y
CO	BAAQMD 9-8-301.3	Y	2000 ppmv @ 15% O ₂ , dry		P/A		Y
	BAAQMD 9-8-302.3	Y	2000 ppmv @ 15% O ₂ , dry		P/A		Y
PM, NO _x , CO, POC	BAAQMD Condition #18729 Part 2	Y	100 hrs/yr for reliability-related activities	BAAQMD Condition #18729, Part 4 & 5	P/M	Totalizer counter and records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII - T
Applicable Limits and Compliance Monitoring Requirements
S-67 Video Jet Printer**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-305	Y	2.1 lb/gal	BAAQMD 8-11-501	P/M	Coating Records	Y
	40 CFR 60, Subpart WW	Y	0.48 kg VOC/l	40 CFR 60, Subpart WW	P/Q	Coating Records	Y

	Section 60.492(a)			Section 60.495			
	BAAQMD Condition #18544 Part 1	Y	5 gallons / 12 consecutive month period	BAAQMD Condition #18544, Part 3	P/M	Records	Y
	BAAQMD Condition #18544 Part 2	Y	1 gallon / 12 consecutive month period	BAAQMD Condition #18544, Part 3	P/M	Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII - U
Applicable Limits and Compliance Monitoring Requirements
S-68 Ink Dot System, Line 3**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-305	Y	2.1 lb/gal	BAAQMD 8-11-501	P/M	Coating Records	Y
	40 CFR 60, Subpart WW, Section 60.492(b)	Y	0.48 kg VOC/l	40 CFR 60, Subpart WW, Section 60.495	P/Q	Coating Records	Y
	BAAQMD Condition #18645 Part 1	Y	75 gallons / 12 consecutive month period	BAAQMD Condition #18645, Part 3	P/M	Records	Y
	BAAQMD Condition #18645 Part 2	Y	15 gallons / 12 consecutive month period	BAAQMD Condition #18645, Part 3	P/M	Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	9 tons/yr of any single HAP or 23 tons/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

**Table VII - V
Applicable Limits and Compliance Monitoring Requirements
S-68 Ink Dot System, Line 1 & 2**

Pollutant	Emission Limit Citation	FE Y/N	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type	Continuous Compliance ? (Y/N)
VOC	BAAQMD 8-11-305	Y	2.1 lb/gal	BAAQMD 8-11-501	P/M	Coating Records	Y
	40 CFR 60, Subpart WW, Section 60.492(b)	Y	0.48 kg VOC/l	40 CFR 60, Subpart WW, Section 60.495	P/Q	Coating Records	Y
	BAAQMD Condition #20955 Part 1	Y	60 gallons / 12 consecutive month period	BAAQMD Condition #20955, Part 3	P/M	Records	Y

	BAAQMD Condition #20955 Part 2	Y	14 gallon / 12 consecutive month period	BAAQMD Condition #20955, Part 3	P/M	Records	Y
HAP	BAAQMD Condition #21993 Part 1	Y	8 ton/yr of any single HAP or 23 ton/yr of any combination of HAPs	BAAQMD Condition #21993, Part 2	P/M	Emission Records	Y

Footnote 1: All coatings received are formulated to be less than the limits set forth in BAAQMD 8-11-301.