BAY AREA AIR QUALITY MANAGEMENT DISTRICT Best Available Control Technology (BACT) Guideline

Source Category

Source:	Spray Booth - Couling of Fun wood I aneung &	Revision:	1
		Document #:	161.7.2
Class:	≥50 lb/day Emissions (Uncontrolled)	Date:	09/06/91

Determination

POLLUTANT	BACT	TYPICAL TECHNOLOGY
1 0220 11111	1. Technologically Feasible/ Cost Effective 2. Achieved in Practice	
РОС	1. Coating w/VOC content and transfer efficiency greater than that required by Reg. 8, Rule 23, and emissions controlled to overall capture/destruction efficiency ≥90% ^a 2. Coating w/VOC content and transfer efficiency complying w/Reg. 8, Rule 23, and emissions controlled to overall capture/destruction efficiency ≥90% ^a	 Collection System Vented to Carbon Adsorber or Afterburner^a Collection System Vented to Carbon Adsorber or Afterburner^a
NOx	1. <i>n/a</i> 2. <i>n/a</i>	1. <i>n/a</i> 2. <i>n/a</i>
SO_2	1. n/a 2. n/a	1. n/a 2. n/a
СО	1. n/a 2. n/a	1. n/a 2. n/a
PM ₁₀	1. n/d 2. n/s	1. n/d 2. Dry Filters or Waterwash, Properly Maintained ^a
NPOC	1. Coating w/ solvent content less than and transfer efficiency greater than that required by Reg. 8, Rule 23, and emissions controlled to overall capture/destruction efficiency ≥90% ^a 2. Coating w/ solvent content and transfer efficiency complying w/ Reg. 8, Rule 23, and emissions controlled to overall capture/ destruction efficiency ≥90% ^a	 Collection System Vented to Carbon Adsorber^a Collection System Vented to Carbon Adsorber^a