BAY AREA AIR QUALITY MANAGEMENT DISTRICT Best Available Control Technology (BACT) Guideline

Source Category

Source:	(dry commodities such as cement, gypsum, line, soda	Revision:	1
		Document #:	26.1
Class:	All	Date:	09/06/91

Determination

POLLUTANT	BACT 1. Technologically Feasible/ Cost Effective 2. Achieved in Practice	TYPICAL TECHNOLOGY
POC	1. n/a 2. n/a	1. n/a 2. n/a
NOx	 Shore utility power n/d 	1. Electric Power 2. n/d
SO ₂	 Shore utility power n/d 	1. Electric Power 2. n/d
СО	1. n/a 2. n/a	1. n/a 2. n/a
PM ₁₀	 Enclosed conveyor system and ship hold vented to baghouse w/ ≤0.0013 gr/dscf; shore containers and transfer points are enclosed and vented to baghouse w/ <0.0013 gr/dscf^{a,b} Enclosed conveyor system and ship hold vented to baghouse w/ <0.004 gr/dscf; shore containers and transfer points are enclosed and vented to baghouse w/ <0.004 gr/dscf^{a,c} 	 BAAQMD Approved Design and Operation^d BAAQMD Approved Design and Operation^d
NPOC	1. n/a 2. n/a	1. n/a 2. n/a

References

b. BAAQMD A #4577 c. CARB/CAPCOA Cleaninghouse d. BAAQMD