## BAY AREA AIR QUALITY MANAGEMENT DISTRICT Best Available Control Technology (BACT) Guideline

## Source Category

	(dry commodities such as cement, gypsum, lime, soda	Revision:	1
Source:		Document #:	29.1
Class:	All	Date:	09/06/91

## Determination

POLLUTANT	BACT 1. Technologically Feasible/ Cost Effective 2. Achieved in Practice	TYPICAL TECHNOLOGY
POC	1. n/a 2. n/a	1. n/a 2. n/a
NOx	1. <i>n/a</i> 2. <i>n/a</i>	1. n/a 2. n/a
$SO_2$	1. <i>n/a</i> 2. <i>n/a</i>	1. n/a 2. n/a
СО	1. n/a 2. n/a	1. n/a 2. n/a
PM <sub>10</sub>	<ol> <li>Enclosed storage vented to a baghouse w/ ≤0.0013 gr/dscf<sup>b</sup></li> <li>Enclosed storage vented to a baghouse w/ ≤0.01 gr/dscf<sup>d</sup></li> </ol>	<ol> <li>BAAQMD Approved Design and Operation<sup>c</sup></li> <li>BAAQMD Approved Design and Operation<sup>c</sup></li> </ol>
NPOC	1. <i>n/a</i> 2. <i>n/a</i>	1. n/a 2. n/a

## References

- b. BAAQMD A #4577 & #4770 c. BAAQMD d. CARB/CAPCOA Clearinghouse