SECTION 2
TITLE V SEMI-ANNUAL REPORT

Section I.F. of the Title V Permit requires the facility to submit semi-annual reports. All instances of non-compliance shall be clearly identified in these reports. Any deviations that occurred during the September 1, 2015 through February 29, 2016 reporting period is included in the table below.

2.1 Title V Monitoring Report Deviations

Source	Permit ID	Description	Deviation Period		Cause of Deviation	Corrective Actions Taken To Remedy or Mitigate Deviation Situation
			Start	End		
			Date/Time	Date/Time		
S-1 Cupola	40 CFR 63.7743(b)	Operating limit for capture system	9/1/15 10:32 (intermittent)	12/2/15 13:07 (intermittent)	Operational parameters; draft pressure 3-hour average dropped below 0.2 inches of water column vacuum for approximately 96.18 hours	On December 4, 2015, maintenance personnel discovered an air leak in the recuperator and repaired the leak the same day.

On November 2, 2015, the BAAQMD issued Notice of Violation (NOV) #A52537 (Failure to Meet Permit Condition) for an incident that occurred during the previous reporting period. Please refer to the March 1, 2015 to August 31, 2015 Semi-Annual Report for further details. On November 6, 2015, AB&I submitted a 10-Day Corrective Action Report to the BAAQMD for NOV #A52537.

The Semi-Annual Monitoring Verification Report is included as Attachment 2-1.

Attachment 2-1
Semi-Annual Monitoring Verification Report

Semi-Annual Monitoring Verification Report
Reporting Period: September 1, 2015 through February 29, 2016
AB&I Foundry

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements Facility (Except S-51)						
Applicable Requirement	**Regulation Title or Description of Requirement**	**Limit**	**Monitoring Citation**	**Monitoring & Frequency**	**Reporting**	**Compliance (Y / N)**
NESHAP 40 CFR Part 63, Subpart EEEEE	**National Emission Standards for Hazardous Air Pollutants for Iron and Steel Foundries (02/07/2008)**					
63.7681	Am I subject to this subpart?					Y
63.7682	What parts of this foundry does this subpart cover?					Y
63.7683(a)	Existing source compliance deadline (April 23, 2007)					Y
63.7683(b)	Existing source compliance deadline for work practice standards (April 22, 2005)					Y
63.7683(f)	Notification and Schedule requirements (63.7750)					Y
63.7700	What work practice standards must I meet?					Y
63.7710(a)	Operate and maintain foundry consistent with good air pollution control practices					Y
63.7720(a)	General compliance requirements, exemption startup, shutdown, malfunction					Y
63.7720(c)	Develop a written startup, shutdown, and malfunction plan					Y
63.7730(b)	Initial demonstration of compliance with work practice standards and operation and maintenance requirements within 30 days of April 22, 2005					Y
63.7731(b)	Subsequent performance tests for fugitive emissions from building or structures	Opacity level ≤ 20% (6 minute average) 63.7690(a)(7)	63.7731(b)	Visible Emissions (M9) P/6 months	Once every six months	Y
63.7735	Initial compliance demonstration with work practice standards					Y
63.7736	Initial compliance demonstration with operation and maintenance requirements					Y
63.7743(a)(7)	Continuous compliance demonstration for fugitive emissions from building or structures	Opacity level ≤ 20% (6 minute average) 63.7690(a)(7)	63.7731(b)	Visible Emissions (M9) P/6 months	Once every six months	Y
63.7745(a)(1)	Continuous compliance demonstration – operation and maintenance requirements			Inspections, corrective action, record keeping P/M	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
Facility (Except S-51)

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.7745(a)(1)	Continuous compliance demonstration – operation and maintenance requirements			Inspections, corrective action, record keeping P/M	Once every six months	Y
63.7745(a)(1)	Continuous compliance demonstration – operation and maintenance requirements			Inspections, corrective action, record keeping P/M	Once every six months	Y
63.7746(b)	Startup, shutdown, malfunction deviations are not violations					Y
63.7750	Notification requirements					Y
63.7751	Reporting requirements					Y
63.7752	Recordkeeping requirements					Y
63.7753	Recordkeeping requirements (5 years)					Y
63.7760	Table 1: Applicability of General Provisions (Subpart A)					Y
63.7761	Delegation					Y
63.7765	Definitions					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 6, Rule 1	**Particulate Matter (12/05/07)**					
6-1-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y
			BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y
6-1-305	Visible Particles					Y
6-1-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y
			63.7731(a); 63.7743(a)(12); BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y
6-1-311	General Operations	FILTERABLE PARTICULATE $4.10P^{0.67}$ lb/hr where P is process weight, ton/hr	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
			63.7731(a); 63.7743(a)(12); BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y
6-1-401	Appearance of Emissions					Y
6-1-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
SIP Regulation 6	**Particulate Matter and Visible Emissions (09/04/98)**					
6-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y
			BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y
6-305	Visible Particles					Y
6-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y
			63.7731(a); 63.7743(a)(12); BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
6-311	General Operations	FILTERABLE PARTICULATE 4.10P0.67 lb/hr. where P is process weight, ton/hr	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y
			63.7731(a); 63.7743(a)(12); BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y
6-401	Appearance of Emissions					Y
6-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
BAAQMD Regulation 8, Rule 2	**Organic Compounds: Miscellaneous Operations (7/20/2005)**					
8-2-301	Miscellaneous Operations	VOC 15 lb/day and 300ppmd	BAAQMD Condition #9351, Part 11	Source Test P/Every 5 years	Every 5 years	Y
8-2-601	Determination of Compliance					Y
BAAQMD Regulation 9, Rule 1	**Inorganic Gaseous Pollutants: Sulfur Dioxide (3/15/1995)**					
9-1-304	Fuel Burning (Liquid and Solid Fuels)	Sulfur content of solid fuel limited to ensure $SO2 \leq 300$ ppmd	BAAQMD Condition #9351, Part 4	Fuel certification; Source test if >1.0% S P/E	Once every six months	Y
			BAAQMD Condition #9351, Part 11	Source Test P/Every 5 years	Every 5 years	Y
9-1-601	Sampling and Analysis of Gas Streams					Y
9-1-602	Sulfur Content of Fuels					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
9-1-603	Averaging Times					Y
BAAQMD Regulation 11, Rule 1	**Hazardous Pollutants/ Lead (3/17/82)**					
11-1-301	Daily Limitation	LEAD 15 lb/day	BAAQMD Condition #9351, Part 11	Source Test P/Every 5 years	Every 5 years	Y
11-1-302	Ground Level Concentration Limit Without Background	LEAD ≤1.0 ug/m^3		N		Y
11-1-604	Determination of Daily Emission Limits					Y
NESHAP 40 CFR Part 63, Subpart EEEEE	**National Emission Standards for Hazardous Air Pollutants for Iron and Steel Foundries (02/07/2008)**					
63.7681	Am I subject to this subpart?					Y
63.7682	What parts of this foundry does this subpart cover?					Y
63.7683(a)	Existing source compliance deadline (April 23, 2007)					Y
63.7690(a)(2)	Emissions Limitations for cupola at existing iron and steel foundry	PM 0.006 gr/dscf; or 0.10 lb PM/ton metal charged; or 0.0005 gr/dscf of total metal HAP; or 0.008 lb of total metal HAP/ton metal charged	63.7740(b)	Bag leak detector C	Once every six months	Y
			63.7740 (b)	Baghouse inspection P/varies		Y
			63.7731(a); 63.7743(a)(12)	Source Test P/Every 5 years		Y
63.7690(a)(8)	Emissions Limitations for cupola at existing iron and steel foundry	VOHAP ≤ 20 ppmv @ 10% O2	63.7740(a)	Temperature monitor C	Once every six months	Y
			63.7731(a); 63.7743(a)(12)	Source Test P/Every 5 years	Every 5 years	Y
63.7690(b)(1)	Install, operate, and maintain a capture and collection system for VOHAP					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.7690(b)(3)	Temperature limit for combustion device applied to emissions from a cupola	Afterburner combustion zone temperature ≥ 1300°F (15-min average, not including 15 min transition from off-blast to on-blast)	63.7740(a)	Temperature monitor C	Once every six months	Y
63.7700	What work practice standards must I meet?					Y
63.7710(a)	Operate and maintain foundry consistent with good air pollution control practices					Y
63.7710(b)	Operation and maintenance plan for each capture and collection system and control device					Y
63.7710(b)(1)	Monthly inspections of abatement equipment					Y
63.7710(b)(2)	Determination of operating limit parameters for each capture system for VOHAP					Y
63.7710(b)(3)	Preventative maintenance plan for each control device					Y
63.7710(b)(4)	Monitoring plan for each bag leak detection system					Y
63.7710(b)(5)	Corrective action plan for each baghouse	Initiate corrective action to determine the cause of the alarm within 1 hour of the alarm, initiate corrective action to correct the cause of the problem within 24 hours	63.7745(a)(4)	Record keeping P/E	Once every six months	Y
63.7720(a)	General compliance requirements, exemption startup, shutdown, malfunction					Y
63.7720(c)	Develop a written startup, shutdown, and malfunction plan					Y
63.7730(a)	Initial performance test within 180 days of April 23, 2007	PM or total metal HAP: 63.7690(a)(2); and VOHAP: 63.7690(a)(8)	40 CFR Part 63.7(a)(2)	Initial performance test P/E	Initial	Y
63.7730(b)	Initial demonstration of compliance with work practice standards and operation and maintenance requirements within 30 days of April 22, 2005					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.7731(a)	Subsequent performance tests for PM or total metal HAP, VOHAP	PM or total metal HAP: 63.7690(a)(2); and VOHAP: 63.7690(a)(8)	63.7731(a)	Source Test P/Every 5 years	Every 5 years	Y
63.7731(b)	Subsequent performance tests for fugitive emissions from building or structures	Opacity level ≤ 20% (6 minute average) 63.7690(a)(7)	63.7731(b)	Visible Emissions (M9) P/6 months	Once every six months	Y
63.7732	Test Methods					Y
63.7733	Procedures for establishing operating limits					Y
63.7734(a)(2)	Initial compliance demonstration for existing cupola					Y
63.7735	Initial compliance demonstration with work practice standards					Y
63.7736	Initial compliance demonstration with operation and maintenance requirements					Y
63.7740(a)	Monitoring requirements – for 63.7690(b)(1) VOHAP limit: install, operate and maintain a CPMS					Y
63.7740(b)	Monitoring requirements –for baghouse, use bag leak detection system					Y
63.7740(c)(1)	Monitoring requirements – Baghouse inspection requirements	Pressure drop Normal operating range	63.7740(c)(1)	Pressure drop monitoring P/D	Once every six months	Y
63.7740(c)(2)	Monitoring requirements – Baghouse inspection requirements	Check dust removal from hoppers	63.7740(c)(2)	Visual inspection P/W	Once every six months	Y
63.7740(c)(3)	Monitoring requirements – Baghouse inspection requirements	Adequate compressed air supply for pulse-jet baghouses	63.7740(c)(3)	Inspection P/D	Once every six months	Y
63.7740(c)(4)	Monitoring requirements – Baghouse inspection requirements	Monitor cleaning cycles	63.7740(c)(4)	Inspection P/A	Once every six months	Y
63.7740(c)(5)	Monitoring requirements – Baghouse inspection requirements	Check bag cleaning mechanisms	63.7740(c)(5)	Visual inspection P/M	Once every six months	Y
63.7740(c)(7)	Monitoring requirements – Baghouse inspection requirements	Check physical integrity of baghouses interior	63.7740(c)(7)	Visual inspection P/Q	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.7740(c)(8)	Monitoring requirements – Baghouse inspection requirements	Inspect fans for wear, material buildup, corrosion	63.7740(c)(8)	Visual inspection P/Q	Once every six months	Y
63.7740(e)	Monitoring requirement - Combustion device	Monitor 15-minute average combustion zone temperature using a CPMS	63.7740(e)	Temperature monitor C	Once every six months	Y
63.7741(a)(2)	Install, operate, maintain each CPMS for each capture system – pressure measurement device		63.7741(a)(2)	Pressure drop monitor P/M	Once every six months	Y
63.7741(a)(3)	Record results of each inspection, calibration, validation check		63.7741(a)(3)	Record keeping P/E	Once every six months	Y
63.7741(b) (1-5)	Install, operate, maintain a bag leak detection system					Y
63.7741(d) (1,4,6,7,8)	Install, operate, maintain each CPMS to measure and record the combustion zone temperature for each combustion device		63.7741(d)(1,4, 6,7,8)	Visual inspection P/M	Once every six months	Y
63.7741(f) (1,2,3)	CPMS requirements					Y
63.7742	Monitoring and collection of data to demonstrate continuous compliance (excluding malfunctions, associated repairs, required quality assurance or control activities)					Y
63.7743(a)(2)	Continuous compliance demonstration for existing cupola	Maintaining the average limits: PM 0.006 gr/dscf; or 0.10 lb PM/ton metal charged; or 0.0005 gr/dscf of total metal HAP; or 0.008 lb of total metal HAP/ton metal charged	63.7740(b)	Bag leak detector C	Once every six months	Y
			63.7740 (c)	Baghouse inspection P/varies		Y
			63.7743(a)(12)	Source Test P/Every 5 years		Y
63.7743(a)(7)	Continuous compliance demonstration for fugitive emissions from building or structures	Opacity level ≤ 20% (6 minute average) 63.7690(a)(7)	63.7731(b)	Visible Emissions (M9) P/6 months	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.7743(a)(8)	Continuous compliance demonstration for existing cupola	Maintaining the average limits: VOHAP ≤ 20 ppmv @ 10% O2	63.7740(a)	Temperature monitor C	Once every six months	Y
			63.7743(a)(12)	Source Test P/Every 5 years	Every 5 years	Y
63.7743(a)(12)	Continuous compliance demonstration – subsequent performance tests for PM or total metal HAP, VOHAP	PM or total metal HAP: 63.7690(a)(2); and VOHAP: 63.7690(a)(8)	63.7731(a)	Source Test P/Every 5 years	Every 5 years	Y
63.7743(b)	Continuous compliance demonstration – capture system	0.2 inches of water column vacuum (O&M Plan)		Static pressure monitor for flow detection C	Once every six months	N – Refer to Title V Monitoring Deviation Report included in Section 2 of the Combined Semi-Annual Report
63.7743(c)	Continuous compliance demonstration - baghouse			Inspections P/varies	Once every six months	Y
63.7743(e)	Continuous compliance demonstration – combustion device			Temperature monitor C	Once every six months	Y
63.7745(a)(1)	Continuous compliance demonstration – operation and maintenance requirements			Inspections, corrective action, record keeping P/M	Once every six months	Y
63.7745(a)(2)	Continuous compliance demonstration – Preventative maintenance			Record keeping P/E	Once every six months	Y
63.7745(a)(3)	Continuous compliance demonstration – bag leak detection system			Record keeping P/E	Once every six months	Y
63.7745(a)(4)	Continuous compliance demonstration – baghouse corrective action			Record keeping P/E	Once every six months	Y
63.7745(b)	Maintain operation and maintenance plan onsite					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.7746(a)	Deviations	Report deviations from emissions limitations, work practice standards, and operation and maintenance requirements, including startup, shutdown, malfunction	63.7746(a)	Record keeping P/E	Once every six months	Y
63.7746(b)	Startup, shutdown, malfunction deviations are not violations					Y
63.7750	Notification requirements					Y
63.7751	Reporting requirements					Y
63.7752	Recordkeeping requirements					Y
63.7753	Recordkeeping requirements (5 years)					Y
63.7760	Table 1: Applicability of General Provisions (Subpart A)					Y
63.7761	Delegation					Y
63.7765	Definitions					Y
BAAQMD Condition #9351						
Part 1	Minimum A-20, A-22 Afterburners combustion zone Temperature (basis: 40 CFR 63.7690 (b)(3))	Afterburner combustion zone temperature ≥ 1300°F (15-min average, not including 15 min transition from off-blast to on-blast)	63.7740(a); BAAQMD Condition #9351, Part 2	Temperature monitor C	Once every six months	Y
Part 2	Continuous temperature monitor and recorder requirement (basis: cumulative increase, Regulation 1-521)					Y
Part 3	Record keeping requirement - temperature (basis: cumulative increase, BAAQMD Regulation 2-6-501)					Y
Part 4	Coke sulfur content limit and procedure to raise limit (basis: BAAQMD Regulation 9-1- 302, BAAQMD Regulation 2-6-501)	Coke sulfur content limit 1.0% by weight	BAAQMD Condition #9351, Part 4	Fuel certification; Source test if > 1.0% S P/E	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
Part 5	Ratio of total metal to total coke charged into S-1 limit	Total Metal (includes scrap iron, steel, returns, and pig iron) to Coke ≥ 10:1	BAAQMD Condition # 9351, Part 8	Record Keeping P/D	Daily, Monthly, Annual Average	Y
Part 6	Daily total metal throughput limit	Total Metal ≤ 513 tons/day	BAAQMD Condition # 9351, Part 8	Record Keeping P/D	Daily, Monthly, Annual Average	Y
Part 7	Gray iron throughput	Gray iron throughput ≤ 172,800 ton/any consecutive 12-months	BAAQMD Condition #9351, Part 8	Record keeping P/M	Once every six months	Y
Part 8	Record keeping requirement - Gray iron throughput (basis: Regulation 2-1-403					Y
Part 9	Limit on firing rate of the A-20 Afterburner (basis: cumulative increase)	Firing rate of the A-20 Afterburner ≤ 8 MMBtu/hr	BAAQMD Condition #9351, Part 8	Record keeping P/M	Once every six months	Y
Part 10	Limit on firing rate of the A-22 Afterburner (basis: cumulative increase)	Firing rate of the A-22 Afterburner ≤ 8 MMBtu/hr	BAAQMD Condition #9351, Part 8	Record keeping P/M	Once every six months	Y
Part 11	Source test for PM, opacity, CO, VOC, SO2, NOx, lead every 5 years					Y
CAM Condition #25039						
Part 14a	Definition of exceedance: OPACITY Ringelmann 1.0 < 3 min/hr(Basis: 40 CFR Part 64.6(c)(2))					Y
Part 14b	Definitions of excursion: i) 10 milligrams PM/actual cubic meter for 15 min; or ii) Pressure drop less than 2 inches or greater than 10 inches water column (Basis: 40 CFR Part 64.6(c)(2))					Y
Part 15	Bag leak detector requirement (Basis: 40 CFR Part 64.6(c)(1); 40 CFR Part 64.6(c)(3))					Y
Part 16	Bag leak detector alarm requirement (Basis: 40 CFR Part 64.6(c)(1))					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-1 – Cupola abated by A-20, A-22 Afterburner and A-19 Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
Part 17	Indicator range: PM<10 milligrams/actual cubic meter (Basis: 40 CFR Part 64.3(a)(2)					Y
Part 18	Visual inspection and testing requirement for bag leak detection sensors (Basis: 40 CFR Part 64.3(b)(3) and (b)(2))					Y
Part 19	Pressure gauge installation requirement (Basis: 40 CFR Part 64.6(c)(1))					Y
Part 20	Indicator range for pressure gauges: 2 to 10 inches of water column (40 CFR Part 64.3(a)(2))					Y
Part 21	Pressure gauge reading - Daily (Basis: 40 CFR Part 64.6(c)(3); 40 CFR Part 64.3(b)(4)(iii))					Y
Part 22	Pressure gauge calibration – quarterly(Basis: 40 CFR Part 64.3(b)(3) and (b)(2))					Y
Part 23	Procedures for excursion (Basis: 40 CFR Parts 64.6(c)(3), 64.7(d)(2), 64.8)					Y
Part 24	Method 9 observation requirement after 2 or more excursions at the same abatement device occur within 2 weeks (Basis: 40 CFR Part 64.6(c)(3); 40 CFR Part 64.3(b)(4)(iii))					Y
Part 25a	Reporting requirement – excursions, exceedances (Basis: 40 CFR Part 64.6(c)(3) and 40 CFR Part 64.9(a)(2))					Y
Part 25b	Reporting requirement – monitor downtime incidents(Basis: 40 CFR Part 64.6(c)(3) and 40 CFR Part 64.9(a)(2))					Y
Part 26	Inspection of baghouse and monitoring system (Basis: 40 CFR Part 64.6(c)(1)(iii))					Y
Part 27	Source test for PM and opacity – every 5 years (Basis: Regulation 2-1-403)					Y
Part 28	Recordkeeping requirements (Basis: Regulation 2-6-501 Recordkeeping)					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 6, Rule 1	**Particulate Matter (12/05/07)**					
6-1-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	40 CFR 63.7740(b); CAM Condition #25039, Part 15 (A-21)	Bag leak detector C	Once every six months	Y
			CAM Condition #25039 Part 21 (A-21)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039 Part 2 (A-14, A-18)	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5 (A-14, A-18)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11 (A-14, A-18) and Part 27 (A-21)	Source Test P/Every 5 years	Every 5 years	Y
6-1-305	Visible Particles					Y
6-1-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	40 CFR 63.7740(b); CAM Condition #25039, Part 15 (A-21)	Bag leak detector C	Once every six months	Y
			CAM Condition #25039 Part 21 (A-21)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039 Part 2 (A-14, A-18)	Visible Emissions (M22) P/W	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
			CAM Condition #25039 Part 5 (A-14, A-18)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11 (A-14, A-18) and Part 27 (A-21)	Source Test P/every 5 years	Every 5 years	Y
6-1-311	General Operations	FILTERABLE PARTICULATE $4.10P^{0.67}$ lb/hr where P is process weight, ton/hr	40 CFR 63.7740(b); CAM Condition #25039, Part 15 (A-21)	Bag leak detector C	Once every six months	Y
			CAM Condition #25039 Part 21 (A-21)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039 Part 2 (A-14, A-18)	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5 (A-14, A-18)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11 (A-14, A-18) and Part 27 (A-21)	Source Test P/every 5 years	Every 5 years	Y
6-1-401	Appearance of Emissions					Y
6-1-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
SIP Regulation 6	**Particulate Matter and Visible Emissions (09/04/98)**					
6-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	40 CFR 63.7740(b); CAM Condition #25039, Part 15 (A-21)	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21 (A-21)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 2, (A-14, A-18)	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5 (A-14, A-18)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11 (A-14, A-18) and Part 27 (A-21)	Source Test P/every 5 years	Once every six months	Y
6-305	Visible Particles					Y
6-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	40 CFR 63.7740(b); CAM Condition #25039, Part 15 (A-21)	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21 (A-21)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039 Part 2 (A-14, A-18)	Visible Emissions (M22) P/W	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
			CAM Condition #25039 Part 5 (A-14, A-18)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11 (A-14, A-18) and Part 27 (A-21)	Source Test P/every 5 years	Once every six months	Y
6-311	General Operations	FILTERABLE PARTICULATE 4.10P0.67 lb/hr. where P is process weight, ton/hr	40 CFR 63.7740(b); CAM Condition #25039, Part 15 (A-21)	Bag leak detector C	Once every six months	Y
			CAM Condition #25039 Part 21 (A-21)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039 Part 2 (A-14, A-18)	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5 (A-14, A-18)	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11 (A-14, A-18) and Part 27 (A-21)	Source Test P/every 5 years	Once every six months	Y
6-401	Appearance of Emissions					Y
6-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
BAAQMD Regulation 8, Rule 2	**Organic Compounds: Miscellaneous Operations (7/20/2005)**					

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
8-2-301	Miscellaneous Operations	VOC 15 lb/day and 300ppmd	BAAQMD Condition #23650, Part 7	Source Test P/Every 5 years	Every 5 years	Y
8-2-601	Determination of Compliance					Y
NESHAP 40 CFR Part 63, Subpart EEEEE	**National Emission Standards for Hazardous Air Pollutants for Iron and Steel Foundries (02/07/2008)**					
63.7681	Am I subject to this subpart?					Y
63.7682	What parts of my foundry does this subpart cover?					Y
63.7683(a)	Existing source compliance deadline (April 23, 2007)					Y
63.7683(b)	Existing source compliance deadline for work practice standards (April 22, 2005)					Y
63.7683(f)	Notification and Schedule requirements (63.7750)					Y
63.7690(a)(5)	Emissions Limitations for each pouring station at existing iron and steel foundry	PM 0.010 gr/dscf; or 0.0008 gr/dscf of total metal HAP	63.7740(b)	Bag leak detector C	Once every six months	Y
			63.7740(b)	Baghouse inspection P/varies		Y
			63.7731(a); 63.7743(a)(12)	Source Test P/Every 5 years		Y
63.7710(a)	Operate and maintain foundry consistent with good air pollution control practices					Y
63.7710(b)	Operation and maintenance plan for each capture and collection system and control device					Y
63.7710(b)(1)	Monthly inspections of abatement equipment					Y
63.7710(b)(3)	Preventative maintenance plan for each control device					Y
63.7710(b)(4)	Monitoring plan for each bag leak detection system					Y
63.7710(b)(5)	Corrective action plan for each baghouse	Initiate corrective action to determine the cause of the alarm within 1 hour of the alarm, initiate corrective action to correct the cause of the problem within 24 hours	63.7745(a)(4)	Record keeping P/E	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.7710(b)(6)	Procedures for providing an ignition source to mold vents of sand mold systems					Y
63.7720(a)	General compliance requirements, exemption startup, shutdown, malfunction					Y
63.7720(c)	Develop a written startup, shutdown, and malfunction plan					Y
63.7730(a)	Initial performance test within 180 days of April 23, 2007	PM or total metal HAP: 63.7690(a)(5)	40 CFR Part 63.7(a)(2)	Initial performance test P/E	Initial	Y
63.7730(b)	Initial demonstration of compliance with work practice standards and operation and maintenance requirements within 30 days of April 22, 2005					Y
63.7731(a)	Subsequent performance tests for PM	PM or total metal HAP: 63.7690(a)(5)	63.7731(a)	Source Test P/Every 5 years	Every 5 years	Y
63.7732	Test Methods					Y
63.7733	Procedures for establishing operating limits					Y
63.7734(a)(2)	Initial compliance demonstration for existing cupola					Y
63.7735	Initial compliance demonstration with work practice standards					Y
63.7736	Initial compliance demonstration with operation and maintenance requirements					Y
63.7740(b)	Monitoring requirements –for baghouse, use bag leak detection system					Y
63.7740(c)(1)	Monitoring requirements – Baghouse inspection requirements	Pressure drop Normal operating range	63.7740(c)(1)	Pressure drop monitoring P/D	Once every six months	Y
63.7740(c)(2)	Monitoring requirements – Baghouse inspection requirements	Check dust removal from hoppers	63.7740(c)(2)	Visual inspection P/W	Once every six months	Y
63.7740(c)(3)	Monitoring requirements – Baghouse inspection requirements	Adequate compressed air supply for pulse-jet baghouses	63.7740(c)(3)	Inspection P/D	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.7740(c)(4)	Monitoring requirements – Baghouse inspection requirements	Monitor cleaning cycles	63.7740(c)(4)	Inspection P/A	Once every six months	Y
63.7740(c)(5)	Monitoring requirements – Baghouse inspection requirements	Check bag cleaning mechanisms	63.7740(c)(5)	Visual inspection P/M	Once every six months	Y
63.7740(c)(7)	Monitoring requirements – Baghouse inspection requirements	Check physical integrity of baghouses interior	63.7740(c)(7)	Visual inspection P/Q	Once every six months	Y
63.7740(c)(8)	Monitoring requirements – Baghouse inspection requirements	Inspect fans for wear, material buildup, corrosion	63.7740(c)(8)	Visual inspection P/Q	Once every six months	Y
63.7741(b) (1-5)	Install, operate, maintain a bag leak detection system					Y
63.7741(f)(1,2,3)	CPMS requirements					Y
63.7742	Monitoring and collection of data to demonstrate continuous compliance (excluding malfunctions, associated repairs, required quality assurance or control activities)					Y
63.7743(a)(5)	Continuous compliance demonstration for existing pouring station	Maintaining the average limits: PM 0.010 gr/dscf; or 0.0008 gr/dscf of total metal HAP	63.7740(b)	Bag leak detector C	Once every six months	Y
			63.7740 (c)	Baghouse inspection P/varies		Y
			63.7731(a); 63.7743(a)(12)	Source Test P/Every 5 years		Y
63.7743(a)(12)	Continuous compliance demonstration - subsequent performance tests for PM	PM or total metal HAP: 63.7690(a)(5)	63.7731(a)	Source Test P/Every 5 years	Every 5 years	Y
63.7743(c)	Continuous compliance demonstration - baghouse			Inspections P/varies	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.7745(a)(1)	Continuous compliance demonstration – operation and maintenance requirements			Inspections, corrective action, record keeping P/M	Once every six months	Y
63.7745	Igniting gasses from mold vents		63.7710(b)(6)	P/E		Y
63.7745(a)(2)	Continuous compliance demonstration – Preventative maintenance			Record keeping P/E	Once every six months	Y
63.7745(a)(3)	Continuous compliance demonstration – bag leak detection system			Record keeping P/E	Once every six months	Y
63.7745(a)(4)	Continuous compliance demonstration – baghouse corrective action			Record keeping P/E	Once every six months	Y
63.7745(b)	Maintain operation and maintenance plan onsite					Y
63.7746(a)	Deviations	Report deviations from emissions limitations, work practice standards, and operation and maintenance requirements, including startup, shutdown, malfunction	63.7746(a)	Record keeping P/E	Once every six months	Y
63.7746(b)	Startup, shutdown, malfunction deviations are not violations					Y
63.7750	Notification requirements					Y
63.7751	Reporting requirements					Y
63.7752	Recordkeeping requirements					Y
63.7753	Recordkeeping requirements (5 years)					Y
63.7760	Table 1: Applicability of General Provisions (Subpart A)					Y
63.7761	Delegation					Y
63.7765	Definitions					Y
BAAQMD Condition #23650						

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
Part 1	Abatement requirement with A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5 (basis: Cumulative Increase)					Y
Part 4	A-21 Baghouse #5 outlet grain loading limit (basis: cumulative increase)	FILTERABLE PARTICULATE 0.01 gr/dscf	CAM Condition #25039, Part 13	Bag leak detector C	Once every six months	Y
Part 6	Recordkeeping requirement (basis: Regulation 2-1-403)					Y
Part 7	Source test requirement for VOC every 5 years (basis: Regulation 2-1-403)					Y
Part 8	Iron cast in sand molds facility limit (Basis: Cumulative Increase)	Iron casting ≤ 36,000 tons/any consecutive 12-month period	BAAQMD Condition #2237, Part 6	Record keeping P/M	Once every six months	Y
CAM Condition #25039						
For A-14 and A-18						
Part 1	Definition of exceedance: OPACITY Ringelmann 1.0 < 3 min/hr (Basis: 40 CFR Part 64.6(c)(2))					Y
Part 2	Definitions of excursion: i) any visible emissions (M22); or iii) Pressure drop less than 2 inches or greater than 10 inches water column (Basis: 40 CFR Part 64.6(c)(2))					Y
Part 3	Pressure gauge installation requirement (Basis: 40 CFR Part 64.6(c)(1))					Y
Part 4	Indicator range for pressure gauges: 2 to 10 inches of water column (40 CFR Part 64.3(a)(2))					Y
Part 5	Pressure gauge reading - Daily (Basis: 40 CFR Part 64.6(c)(3); 40 CFR Part 64.3(b)(4)(iii))					Y
Part 6	Pressure gauge calibration (Basis: 40 CFR Part 64.3(b)(3) and (b)(2))					Y
Part 7	Procedures for excursion (Basis: 40 CFR Parts 64.6(c)(3), 64.7(d)(2), 64.8)					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
Part 8	Method 9 observation requirement after 2 or more excursions at the same abatement device occur within 2 weeks (Basis: 40 CFR Part 64.6(c)(3); 40 CFR Part 64.3(b)(4)(iii))					Y
Part 9a	Reporting requirement – excursions, exceedances (Basis: 40 CFR Part 64.6(c)(3) and 40 CFR Part 64.9(a)(2))					Y
Part 9b	Reporting requirement – monitor downtime incidents (Basis: 40 CFR Part 64.6(c)(3) and 40 CFR Part 64.9(a)(2))					Y
Part 10	Inspection of baghouse (Basis: 40 CFR Part 64.6(c)(1)(iii))					Y
Part 11	Source test for compliance with SIP Regulation 6, sections 301, 310 and 311 – every 5 years (Basis: Regulation 2-1-403)					Y
Part 12	Recordkeeping requirements (Basis: Regulation 2-6-501 Recordkeeping)					Y
Part 13	Operation and Maintenance Plan (non-NESHAP) requirement (Basis: 40 CFR Part 64.6(c)(1)(iii))					Y
For A-21						
Part 14a	Definition of exceedance: OPACITY Ringelmann 1.0 < 3 min/hr(Basis: 40 CFR Part 64.6(c)(2))					Y
Part 14b	Definitions of excursion: i) 10 milligrams PM/actual cubic meter for 15 min; or ii) Pressure drop less than 2 inches or greater than 10 inches water column (Basis: 40 CFR Part 64.6(c)(2))					Y
Part 15	Bag leak detector requirement (Basis: 40 CFR Part 64.6(c)(1); 40 CFR Part 64.6(c)(3))					Y
Part 16	Bag leak detector alarm requirement (Basis: 40 CFR Part 64.6(c)(1))					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-2 Pouring, Cooling, Shakeout abated by A-14 Baghouse #2, A-18 Baghouse #4 and A-21 Baghouse #5

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
Part 17	Indicator range: PM<10 milligrams/actual cubic meter (Basis: 40 CFR Part 64.3(a)(2)					Y
Part 18	Visual inspection and testing requirement for bag leak detection sensors (Basis: 40 CFR Part 64.3(b)(3) and (b)(2))					Y
Part 19	Pressure gauge installation requirement (Basis: 40 CFR Part 64.6(c)(1))					Y
Part 20	Indicator range for pressure gauges: 2 to 10 inches of water column (40 CFR Part 64.3(a)(2))					Y
Part 21	Pressure gauge reading - Daily (Basis: 40 CFR Part 64.6(c)(3); 40 CFR Part 64.3(b)(4)(iii))					Y
Part 22	Pressure gauge calibration – quarterly(Basis: 40 CFR Part 64.3(b)(3) and (b)(2))					Y
Part 23	Procedures for excursion (Basis: 40 CFR Parts 64.6(c)(3), 64.7(d)(2), 64.8)					Y
Part 24	Method 9 observation requirement after 2 or more excursions at the same abatement device occur within 2 weeks (Basis: 40 CFR Part 64.6(c)(3); 40 CFR Part 64.3(b)(4)(iii))					Y
Part 25a	Reporting requirement – excursions exceedances (Basis: 40 CFR Part 64.6(c)(3) and 40 CFR Part 64.9(a)(2))					Y
Part 25b	Reporting requirement – monitor downtime incidents(Basis: 40 CFR Part 64.6(c)(3) and 40 CFR Part 64.9(a)(2))					Y
Part 26	Inspection of baghouse and monitoring system (Basis: 40 CFR Part 64.6(c)(1)(iii))					Y
Part 27	Source test for PM and opacity – every 5 years (Basis: Regulation 2-1-403)					Y
Part 28	Recordkeeping requirements (Basis: Regulation 2-6-501 Recordkeeping)					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-3 –Sand Preparation abated by A-15 Baghouse #1

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 6, Rule 1	**Particulate Matter (12/05/07)**					
6-1-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
6-1-305	Visible Particles					Y
6-1-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11	Source Test P/every 5 years	Every 5 years	Y
6-1-311	General Operations	FILTERABLE PARTICULATE $4.10P^{0.67}$ lb/hr where P is process weight, ton/hr	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
6-1-401	Appearance of Emissions					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-3 –Sand Preparation abated by A-15 Baghouse #1

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
6-1-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
SIP Regulation 6	**Particulate Matter and Visible Emissions (09/04/98)**					
6-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
6-305	Visible Particles					Y
6-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
6-311	General Operations	FILTERABLE PARTICULATE $4.10P^{067}$ lb/hr. where P is process weight, ton/hr	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-3 –Sand Preparation abated by A-15 Baghouse #1

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
6-401	Appearance of Emissions					Y
6-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
BAAQMD Condition #2237						
Part 2	Abatement requirement with A-15 Baghouse #1 (Basis: Cumulative Increase)					Y
Part 3	A-15 Baghouse #1 maintenance requirement (Basis: Cumulative Increase)					Y
Part 4	A-15 Baghouse #1 outlet grain loading limit (Basis: Cumulative Increase)	FILTERABLE PARTICULATE 0.04 gr/dscf	BAAQMD Condition #2237, Part 6	Record keeping of Preventative Maintenance P/W	Once every six months	Y
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
Part 5	Monthly good iron casting production record keeping (Basis: Cumulative Increase, BAAQMD Regulation 2-6-501)					Y
Part 9	Sand throughput limit (Basis: Cumulative Increase)	Sand throughput limit ≤ 572,000 tons/any consecutive 12-month period	BAAQMD Condition #2237, Part 10	Record keeping P/M	Once every six months	Y
Part 10	Record keeping requirements (Basis: Regulation 2-1-403)					Y
CAM Condition #25039						
Part 1	Definition of exceedance: OPACITY Ringelmann 1.0 < 3 min/hr (Basis: 40 CFR Part 64.6(c)(2))					Y
Part 2	Definitions of excursion: i) any visible emissions (M22); or					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-3 –Sand Preparation abated by A-15 Baghouse #1

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
	iii) Pressure drop less than 2 inches or greater than 10 inches water column (Basis: 40 CFR Part 64.6(c)(2))					
Part 3	Pressure gauge installation requirement (Basis: 40 CFR Part 64.6(c)(1))					Y
Part 4	Indicator range for pressure gauges: 2 to 10 inches of water column (40 CFR Part 64.3(a)(2))					Y
Part 5	Pressure gauge reading - Daily (Basis: 40 CFR Part 64.6(c)(3); 40 CFR Part 64.3(b)(4)(iii))					Y
Part 6	Pressure gauge calibration (Basis: 40 CFR Part 64.3(b)(3) and (b)(2))					Y
Part 7	Procedures for excursion (Basis: 40 CFR Parts 64.6(c)(3), 64.7(d)(2), 64.8)					Y
Part 8	Method 9 observation requirement after 2 or more excursions at the same abatement device occur within 2 weeks (Basis: 40 CFR Part 64.6(c)(3); 40 CFR Part 64.3(b)(4)(iii))					Y
Part 9a	Reporting requirement – excursions, exceedances (Basis: 40 CFR Part 64.6(c)(3) and 40 CFR Part 64.9(a)(2))					Y
Part 9b	Reporting requirement – monitor downtime incidents (Basis: 40 CFR Part 64.6(c)(3) and 40 CFR Part 64.9(a)(2))					Y
Part 10	Inspection of baghouse (Basis: 40 CFR Part 64.6(c)(1)(iii))					Y
Part 11	Source test for compliance with SIP Regulation 6, sections 301, 310 and 311 – every 5 years (Basis: Regulation 2-1-403)					Y
Part 12	Recordkeeping requirements (Basis: Regulation 2-6-501 Recordkeeping)					Y
Part 13	Operation and Maintenance Plan (non-NESHAP) requirement – includes monitoring, inspection, maintenance, corrective action plan, recordkeeping (Basis:					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements S-3 –Sand Preparation abated by A-15 Baghouse #1						
Applicable Requirement	**Regulation Title or Description of Requirement**	**Limit**	**Monitoring Citation**	**Monitoring & Frequency**	**Reporting**	**Compliance (Y / N)**
	40 CFR Part 64.6(c)(1)(iii))					

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-4 – Wheelabrator Shot Blast (No.1) abated by A-17 Baghouse #3 S-5 Pangborn Shot Blast (No. 2) abated by A-17 Baghouse #3
S-27 Wheelabrator Shot Blast (No. 3) abated by A-17 Baghouse #3 S-30 Inline Shot Blast abated by A-17 Baghouse #3

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 6, Rule 1	**Particulate Matter (12/05/07)**					
6-1-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
6-1-305	Visible Particles					Y
6-1-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
6-1-311	General Operations	FILTERABLE PARTICULATE $4.10P^{0.67}$ lb/hr where P is process weight, ton/hr	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y
			CAM	Source Test	Every 5 years	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-4 – Wheelabrator Shot Blast (No.1) abated by A-17 Baghouse #3 S-5 Pangborn Shot Blast (No. 2) abated by A-17 Baghouse #3
S-27 Wheelabrator Shot Blast (No. 3) abated by A-17 Baghouse #3 S-30 Inline Shot Blast abated by A-17 Baghouse #3

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
			Condition #25039, Part 11	P/Every 5 years		
6-1-401	Appearance of Emissions					Y
6-1-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
SIP Regulation 6	**Particulate Matter and Visible Emissions (09/04/98)**					
6-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
6-305	Visible Particles					Y
6-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring P/D	Once every six months	Y
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
6-311	General Operations	FILTERABLE PARTICULATE 4.10P0.67 lb/hr. where P is process weight, ton/hr	CAM Condition #25039 Part 2	Visible Emissions (M22) P/W	Once every six months	Y
			CAM Condition #25039 Part 5	Pressure drop monitoring	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-4 – Wheelabrator Shot Blast (No.1) abated by A-17 Baghouse #3 S-5 Pangborn Shot Blast (No. 2) abated by A-17 Baghouse #3
S-27 Wheelabrator Shot Blast (No. 3) abated by A-17 Baghouse #3 S-30 Inline Shot Blast abated by A-17 Baghouse #3

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
				P/D		
			CAM Condition #25039, Part 11	Source Test P/Every 5 years	Every 5 years	Y
6-401	Appearance of Emissions					Y
6-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
BAAQMD Condition #10139						
Part 1	S-27 Wheelabrator Shot Blast (No. 3) shot throughput limit (Basis: Cumulative Increase)	Shot blast material ≤ 36 tons/any consecutive 12-month period	BAAQMD Condition #10139, Part 5	Record keeping P/M	Once every six months	Y
Part 2	Abatement requirement with A-17 Baghouse #3 (Basis: Cumulative Increase)					Y
Part 5	S-27 throughput record keeping (Basis: Cumulative Increase, BAAQMD Regulation 2-6-501)					Y
Part 6	S-4 – Wheelabrator Shot Blast (No.1) shot throughput limit (Basis: Regulation 2-1-403)	Shot blast material ≤ 4,600 tons/any consecutive 12-month period	BAAQMD Condition #10139, Part 8	Record keeping P/M	Once every six months	Y
Part 7	S-5 Pangborn Shot Blast (No. 2) shot throughput limit (Basis: Regulation 2-1-403)	Shot blast material ≤2,800 tons/any consecutive 12-month period	BAAQMD Condition #10139, Part 8	Record keeping P/M	Once every six months	Y
Part 8	Record keeping requirements (Basis: Regulation 2-1-403)					Y
BAAQMD Condition #13298						
Part 1	S-30 Blast Cleaning Machine blast media throughput limit (Basis: Cumulative Increase)	Shot blast material ≤ 105 tons/any consecutive 12-month period	BAAQMD Condition #13298 Part 3	Record keeping P/M	Once every six months	Y
Part 2	Abatement requirement with A-17 Baghouse #3 (Basis:					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-4 – Wheelabrator Shot Blast (No.1) abated by A-17 Baghouse #3 S-5 Pangborn Shot Blast (No. 2) abated by A-17 Baghouse #3
S-27 Wheelabrator Shot Blast (No. 3) abated by A-17 Baghouse #3 S-30 Inline Shot Blast abated by A-17 Baghouse #3

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
	Cumulative Increase)					
Part 3	Record keeping requirements (Basis: Regulation 2-1-403)					Y
CAM Condition #25039						
Part 1	Definition of exceedance: OPACITY Ringelmann 1.0 < 3 min/hr (Basis: 40 CFR Part 64.6(c)(2))					Y
Part 2	Definitions of excursion: i) any visible emissions (M22); or iii) Pressure drop less than 2 inches or greater than 10 inches water column (Basis: 40 CFR Part 64.6(c)(2))					Y
Part 3	Pressure gauge installation requirement (Basis: 40 CFR Part 64.6(c)(1))					Y
Part 4	Indicator range for pressure gauges: 2 to 10 inches of water column (40 CFR Part 64.3(a)(2))					Y
Part 5	Pressure gauge reading - Daily (Basis: 40 CFR Part 64.6(c)(3); 40 CFR Part 64.3(b)(4)(iii))					Y
Part 6	Pressure gauge calibration (Basis: 40 CFR Part 64.3(b)(3) and (b)(2))					Y
Part 7	Procedures for excursion (Basis: 40 CFR Parts 64.6(c)(3), 64.7(d)(2), 64.8)					Y
Part 8	Method 9 observation requirement after 2 or more excursions at the same abatement device occur within 2 weeks (Basis: 40 CFR Part 64.6(c)(3); 40 CFR					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-4 – Wheelabrator Shot Blast (No.1) abated by A-17 Baghouse #3 S-5 Pangborn Shot Blast (No. 2) abated by A-17 Baghouse #3
S-27 Wheelabrator Shot Blast (No. 3) abated by A-17 Baghouse #3 S-30 Inline Shot Blast abated by A-17 Baghouse #3

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
	Part 64.3(b)(4)(iii))					
Part 9a	Reporting requirement – excursions, exceedances (Basis: 40 CFR Part 64.6(c)(3) and 40 CFR Part 64.9(a)(2))					Y
Part 9b	Reporting requirement – monitor downtime incidents (Basis: 40 CFR Part 64.6(c)(3) and 40 CFR Part 64.9(a)(2))					Y
Part 10	Inspection of baghouse (Basis: 40 CFR Part 64.6(c)(1)(iii))					Y
Part 11	Source test for compliance with SIP Regulation 6, sections 301, 310 and 311 – every 5 years (Basis: Regulation 2-1-403)					Y
Part 12	Recordkeeping requirements (Basis: Regulation 2-6-501 Recordkeeping)					Y
Part 13	Operation and Maintenance Plan (non-NESHAP) requirement – includes monitoring, inspection, maintenance, corrective action plan, recordkeeping (Basis: 40 CFR Part 64.6(c)(1)(iii))					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-25 Holding Furnace abated by A-25 Fume Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 6, Rule 1	**Particulate Matter (12/05/07)**					
6-1-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	BAAQMD Condition #9668, Part 3	Bag leak detector C	Once every six months	Y
			BAAQMD Condition #9668, Part 8	Source Test P/Every 5 years	Every 5 years	Y
			BAAQMD Condition #9668, Part 5	Record keeping of preventative maintenance P/W	Once every six months	Y
6-1-305	Visible Particles					Y
6-1-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	BAAQMD Condition #9668, Part 3	Bag leak detector C	Once every six months	Y
			BAAQMD Condition #9668, Part 8	Source Test P/Every 5 years	Every 5 years	Y
			BAAQMD Condition #9668, Part 5	Record keeping of preventative maintenance P/W	Once every six months	Y
6-1-311	General Operations	FILTERABLE PARTICULATE $4.10P^{0.67}$ lb/hr where P is process weight, ton/hr	BAAQMD Condition #9668, Part 3	Bag leak detector C	Once every six months	Y
			BAAQMD Condition #9668, Part 8	Source Test P/Every 5 years	Every 5 years	Y
			BAAQMD Condition #9668, Part 5	Record keeping of preventative maintenance P/W	Once every six months	Y
6-1-401	Appearance of Emissions					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-25 Holding Furnace abated by A-25 Fume Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
6-1-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
SIP Regulation 6	**Particulate Matter and Visible Emissions (09/04/98)**					
6-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	BAAQMD Condition #9668, Part 3	Bag leak detector C	Once every six months	Y
			BAAQMD Condition #9668, Part 8	Source Test P/Every 5 years	Every 5 years	Y
			BAAQMD Condition #9668, Part 5	Record keeping of preventative maintenance P/W	Once every six months	Y
6-305	Visible Particles					Y
6-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	BAAQMD Condition #9668, Part 3	Bag leak detector C	Once every six months	Y
			BAAQMD Condition #9668, Part 8	Source Test P/Every 5 years	Every 5 years	Y
			BAAQMD Condition #9668, Part 5	Record keeping of preventative maintenance P/W	Once every six months	Y
6-311	General Operations	FILTERABLE PARTICULATE 4.10P0.67 lb/hr. where P is process weight, ton/hr	BAAQMD Condition #9668, Part 3	Bag leak detector C	Once every six months	Y
			BAAQMD Condition #9668, Part 8	Source Test P/Every 5 years	Every 5 years	Y
			BAAQMD Condition #9668, Part 5	Record keeping of preventative maintenance	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-25 Holding Furnace abated by A-25 Fume Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
				P/W		
6-401	Appearance of Emissions					Y
6-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
BAAQMD Condition #9668						
Part 1	Abatement requirement (basis: cumulative increase)					Y
Part 2	Baghouse maintenance requirement (basis: cumulative increase,)		BAAQMD Condition #9668, Part 5	Preventative maintenance record keeping P/W	Once every six months	Y
Part 3	Broken bag leak detector requirement (basis: cumulative increase)					Y
Part 4	A-25 outlet grain loading limit (basis: cumulative increase)	PM10 0.002 gr/dscf	BAAQMD Condition #9668, Part 3	Bag leak detector C	Once every six months	Y
Part 5	Weekly records of preventive maintenance inspections of A-25 Fume Baghouse (basis:BAAQMD Regulation 6-1-301, BAAQMD Regulation 2-6-501)					Y
Part 6	Gray iron throughput limit (basis: Regulation 2-1-403)	Gray iron throughput ≤ 172,000 ton/any consecutive 12-month period	BAAQMD Condition #9668, Part 7	Record keeping P/M	Once every six months	Y
Part 7	Gray iron throughput record keeping requirement					Y
Part 8	Source testing requirement for PM and opacity					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-28 Storage Silo (Baghouse Dust) abated by A-19 Cupola Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 6, Rule 1	**Particulate Matter (12/05/07)**					
6-1-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y
			BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y
6-1-305	Visible Particles					Y
6-1-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y
			BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y
6-1-311	General Operations	FILTERABLE PARTICULATE 4.10P0.67 lb/hr. where P is process weight, ton/hr	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-28 Storage Silo (Baghouse Dust) abated by A-19 Cupola Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
			BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y
6-1-401	Appearance of Emissions					Y
6-1-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
SIP Regulation 6	**Particulate Matter and Visible Emissions (09/04/98)**					
6-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y
			BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y
6-305	Visible Particles					Y
6-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y
			BAAQMD Condition #9351, Part 11;	Source Test P/Every 5 years	Every 5 years	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-28 Storage Silo (Baghouse Dust) abated by A-19 Cupola Baghouse

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
			CAM Condition #25039, Part 27			
6-311	General Operations	FILTERABLE PARTICULATE 4.10P0.67 lb/hr. where P is process weight, ton/hr	63.7740(b); CAM Condition #25039, Part 15	Bag leak detector C	Once every six months	Y
			CAM Condition #25039, Part 21	Pressure drop monitoring P/D	Once every six months	Y
			BAAQMD Condition #9351, Part 11; CAM Condition #25039, Part 27	Source Test P/Every 5 years	Every 5 years	Y
6-401	Appearance of Emissions					Y
6-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
BAAQMD Condition #10762						
Part 1	Abatement requirement with A-19 (Basis: Cumulative Increase)					Y
Part 6	Throughput limit (basis: Regulation 2-1-403)	Throughput 1500 ton/ any consecutive 12-month period	BAAQMD Condition #10762, Part 7	Record keeping P/M	Once every six months	Y
Part 7	Record keeping requirements (Basis: Regulation 2-1-403)					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-31 Emergency Standby Diesel Generator

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 6, Rule 1	**Particulate Matter (12/05/07)**					
6-1-303.1	Ringelmann Number 2 Limitation	OPACITY Ringelmann 2.0 for < 3 min/hr		N		Y
6-1-305	Visible Particles					Y
6-1-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf		N		Y
6-1-401	Appearance of Emissions					Y
SIP Regulation6	**Particulate Matter and Visible Emissions (09/04/98)**					
6-303.1	Ringelmann Number 2 Limitation	OPACITY Ringelmann 2.0 for < 3 min/hr		N		Y
6-305	Visible Particles					Y
6-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf		N		Y
6-401	Appearance of Emissions					Y
BAAQMD Regulation 9, Rule 1	**Inorganic Gaseous Pollutants: Sulfur Dioxide (3/15/1995)**					
9-1-301	Ground Level Concentration	SO2 < 0.5 ppm continuously for 3 consecutive minutes or 0.25 ppm averaged over 60 consecutive minutes, or 0.05 ppm averaged over 24 hours.		N		Y
9-1-304	Fuel Burning (Liquid and Solid Fuels)	Sulfur content of liquid fuel ≤ 0.5% by weight		N		Y
9-1-602	Sulfur Content of Fuels					Y
AQMD Regulation 9, Rule 8	**Inorganic Gaseous Pollutants: NOx and CO from Stationary Internal Combustion Engines (7/25/2007)**					
9-8-110.5	Exemption Emergency Standby engines					Y
9-8-330	Emergency Standby Engines, Hours of Operation					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-31 Emergency Standby Diesel Generator

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
9-8-330.1	Emergency Standby Engines, Hours of Operation	Unlimited hours for emergency use				Y
9-8-330.2	Emergency Standby Engines, Hours of Operation (until 1/01/2012)	Reliability-related activities limited to 100 hours per calendar year	BAAQMD Condition #19947, part 1	Log/Record Keeping P/M	Once every six months	Y
9-8-330.3	Emergency Standby Engines, Hours of Operation (effective 1/01/2012)	Reliability-related activities limited to 50 hours per calendar year	BAAQMD Condition # 19947, part 1	Log/Record Keeping P/M	Once every six months	Y
9-8-530	Emergency Standby Engines, Monitoring and Recordkeeping					Y
SIP Regulation 9, Rule 8	**Inorganic Gaseous Pollutants: NOx and CO from Stationary Internal Combustion Engines (12/15/1997)**					
9-8-101	Exclusion: Emergency Standby Engines					Y
40 CFR Part 63, Subpart ZZZZ	**National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (3/09/11)**					
63.6580	What is the purpose of subpart ZZZZ?					Y
63.6585(a), (b)	Am I subject to this subpart? – stationary RICE located at a major source of HAPs					Y
63.6590(a)(1)(i)	What parts of my plant does this subpart cover? – existing stationary RICE > 500hp at a major source of HAPs and commenced construction prior to December 19, 2002 (initial operation 2/15/2001)					Y
63.6590(b)(3)(iii)	Stationary RICE subject to limited requirements –existing emergency stationary RICE > 500hp located at a major source of HAP emissions.					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements S-31 Emergency Standby Diesel Generator						
Applicable Requirement	**Regulation Title or Description of Requirement**	**Limit**	**Monitoring Citation**	**Monitoring & Frequency**	**Reporting**	**Compliance (Y / N)**
	Exemption from requirements of this subpart and of subpart A of this part					
63.6600(c)	Emission limitations – stationary RICE > 500hp located at a major source of HAPs Exemption from emission limitations in Tables 1a, 2a, 2c, 2d, and operating limitations in Tables 1b, 2b– emergency stationary RICE > 500hp located at a major source of HAPs					Y
63.6625	What are my monitoring, installation, collection, operation, and maintenance requirements? None for existing emergency stationary RICE > 500hp located at a major source of HAP emissions					Y
63.6640(e)	Continuous compliance demonstration Exemption – emergency stationary RICE > 500hp located at a major source of HAPs					Y
63.6640(f)(2)	Requirements for emergency stationary RICE > 500hp located at a major source of HAPs installed before June 12, 2006					Y
63.6640 (f)(2)(i)	No limit on emergency use					Y
63.6640 (f)(2)(ii)	Maintenance and readiness testing operation recommended by manufacturer/vendor/insurance company – minimize, but no limit					Y
63.6640 (f)(2)(iii)	Additional 50 hours operation for non-emergency situations (not for peak shaving or to generate income)	HOURS OF OPERATION – non-emergency, non-maintenance and testing				Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-31 Emergency Standby Diesel Generator

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
		50 hours/year				
63.6645(a)(5)	What notifications must I submit and when? Exemption for existing stationary emergency RICE					Y
63.6655(e)(2)	What records must I keep? – maintenance records					Y
	demonstrating operation and maintenance according to your maintenance plan					Y
63.6660	In what form and how long must I keep my records? 63.10(b)(1) format; 5 years					Y
63.6665	What General Provisions apply to me? Exemption – emergency stationary RICE > 500hp located at a major source of HAPs except initial notification					Y
63.6670	Who implements and enforces this subpart?					Y
63.6675	What definitions apply to this subpart?					Y
BAAQMD Condition # 19947						
Part 1	10.6 hours of reliability related testing and unlimited hours of emergency standby power [Basis: Regulation 2, Rule 5; "Stationary Diesel Engine ATCM" CA Code of Regulations, Title 17, section 93115.6(b)(3)(A)(1)(a)]	10.6 hours/year	BAAQMD Condition # 19947, Part 4	Log/Record keeping P/M	Every six months	Y
Part 2	Operating conditions Basis: [BAAQMD Regulation 9-8-330, "Stationary Diesel Engine ATCM" CA Code of Regulations, Title 17, section 93115.6(b)(3)(A)(1)(a)]					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements S-31 Emergency Standby Diesel Generator						
Applicable Requirement	**Regulation Title or Description of Requirement**	**Limit**	**Monitoring Citation**	**Monitoring & Frequency**	**Reporting**	**Compliance (Y / N)**
Part 3	Installation of a non-resettable totalizing hour meter [Basis: BAAQMD Regulation 9-8-530, "Stationary Diesel Engine ATCM" CA Code of Regulations, Title 17, section 93115.10(e)(1)]					Y
Part 4	Record keeping requirements [Basis: BAAQMD Regulation 9-8530, 2-6-501, "Stationary Diesel Engine ATCM" CA Code of Regulations, Title 17, section 93115.10(g)]					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-32 Flow Jet Pipe Labeler

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 8, Rule 4	**General Solvent and Surface Coating Operations (10/16/02)**					
8-4-302.3	Solvents and Surface Coating Requirements	VOC content of coatings ≤ 3.5 lb/gallon of coating as applied	BAAQMD Condition #21322, Part 4	Record keeping P/M	Once every six months	Y
8-4-312	Solvent Evaporative Loss Minimization					Y
8-4-501	Record keeping requirements					Y
8-4-603	Analysis of Samples					Y
BAAQMD Regulation 8, Rule 19	**Surface Preparation and Coating of Miscellaneous Metal Parts and Products (10/16/02)**					
8-19-117	Exemption, Stencil Coatings					Y
NESHAP 40 CFR Part 63, Subpart MMMM	**National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products (04/20/06)**					
63.3880	What is the purpose of this subpart?					Y
63.3881(a),(b)	Am I subject to this subpart? – facility					Y
63.3882(a), (b)(1)	What parts of my plant does this subpart cover? – coating operation					Y
63.3883(b)	Initial compliance date (January 2, 2007)					Y
63.3890(b)(1)	Emission limit – existing facility general use coating	Organic HAP ≤ 2.6 lb/gal of coating solids used during each 12-month compliance period	§63.3930	Record keeping P/M	Every six months	Y
63.3891(a)	Emission limit option – compliant material option	Organic HAP content of each coating used is ≤ §63.3890 (2.6 lb HAP/gal coating solids) and each thinner, additive, and cleaning material contains no organic HAP	§63.3930	Record keeping P/M	Every six months	Y
63.3892	Operating limit – Exemption for compliant					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-32 Flow Jet Pipe Labeler

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
	material option					
63.3893	Work practice standards – Exemption for compliant material option					Y
63.3900(a)(1)	General requirements – compliant material option	Comply with §63.3890	§63.3930	Record keeping P/M	Every six months	Y
63.3910(b)	Initial Notification –January 1, 2004					Y
63.3910(c)(1)-(3)	Notification of compliance status – name, address, responsible official, reporting period dates					Y
63.3910(c)(4)	Notification of compliance status – Identification of compliance option(s)					Y
63.3910(c)(5)	Notification of compliance status – Achievement of emission limitations for the initial compliance period					Y
63.3910(c)(6)	Notification of compliance status – Deviation reports					Y
63.3910(c)(7)	Notification of compliance status – Data (mass fraction of HAPs, volume fraction of coating solids, density, waste material and mass of HAPs)					Y
63.3910 (c)(8)(i)	Notification of compliance status – calculation of lb HAP emitted per gallon of coating solids					Y
63.3920(a)	Reporting requirements – semiannual compliance reports					Y
63.3930	Record keeping requirements					Y
63.3931	Records retention – 5 years total, 2 years onsite					Y
63.3940	Initial Compliance demonstration date - §63.3883					Y
63.3941	Initial Compliance demonstration methods					Y
63.3942(a)	Continuous Compliance demonstration	Comply with §63.3890	§63.3930	Record keeping P/M	Every six months	Y
63.3942(b)	Deviation definition for compliant material					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-32 Flow Jet Pipe Labeler

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
	option					
63.3942(c),(d)	Continuous Compliance demonstration – semiannual reports, records					Y
63.3980	Delegation					Y
63.3981	Definitions					Y
Table 2 to Subpart MMMM of Part 63	Applicability of General Provisions					Y
Table 3 to Subpart MMMM of Part 63	Default Organic HAP Mass Fraction for Solvents and Solvent Blends					Y
BAAQMD Condition #21322						
Part 1	Material throughput limit - Ink (Basis: Cumulative Increase)	Ink throughput ≤ 2,500 gallons/any consecutive 12-month period	BAAQMD Condition #21322, Part 4	Record keeping P/M	Once every six months	Y
Part 2	Material throughput limit – Cleanup Solvent (Basis: Cumulative Increase)	Cleanup Solvent ≤ 1,000 gallons/any consecutive 12-month period	BAAQMD Condition #21322, Part 4	Record keeping P/M	Once every six months	Y
Part 3	Material Options – POC limit, NPOC limit (Basis: Cumulative Increase)	POC = 0 lb/year NPOC ≤ 22,880 lb/ any consecutive 12-month period	BAAQMD Condition #21322, Part 4	Record keeping P/M	Once every six months	Y
Part 4	Record keeping requirements (Basis: Cumulative Increase, Regulation 2-5)					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements S-14 Fittings Dip Barrel
S-34 Pipe Finishing Dip Tank (P2, P3) S-35 Pipe Finishing Dip Tank (P4)
S-36 Pipe Finishing Dip Tank (P5, P6)
S-43 Pipe Finishing Dip Tank (P1)

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 8, Rule 19	**Surface Preparation and Coating of Miscellaneous Metal Parts and Products (10/16/02)**					
8-19-302.2	Solvents and Surface Coating Requirements	VOC content of coatings 2.8 lb/gallon of coating applied, excluding water	BAAQMD Condition #24639, Part 11	Record keeping P/M	Once every six months	Y
8-19-320	Solvent Evaporative Loss Minimization					Y
8-19-501	Record keeping requirements					Y
8-19-601	Analysis of Samples					Y
NESHAP 40 CFR Part 63, Subpart MMMM	**National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products (04/20/06)**					
63.3880	Purpose					Y
63.3881(a),(b)	Applicability - facility					Y
63.3882(a), (b)(1)	Applicability – coating operation					Y
63.3883(b)	Initial compliance date (January 2, 2007)					Y
63.3890(b)(1)	Emission limit – existing facility general use coating	Organic HAP ≤ 2.6 lb/gal of coating solids used during each 12-month compliance period	§63.3930	Record keeping P/M	Every six months	Y
63.3891(a)	Emission limit option – compliant material option	Organic HAP content of each coating used is ≤ §63.3890 (≤ 2.6 lb/gal of coating solids)and each thinner, additive, and cleaning material contains no organic HAP	§63.3930	Record keeping P/M	Every six months	Y
63.3892	Operating limit – Exemption for compliant material option					Y
63.3893	Work practice standards –					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements S-14 Fittings Dip Barrel S-34 Pipe Finishing Dip Tank (P2, P3) S-35 Pipe Finishing Dip Tank (P4) S-36 Pipe Finishing Dip Tank (P5, P6) S-43 Pipe Finishing Dip Tank (P1)

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
	Exemption for compliant material option					
63.3900(a)(1)	General requirements – compliant material option	Comply with §63.3890	§63.3930	Record keeping P/M	Every six months	Y
63.3910(b)	Initial Notification – January 1, 2004					Y
63.3910(c)(1)-(3)	Notification of compliance status – name, address, responsible official, reporting period dates					Y
63.3910(c)(4)	Notification of compliance status – Identification of compliance option(s)					Y
63.3910(c)(5)	Notification of compliance status – Achievement of emission limitations for the initial compliance period					Y
63.3910(c)(6)	Notification of compliance status – Deviation reports					Y
63.3910(c)(7)	Notification of compliance status – Data (mass fraction of HAPs, volume fraction of coating solids, density, waste material and mass of HAPs)					Y
63.3910 (c)(8)(i)	Notification of compliance status – calculation of lb HAP emitted per gallon of coating solids					Y
63.3920(a)	Reporting requirements – semiannual compliance reports					Y
63.3930	Record keeping requirements					Y
63.3931	Records retention – 5 years total, 2 years onsite					Y
63.3940	Initial Compliance demonstration date - §63.3883					Y
63.3941	Initial Compliance demonstration methods					Y
63.3942(a)	Continuous Compliance demonstration	Comply with §63.3890	§63.3930	Record keeping P/M	Every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements S-14 Fittings Dip Barrel
S-34 Pipe Finishing Dip Tank (P2, P3) S-35 Pipe Finishing Dip Tank (P4)
S-36 Pipe Finishing Dip Tank (P5, P6)
S-43 Pipe Finishing Dip Tank (P1)

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.3942(b)	Deviation definition for compliant material option					Y
63.3942(c),(d)	Continuous Compliance demonstration – semiannual reports, records					Y
63.3980	Delegation					Y
63.3981	Definitions					Y
Table 2 to Subpart MMMM of Part 63	Applicability of General Provisions					Y
Table 3 to Subpart MMMM of Part 63	Default Organic HAP Mass Fraction for Solvents and Solvent Blends					Y
BAAQMD Condition #24639	**For S-34, S-35, S-36, S-43**					
Part 1	Material throughput limit for S-34, S-35, S-36 and S-43 combined (Basis: Cumulative Increase, Offsets, Toxics)	Synthetic asphalt pipe coating throughput ≤ 251,442 gallons (1,090 tons)/any consecutive 12-month period	BAAQMD Condition #24639, Part 11	Record keeping P/M	Once every six months	Y
Part 2	Material throughput limit for S-43 (Basis: Cumulative Increase)	Synthetic asphalt pipe coating throughput ≤ 2,000 gallons/any consecutive 12-month period	BAAQMD Condition #24639, Part 11	Record keeping P/M	Once every six months	Y
Part 3	Specification of material - Synthetic asphalt pipe coating (Basis: Cumulative Increase)	VOC limit ≤ 0.04 lb/gallon	BAAQMD Condition #24639, Part 11	Record keeping P/M	Once every six months	Y
Part 4	Abatement requirement – S-34, S-35, S-36 abated by A35 and A-36 (Basis: Cumulative Increase)					Y
Part 5	A-35 and A-36 pressure gauge and operation and maintenance requirement (Basis: Cumulative Increase)					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements S-14 Fittings Dip Barrel S-34 Pipe Finishing Dip Tank (P2, P3) S-35 Pipe Finishing Dip Tank (P4) S-36 Pipe Finishing Dip Tank (P5, P6) S-43 Pipe Finishing Dip Tank (P1)

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
Part 6	Hot dip operating temperature limit (S-34, S-35, S-36, S-43) (Basis: Cumulative Increase, Toxics)	Coating Temperature Limit ≤ 500 degrees F	BAAQMD Condition #24639, Part 7	Record keeping P/M	Once every six months	Y
Part 7	Temperature measuring and recording device requirement for each S-34, S-35, S-36, S-43					Y
Part 8	Prohibition on cleanup solvent (Basis: Cumulative Increase)					Y
Part 9	Odor Abatement Plan requirement for S-43 if one District-confirmed odor complaint					Y
Part 10	Comprehensive Odor Abatement Plan requirement if public nuisance under BAAQMD 1-301					Y
Part 11	Record keeping requirements of net usage of asphalt coating at each S-34, S-35, S-36, S-43 (Basis: Record keeping)					Y
Part 11a	Record keeping requirements Operating hours of S-34, S35, S-36, S-43 (Basis: Record keeping)					Y
Part 11b	Record keeping requirements Operating hours of A-35 and A-36 (Basis: Record keeping)					Y
Part 11c	Maintenance Records for A-35 and A-36 (Basis: Record keeping)					Y
Part 12	Shutdown requirement for cutback asphalt dip tanks (Basis: Contemporaneous emission reduction credits)					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-38 Vertical Asphalt Storage Tank #1 (exempt)
S-39 Vertical Asphalt Storage Tank #2 (exempt)

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 2, Rule 1						
2-1-123.3.7	Exemption from permit requirements (storage of asphalt with a sulfur content < 0.5%)					Y
BAAQMD Regulation 8, Rule 5	**Storage of Organic Liquids (10/18/06)**					
8-5-117	Limited Exemption, Low Vapor Pressure (≤ 0.5 psia)					Y
SIP Regulation 8, Rule 5	**Storage of Organic Liquids (06/05/03)**					
8-5-117	Limited Exemption, Low Vapor Pressure (≤ 0.5 psia)					Y
NESHAP 40 CFR Part 63, Subpart MMMM	**National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products (04/20/06)**					
63.3880	Purpose					Y
63.3881(a),(b)	Applicability - facility					Y
63.3882(a), (b)(2)	Applicability – storage containers and mixing vessels of coatings, thinners					Y
63.3883(b)	Initial compliance date (January 2, 2007)					Y
63.3893	Work practice standards – Exemption for compliant material option					Y
63.3910(b)	Initial Notification – January 1, 2004					Y
63.3910(c)(1)-(3)	Notification of compliance status – name, address, responsible official, reporting period dates					Y
63.3910(c)(4)	Notification of compliance status – Identification of compliance option(s)					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-38 Vertical Asphalt Storage Tank #1 (exempt)
S-39 Vertical Asphalt Storage Tank #2 (exempt)

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.3910(c)(5)	Notification of compliance status – Achievement of emission limitations for the initial compliance period					Y
63.3910(c)(6)	Notification of compliance status – Deviation reports					Y
63.3910(c)(7)	Notification of compliance status – Data (mass fraction of HAPs, volume fraction of coating solids, density, waste material and mass of HAPs)					Y
63.3910 (c)(8)(i)	Notification of compliance status – calculation of lb HAP emitted per gallon of coating solids					Y
63.3920(a)	Reporting requirements – semiannual compliance reports					Y
63.3930	Record keeping requirements					Y
63.3931	Records retention – 5 years total, 2 years onsite					Y
63.3942(b)	Deviation definition for compliant material option					Y
63.3942(c),(d)	Continuous Compliance demonstration – semiannual reports, records					Y
63.3980	Delegation					Y
63.3981	Definitions					Y
Table 2 to Subpart MMMM of Part 63	Applicability of General Provisions					Y
Table 3 to Subpart MMMM of Part 63	Default Organic HAP Mass Fraction for Solvents and Solvent Blends					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-46 – Sand Storage Bunker
S-47 – Storage Piles S-50 Slurry Mix Stations

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 6, Rule 1	**Particulate Matter (12/05/07)**					
6-1-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr				Y
6-1-305	Visible Particles					Y
6-1-311	General Operations	FILTERABLE PARTICULATE $4.10P^{0.67}$ lb/hr where P is process weight, ton/hr				Y
6-1-401	Appearance of Emissions					Y
6-1-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y
SIP Regulation 6	**Particulate Matter and Visible Emissions (09/04/98)**					
6-301	Ringelmann 1.0 Limitation	OPACITY Ringelmann 1.0 < 3 min/hr				Y
6-305	Visible Particles					Y
6-310	Particulate Weight Limitation	FILTERABLE PARTICULATE 0.15 gr/dscf				Y
6-311	General Operations	FILTERABLE PARTICULATE $4.10P^{0.67}$ lb/hr. where P is process weight, ton/hr				Y
6-401	Appearance of Emissions					Y
6-601	Particulate Matter, Sampling, Sampling Facilities, Opacity Instruments and Appraisal of Visible Emissions					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements S-51 Specialty Finishing Paint Dip Tanks						
Applicable Requirement	**Regulation Title or Description of Requirement**	**Limit**	**Monitoring Citation**	**Monitoring & Frequency**	**Reporting**	**Compliance (Y / N)**
BAAQMD Regulation 8, Rule 19	**Surface Preparation and Coating of Miscellaneous Metal Parts and Products (10/16/02)**					
8-19-302.2	Solvents and Surface Coating Requirements	VOC content of coatings 2.8 lb/gallon of coating applied, excluding water	BAAQMD Condition #24639, Part 11	Record keeping P/M	Once every six months	Y
8-19-320	Solvent Evaporative Loss Minimization					Y
8-19-501	Record keeping requirements					Y
8-19-601	Analysis of Samples					Y
NESHAP 40 CFR Part 63, Subpart MMMM	**National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products (04/20/06)**					
63.3880	Purpose					Y
63.3881(a),(b)	Applicability - facility					Y
63.3882(a), (b)(1)	Applicability – coating operation					Y
63.3883(b)	Initial compliance date (January 2, 2007)					Y
63.3890(b)(1)	Emission limit – existing facility general use coating	Organic HAP ≤ 2.6 lb/gal of coating solids used during each 12-month compliance period	§63.3930	Record keeping P/M	Every six months	Y
63.3891(a)	Emission limit option – compliant material option	Organic HAP content of each coating used is ≤ §63.3890 (≤ 2.6 lb/gal of coating solids)and each thinner, additive, and cleaning material contains no organic HAP	§63.3930	Record keeping P/M	Every six months	Y
63.3892	Operating limit – Exemption for compliant					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-51 Specialty Finishing Paint Dip Tanks

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
	material option					
63.3893	Work practice standards – Exemption for compliant material option					Y
63.3900(a)(1)	General requirements – compliant material option	Comply with §63.3890	§63.3930	Record keeping P/M	Every six months	Y
63.3910(b)	Initial Notification – January 1, 2004					Y
63.3910(c)(1)-(3)	Notification of compliance status – name, address, responsible official, reporting period dates					Y
63.3910(c)(4)	Notification of compliance status – Identification of compliance option(s)					Y
63.3910(c)(5)	Notification of compliance status – Achievement of emission limitations for the initial compliance period					Y
63.3910(c)(6)	Notification of compliance status – Deviation reports					Y
63.3910(c)(7)	Notification of compliance status – Data (mass fraction of HAPs, volume fraction of coating solids, density, waste material and mass of HAPs)					Y
63.3910 (c)(8)(i)	Notification of compliance status – calculation of lb HAP emitted per gallon of coating solids					Y
63.3920(a)	Reporting requirements – semiannual compliance reports					Y
63.3930	Record keeping requirements					Y
63.3931	Records retention – 5 years total, 2 years onsite					Y
63.3940	Initial Compliance demonstration date - §63.3883					Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-51 Specialty Finishing Paint Dip Tanks

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
63.3941	Initial Compliance demonstration methods					Y
63.3942(a)	Continuous Compliance demonstration	Comply with §63.3890	§63.3930	Record keeping P/M	Every six months	Y
63.3942(b)	Deviation definition for compliant material option					Y
63.3942(c),(d)	Continuous Compliance demonstration – semiannual reports, records					Y
63.3980	Delegation					Y
63.3981	Definitions					Y
Table 2 to Subpart MMMM of Part 63	Applicability of General Provisions					Y
Table 3 to Subpart MMMM of Part 63	Default Organic HAP Mass Fraction for Solvents and Solvent Blends					Y
BAAQMD Condition # 25748	**For S-51**					
Part 1	Material throughput limit for S-51 (Basis: Cumulative Increase)	1000 gallon rust inhibitor and 500 gallon of grey/any consecutive 12-month period	BAAQMD Condition # 25748, Part 3	Record keeping P/M	Once every six months	Y

Source-specific Applicable Requirements, Applicable Limits & Compliance Monitoring Requirements
S-52 No Bake Molding System

Applicable Requirement	Regulation Title or Description of Requirement	Limit	Monitoring Citation	Monitoring & Frequency	Reporting	Compliance (Y / N)
BAAQMD Regulation 8, Rule 4	**General Solvent and Surface Coating Operations (10/16/02)**					
8-4-302.3	Solvents and Surface Coating Requirements	VOC content of coatings ≤3.5 lb/gallon of coating as applied	BAAQMD Condition #21322, Part 4	Record keeping P/M	Once every six months	Y
8-4-312	Solvent Evaporative Loss Minimization					Y
8-4-501	Record keeping requirements					Y
8-4-603	Analysis of Samples					Y
BAAQMD Condition # 25437	**For S-52**					
Part 1	Throughput limit (Basis: Cumulative Increase)	Techniset binder limit ≤ 43,880 gallons combined ≤ 251,442 gallons during any consecutive 12month period	BAAQMD Condition # 25437, Part 3 and 4	Record keeping P/M	Once every six months	Y
Part 2	Abatement Requirement by S-1 and A-21 and A-25		63.7740(a); BAAQMD Condition #9351, Part 2	Temperature monitor C	Once every six months	Y